

## **Kensington® Collection: Dura-Luster Floors 3/8", 3/4" & 5/16"**

### **Bruce Hardwood Floors**

16803 Dallas Parkway  
Dallas, TX 75248  
Phone 800-722-4647  
Fax 214-887-2110

09640/BRU  
BuyLine 4923

### **3/4" Solid Oak Strip and Plank**

#### **a. Laurel™ Strip**

Random lengths and a standard 2-1/4" width. Eased edges with square ends. Tongue and groove.

Size: 3/4" x 2-1/4"

CB-910 White Oak Natural  
CB-921 Natural  
CB-922 Spice  
CB-923 Winter White  
CB-924 Gunstock  
CB-926 Butterscotch  
CB-927 Saddle

#### **b. Valley View™ Plank**

Random lengths and a standard 3-1/4" width. Eased edges with square ends. Tongue and groove.

Size: 3/4" x 3-1/4"

CB-931 Natural  
CB-934 Gunstock

#### **c. Bayport™ Strip**

Random lengths and a standard 2-1/4" width. Square edges and ends. Tongue and groove.

Size: 3/4" x 2-1/4"

CB-820 Auburn  
CB-821 Natural  
CB-822 Spice  
CB-824 Gunstock  
CB-826 Butterscotch  
CB-827 Saddle

### **5/16" Solid Oak Parquet**

#### **d. Sorrento® Parquet**

Single unit contains oak fillets joined with a soft metal spline. Square edges. Size: 5/16" x 12" x 12"

L-92 Mellow  
L-93 Desert  
L-94 Chestnut  
L-95 Quartz

## **3/8" Engineered Oak Strip and Plank**

### **e. Riverside™ Plank**

Random lengths with a standard 3" width. 5-ply engineered oak with square edges and ends. Tongue and groove. Size: 3/8" x 3"

EB-720 Toast

EB-721 Gunstock

EB-723 Ivory White

EB-724 Spice

EB-726 Butterscotch

EB-727 Saddle

### **f. Glen Cove™ Plank**

Random lengths and a standard 3" width. 3-ply engineered oak with eased edges and ends. Tongue and groove. Size: 3/8" x 3"

EB-880 Toast

EB-881 Gunstock

EB-883 Ivory White

EB-884 Spice

EB-886 Butterscotch

EB-887 Saddle

### **g. Springdale™ Plank**

Random lengths with a standard 3" width. 3-ply engineered oak with square edges and ends. Tongue and groove. Size: 3/8" x 3"

EB-520 Toast

EB-521 Gunstock

EB-525 Mellow

EB-526 Butterscotch

EB-527 Saddle

### **h. Summerside™ Strip**

Random lengths and a standard 2-1/4" width. 3-ply engineered oak with square edges and ends. Tongue and groove. Size: 3/8" x 2-1/4"

EB-620 Toast

EB-621 Gunstock

EB-625 Mellow

EB-626 Butterscotch

EB-627 Saddle

## **Warranty:**

All Bruce products carry a Full Lifetime Warranty on Structural Integrity, Adhesive Bond, and Subfloor Moisture Protection.

- First line Benchmark Dura-Luster urethane products carry a Full Five Year Finish Wear Layer Warranty for residential applications.
- Kensington Dura-Luster urethane products carry a Full Three Year Finish Wear Layer Warranty for residential applications.

## **How to Specify Dura-Luster Urethane Finish Floors:**

- A. Flooring shall be Bruce (state name, size and/or width) strip, plank, custom wood tile or parquet in the grade of (specify wood species) with a surface color/finish of (state color item number) as manufactured by Bruce Hardwood Floors, a division of Triangle Pacific Corporation.
- B. Factory finished engineered strip, plank or parquet and solid strip, plank or parquet shall be sanded for a smooth finish and have an ultra violet cured urethane finish.
- C. Installation must be made in accordance with the installation instruction sheets provided in each carton.
- D. Installation of all 3/8", 3-ply products can be either nailed, stapled, or glued using properly recommended tools.
- E. Use Bruce Adhesive for glue-down installation. Bruce Adhesive shall be used for all 3/8" strip, plank, and parquet (5/16" and 3/4"). Adhesive for end fastening 3/4" random planks shall be Bruce Oakbond or PL-400 as recommended by Bruce Hardwood Floors.
- F. Trowel for spreading Bruce adhesive shall be notched as required by Bruce Hardwood Floors.
- G. Nailing Machines: 2" barbed fasteners or approved staples should be used for installing Bruce 3/4" strip or plank flooring, and nailing machines with 1-1/4" cleats should be used for nail-down installation of 3/8" strip or plank as required by Bruce Hardwood Floors.

One inch or longer glue-coated staples should be used with Stanley LHF S3297 stapler for 3/8", 3-ply products as recommended.