

HARTCO® URETHANE PARQUET

A gleaming, high-gloss look for residential use.

Hartco Urethane parquet is recommended for residential use only. Its gleaming finish is easily maintained under normal family living conditions and protects from water spotting and spills.

Urethane parquet is suitable for foyers, living rooms, dining rooms, bedrooms and kitchens, and may be installed on or above grade.

Pledge of Quality Warranty

- Lifetime Structure
- 3-Year Wear
- Pre-Installation

For a copy of the complete warranty, call 1-423-569-8888.

Engineering

Hartco Urethane finish parquet has a high-gloss surface. After sanding, staining and sealing, urethane is applied, followed by a final coat of wax. **It is available with a 1/8" closed-cell foam backing that serves to insulate, deaden sound, provide comfort underfoot as well as a moisture harrier.**

Specifications

Species to be 100% oak, at least 80% of slats quarter-sawn. All hardwood material to be kiln-dried, product moisture content to average 9% (plus or minus 2%). Parquet thickness to be 0.312" (plus 0.005"/minus 0.012").

Each 6" x 6" tile will be square within 0.009" machine-sanded top and bottom surfaces, manufactured with a tapered tongue and

groove system. A minimum of 0.008" spacing between each slat to be provided to compensate for normal expansion.

Four 6" x 6" tiles to be bonded together with a hot melt adhesive to form a smooth-surface 12" x 12" unit. Stain to be rubbed into top surface cell structure, sealed and to receive urethane finish and final coat of wax.

Maintenance

For routine cleaning, use Hartco Easy Clean. Use Hartco Wipe Clean for difficult cleaning needs such as adhesive removal. For routine polishing, use Hartco Total Care and Hartco Guard Wax/Guard Wax White. Use Hartco Easy Tone and/or Touch Up Kit to renew color in worn areas.

Hartco® Flooring Company
300 S. Main Street

Oneida, Tennessee 37841
(423) 569-8888 Fax: 569-9031