

Hartco® Flooring Company

300 S. Main Street
Oneida, Tennessee 37841
(423) 569-8888 Fax: 569-9031

Choosing the right Hartco product.

All Hartco flooring comes with one of three factory finishes. Selecting the optimum finish for a specific installation is a function of the amount of use the floor will get, the look desired, the amount of maintenance anticipated, and the price.

Hartwood™ is Hartco's proprietary name for our acrylic impregnated product. The exclusive Hartwood Thru-Grain process forces acrylic and stain through the wood, resulting in a surface that is truly harder than hardwood, with color that permeates through the wear layer and does not need restaining. Hartwood is so durable it is covered by a 25-year Wear Warranty. Hartwood is recommended for high-traffic commercial and residential installations.

HartGuard® is Hartco's exclusive name for our premium urethane finish. It imparts a glossy sheen, protects from water spotting and spills, and is guaranteed against wear-through for five full years. It is recommended for residential use; its no-wax finish is easily maintained under normal family living conditions.

Hartco Urethane is our standard urethane finish. Its gleaming, high-gloss surface results from a factory finishing process that includes sanding, staining, sealing and an application of tough urethane, followed by a final coat of wax. It is recommended for residential use and is guaranteed against wear-through for three full years.

Hartco floor care and maintenance products.

Hartco provides a complete line of exclusive care and maintenance products created specifically for the cleaning and protection of our various wood floors in commercial and residential installations. Detailed instructions for proper use appear on each product label.

Hartco provides adhesives created specifically for installation of each Hartco flooring. Hartco also recommends nail-down and staple-down systems for some of its products.

Only adhesives, trowels, nail-down systems, and staple-down systems recommended by Hartco should be used when installing Hartco floors.