

Solid Vinyl Tile								
	Physical Characteristics			Recommended Subfloors/Adhesives				
	Size	Gauge	Indentation resistance in pounds per sq. in.	Consult Azrock Information Manual [□] for complete and detailed information				
				Concrete, suspended	Concrete, on grade [§]	Concrete, below grade [§]	APA Plywood suspended	APA Sturd-i-floor ³
Stone Granada	12" x 12"	1/8"	150	Azrock LVT and PVC Flooring Adhesive, Azrock Polyurethane Adhesive ‡	Azrock Polyurethane Adhesive ‡, Azrock LVT and PVC Flooring Adhesive	Azrock Polyurethane Adhesive ‡	Azrock LVT and PVC Flooring Adhesive, Azrock Polyurethane Adhesive	Azrock LVT and PVC Flooring Adhesive, Azrock Polyurethane Adhesive ³
Aegean Stone	12" x 12"	1/8"	150					

³ APA Sturd-i-floor constructed per APA Design/Construction

Guide, Residential and Commercial, Form E30L revised

[§] Moisture test recommended

[□] All Azrock products should be maintained according to the recommended procedures outlined in the current Domco Installation & Maintenance Manual.

[‡] For installation in areas where Azrock Slip Resistant, Luxury Vinyl Tile or Solid Vinyl Tile may be exposed to temperature changes (around freezer and refrigerator areas) and/or frequent surface water (spray from produce areas) we recommend the use of Azrock Polyurethane Adhesive.

Solid Vinyl Tile		Solid Vinyl Tile	
Specifications		Chemicals, Reagents, and Stains	
	Chemical	Five Minutes	24 Hours
SS-T-312B, Type III, Solid Vinyl, ASTM E-648 (NFPA-253), CRF (Critical Radiant Flux) 0.45 or more, ASTM E-84 (NSTA-255) with a flame spread rating of less than 75	Methanol	No stain	No stain
	Acetonitrile	No stain	Slight stain
	Petroleum Ether	No stain	No stain
	Phosphoric Acid	No stain	Moderate Stain
	Ethyl Ether	Trace stain	Trace Stain
	Chloroform	Slight stain	Slight stain
	Acetone	Slight stain	Slight stain
	50% Phosphoric Acid	No stain	Moderate Stain
	Glacial Acetic Acid	Bleaching, slight	Bleaching, severe
Hydrochloric Acid	Bleaching, slight	Bleaching, severe	

Solid Vinyl Tile					
PACKING DATA					
<i>Description</i>	<i>Pieces Per Carton</i>	<i>Square Feet Per Carton</i>	<i>Approximate Pounds Per Carton</i>	<i>Square Meters Per Carton</i>	<i>Approximate Kilograms Per Carton</i>
Aegean Stone & Stone Granada	1/8"	1/8"	1/8"	1/8"	1/8"
12" x 12"	45	45	52	4.18	23.59

Solid Vinyl Tile																		
Light Reflectance Values																		
% 0-9	10-14	15-19	20-24	25-29	30-34	35-39	40-44	45-49	50-54	55-59	60-64	65-69	70-74	75-79	80-84	85-89	90-94	95-100
							SG310 SG320		SG330		SG331 SG350	SG300						