

SECTION 09668

LINOLEUM

- A. Type: Azrock/Linosom™ marbled linoleum consisting of oxidized linseed oil and natural resins mixed with wood or corkflour, limestone, and pigments; 2 m wide by 30 m long.
1. Manufacturer: Azrock Commercial Flooring, a brand of Domco Inc., P.O. Box 354, Florence, Alabama, 35631; Telephone 800-558-2240 (samples) and 800-DOMCOTXx223 (Azrock Technical Assistance); Fax 713-869-5271 (Azrock Technical Assistance).
 2. Standards: ASTM F 1303, Type II, Grade 1, Class B (replacing FS L-F-475A(3), Type II, Grade A); 2 mm [2.5 mm] [3.2 mm] thick; minimum 0.45 CRF per ASTM E 648; maximum smoke density of 450 per ASTM E 662; static load limit of 450 psi or higher; minimum floor slip resistance rating per ASTM D 2047.
 3. Color:
 - a. Umbro (12 colors).
 - b. Veneto (24 colors).

For more comprehensive product information, visit our Web site at www.domco.com

For the Azrock Flooring Consultant in your area, call our **Hotline: 1-800-877-8453** between the hours of 8am and 5pm CST. After hours, just leave us a voice message and we'll get back to you the next business day. If you are calling from outside the United States or Canada, or need technical assistance, call 1-713-869-5811.

For product samples, fill out the Product Sample Order Form in the "Samples" section of our Web site to E-mail your order directly to us or call **1-800-558-2240**. If you are calling from outside the United States or Canada, call (205) 766-0234 ext. 197.

Domco Inc.

Corporate Headquarters

1001 Yamaska Street East
Farnham, Quebec J2N 1J7
Telephone: (514) 293-3173
Fax: (514) 293-6644

Sales and Marketing

4103 Parkway Drive
Florence, AL 35630
Tel: (205) 766-0234
Fax: (205) 766-3381
Website: www.domco.com