

WALLFLOWERS MOLDED RUBBER COVE BASE

Wallflowers Molded Rubber Cove Base is the perfect finishing touch to any environment. Its 32 hues and unparalleled performance make it the choice of designers and builders alike. Applied in a contrasting color to the wallcovering or floor material, Wallflowers adds a new level of pizzazz and craftsmanship to an interior. Plus, the high-grade rubber compound provides superior flexibility for labor-saving installation, and dimensional stability, precise gauging, uniform height, and clean surfaces make it stand out in its class.

FEATURES AND BENEFITS

- * Clean on face and back for easy installation
- * Palette of fresh colors
- * Matte finish
- * High grade rubber
- * Maximum flexibility
- * Superior durability
- * Mar-resistant
- * Uniform height
- * Easily cleaned with mild soap and water
- * Available in set-on for use with carpet, or straight for hard surface flooring

COLOR SELECTION

WF-01 Black Dahlia
WF-02 Bark
WF-03 Charcoal
WF-09 Veiled Brown
WF-014 Medium Gray
WF-015 Rosewood
WF-016 Taupe
WF-017 Putty*
WF-018 Baby's Breath*
WF-020 Neutrail*
WF-021 Canvas*
WF-025 Light Gray
WF-029 Arctic*
WF-030 Meridian Bone
WF-031 Zephyr
WF-032 Dune
WF-033 Doe
WF-035 Delft Pansy
WF-036 Gray
WF-037 Dark Beige
WF-038 Outer Banks
WF-039 Light Brick*
WF-040 Winter Oak*
WF-041 Quarry Red*
WF-042 Desiree*
WF-043 Fjord*

WF-044 Teal
WF-045 River Rock*
WF-058 Blue Shadow
WF-070 Ingot Gray
WF-071 Black/Brown
WF-072 Chocolate

* These colors are only available in 4" height (set-on and straight).

WALLFLOWERS RUBBER COVE BASE

1. PRODUCT NAME

FLEXCO Wallflowers Rubber Cove Base

2. MANUFACTURER

FLEXCO Company
P.O. Box 553
Tuscumbia, AL 35674

Phone: (205) 383-7474
(800) 633-3151 (US)
(800) 223-5930 (AL)

3. PRODUCT DESCRIPTION

Basic Use: FLEXCO Rubber Cove Base is a molded rubber base specifically formulated for use in commercial and residential applications.

Corners: Inside and outside Rubber Cove Base corners are available in 2" and 3-1/4" returns; outside Rubber Cove Base corners are available in 2" returns only.

Limitations: FLEXCO Rubber Cove Base should not be installed over vinyl wall covering or epoxy paint. (Ensure that wall coverings or paints do not extend more than 1/2" below the top of the base.) Fading can occur from heavy direct or glass-filtered sunlight, or heavy ultra-violet light.

Gauge: 1/8"

Sizes: FLEXCO Rubber Cove Base is available in 48" lengths and 120 foot rolls in 2-1/2", 4" and 6" heights.

Styles: FLEXCO Rubber Cove Base is available in 2-1/2", 4" and 6" coved; 2-1/2" and 4" inch straight styles.

Colors: FLEXCO Rubber Cove Base is available in 26 colors. Some colors are available only in 4" heights. Please check the Sweet's Catalog or with a FLEXCO distributor for currently available colors.

4. TECHNICAL DATA

FLEXCO Rubber Cove Base meets Federal Specification SS-W-40A Type I.

5. INSTALLATION

Surface Preparation: Use only on structurally sound surfaces such as plaster, drywall, plywood, paneling and masonry which are clean, dry and free from dust, dirt, wax, grease, loose paint or plaster. Old adhesive, plaster and cement must be thoroughly seasoned. DO NOT APPLY OVER NONPOROUS SURFACES SUCH AS VINYL WALL COVERINGS, LAMINATED MASONITE OR PLASTIC LAMINATES, ETC.

FLEXCO #106 COVE BASE ADHESIVE: FLEXCO #106 Cove Base Adhesive is a strong, easy spreading, non-flammable synthetic polymer emulsion adhesive recommended for FLEXCO Rubber and Vinyl Cove Base installations.

Application: Spread adhesive with a 1/8" notched spreader on back of base or wall surface. Press base firmly into place within 10 minutes after application of adhesive and roll with a hand cove base roller.

Clean-Up: Wet adhesive can be cleaned up with soapy water used sparingly. When dry use a non-flammable cleaner.

Coverage: Approximately 110 sq. ft. per gallon (300-350 lin. ft. of 4" cove base).

6. AVAILABILITY AND COST

Availability: FLEXCO Rubber Cove Base is available through FLEXCO distributors. A list of FLEXCO distributors is available in the current Sweet's Catalog or contact FLEXCO.

Cost: The applied cost of FLEXCO Rubber Cove Base will vary with job conditions, job size and quantities of material. Contact FLEXCO for further information.

7. WARRANTY

LIMITED WARRANTY: Robbins Tire and Rubber Company Inc. hereinafter referred to as FLEXCO, manufactures and markets its floor products under the trade name FLEXCO. FLEXCO products are warranted for a period of one year from date of installation to be free of defects in material and workmanship if installed, maintained and used strictly in accordance with FLEXCO's written instructions available from your dealer or by writing FLEXCO, Attn: Manager, Product Services, P.O. Box 553, Tuscumbia, AL 35674. Notice of any defect must be made in writing to FLEXCO within 30 days after buyer learns of the defect. No merchandise is to be returned prior to FLEXCO's inspection and written approval. Buyer's exclusive remedy against FLEXCO and Dealer for claims arising hereunder for any and all losses and damages resulting from any cause shall be receipt of at FLEXCO's option, either replacement of the defective merchandise or a refund of the sale price of the defective merchandise. Buyer waives all other claims and remedies of any nature. THESE WARRANTIES ARE EXPRESSLY IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. By retaining FLEXCO's merchandise for more than 5 days after receipt of such merchandise, buyer agrees that it accepts the terms of this limited warranty and that there are no warranties or rights beyond those contained herein.

Please contact FLEXCO for specific details on Conductive, Static Dissipative, and Flex-Tuft Tile warranties, 1-800-633-3151.

8. MAINTENANCE

Using a soft cloth, clean with a mild soap and water solution and rinse sparingly with clear water.

9. TECHNICAL SERVICES

Further technical information may be obtained from Flexco. Call 800-633-3151 or 205-383-7474.

10. FILING SYSTEMS

FLEXCO Specifications are available in the Sweet's Catalog, in SPEC-DATA format and on 5-1/4" floppy disk for many computer systems and word processors.