

VINYL COVE BASE

Made of homogeneous vinyl in a complete range of contemporary colors, Flexco's Vinyl Cove Base has a superior finish to assure an attractive juncture of floors and walls. Its flexibility not only makes installation fast and economical, but it helps conceal floor and wall irregularities. Special heat weld formulation vinyl cove base is available on request.

COLOR SELECTION

VC-100 Black
VC-180 White
VC-200 Brown
VC-300 Burnt Umber
VC-500 Light Brown
VC-700 Light Gray
VC-704 Almond
VC-706 Red Sox
VC-708 Purple Shadow
VC-758 Blue Shadow
VC-767 Bleached Almond
VC-772 Southern Gray
VC-120 Beige
VC-185 Oyster White
VC-703 Mauve
VC-400 Tan
VC-600 Gray
VC-250 Russet
VC-705 Fresco
VC-707 Irish Setter
VC-709 Empire
VC-763 Elephant
VC-770 Ingot Gray
VC-850 Dark Gray

Note: Add HW to color name for heat weld formulation (e.g. VC-100 HW, etc.)

1. PRODUCT NAME

FLEXCO Vinyl Cove Base

2. MANUFACTURER

FLEXCO Company
P.O. Box 553
Tuscumbia, AL 35674

Phone: (205) 383-7474
(800) 633-3151 (US)
(800) 223-5930 (AL)

3. PRODUCT DESCRIPTION

Basic Use: FLEXCO Cove Base is a molded vinyl base specifically formulated for use in commercial and residential applications.

Corners: Inside and outside Vinyl Cove Base corners are available with a 2" return.

Limitations: FLEXCO Vinyl Cove Base should not be installed over vinyl wall covering or epoxy paint. (Ensure that wall coverings or paints do not extend more than 1/2 inch below the top of the base.)

Gauge: 1/8", .080"

Sizes: FLEXCO Vinyl Cove Base is available in 48" lengths and 120' rolls.

Styles: FLEXCO Vinyl Cove Base is available in 2-1/2", 4" and 6" cove and straight.

Colors: FLEXCO Vinyl Cove Base is available in 15 colors. Please check the Sweet's Catalog or with a FLEXCO distributor for currently available colors.

4. TECHNICAL DATA

FLEXCO Vinyl Cove Base meets Federal Specification SS-W-40A Type II.

5. INSTALLATION

Surface Preparation: Use only on structurally sound surfaces such as plaster, drywall, plywood, paneling and masonry which are clean, dry and free from dust, dirt, wax, grease, loose paint or plaster. Old adhesive, plaster and cement must be thoroughly seasoned. **DO NOT APPLY OVER NONPOROUS SURFACES SUCH AS VINYL WALL COVERINGS, LAMINATED MASONITE OR PLASTIC LAMINATES, ETC.**

Temperature: Cove should be stored on job site, in a heated area of 70 degrees or more for at least 24 hours. Wall must be clean, dry, smooth and free of extraneous material.

CAUTION: Vinyl cove can be stretched while rolling and will later return to its original length. It is very important to roll the base in one direction and toward the last piece installed. This will tend to force the two sections together and will eliminate stretching.

FLEXCO vinyl cove can be formed around outside corners and mitered for inside corners in the conventional manner by heating and forming on the job. Pre-formed inside and outside corners are available if required.

FLEXCO #106 Cove Base Adhesive: FLEXCO #106 Cove Base Adhesive is a strong, easy spreading, non-flammable synthetic polymer emulsion adhesive recommended for FLEXCO Rubber and Vinyl Cove Base installations.

Application: Spread adhesive with a 1/8" notched spreader on back of base or wall surface. Press base firmly into place within 10 minutes after application of adhesive and roll with a hand cove base roller.

Clean-Up: Wet adhesive can be cleaned up with soapy water used sparingly. When dry use a non-flammable cleaner.

Coverage: Approximately 110 sq. ft. per gallon. (220 lin. ft. of 4" cove base).

6. AVAILABILITY AND COST

Availability: FLEXCO Vinyl Cove Base is available through FLEXCO distributors. A list of FLEXCO distributors is available on the current Sweet's Catalog or contact FLEXCO.

Cost: The applied cost of FLEXCO Vinyl Cove Base will vary with job conditions, job size and quantities of material. Contact FLEXCO for further information.

7. WARRANTY

Limited Warranty: Robbins Tire and Rubber Company, Inc. hereinafter referred to as FLEXCO, manufactures and markets its floor products under the trade name FLEXCO. FLEXCO products are warranted for a period of one year from date of installation to be free of defects in material and workmanship if installed, maintained and used strictly in accordance with FLEXCO's written instructions available from your dealer or by writing FLEXCO, Attn: Manager, Product Services, P.O. Box 553, Tuscumbia, AL 35674. Notice of any defect must be made in writing to FLEXCO within 30 days after buyer learns of the defect. No merchandise is to be returned prior to FLEXCO's inspection and written approval. Buyer's exclusive remedy against FLEXCO and Dealer for claims arising hereunder for any and all losses and damages resulting from any cause shall be receipt of at FLEXCO's option, either replacement of the defective merchandise or a refund of the sale price of the defective merchandise. Buyer waives all other claims and remedies of any nature. THESE WARRANTIES ARE EXPRESSLY IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. By retaining FLEXCO's merchandise for more than 5 days after receipt of such merchandise, buyer agrees that it accepts the terms of this limited warranty and that there are no warranties or rights beyond those contained herein.

Please contact FLEXCO for specific details on Conductive, Static Dissipative, and Flex-Tuft Tile warranties, 1-800-633-3151.

8. MAINTENANCE

Using a soft cloth, clean with a mild soap and water solution and rinse sparingly with clear water.

9. TECHNICAL SERVICES

Further technical information may be obtained from Flexco. Call (800)-633-3151 or (205)-383-7474.

10. FILING SYSTEMS

FLEXCO Specifications are available in the Sweet's Catalog, in SPEC-DATA[®] II format and on 5-1/4" floppy disk for many computer systems and word processors.