

## **Inspired Fields® Premium Inlaid Sheet Vinyl**

13001 - Pastel Tones  
13002 - Cream Tones  
13003 - Peach Medley  
13004 - White Multiflec  
13005 - Beige Multiflec  
13006 - Blue Tones  
13007 - Shadow Tones  
13008 - Willow Tones  
13009 - Woodrose Tones  
13010 - Concorde Medley  
13011 - Spice Multiflec  
13012 - Navy Multiflec  
13013 - Aegean Multiflec  
13014 - Wineberry Medley  
13015 - Rust Multiflec

**For Installation, Specifications, Maintenance and Warranty Information, Call 1-800-FLOOR-85**

**For Product Literature or Samples, Call 1-800-241-2262**

Inlaid sheet vinyl - 6 ft. widths - Heat or chemically welded seams - Excellent stain resistance - Made in U.S.A.

### **Product Specifications**

#### **Gauge**

Wearlayer Nominal Inlaid Thickness, in. (mm) = .068 (1.73)

Overall Nominal Thickness, in. (mm) = .082 (2.08)

#### **Weight**

Average Weight, lbs./sq (kg/sm) = 5.6 (3.04)

#### **Width**

Width, ft.(m) = 6 (1.83)

#### **Recommended Load Limit**

Static Load Limit, p.s.i. (kg/cm<sup>2</sup>) = 125 (8.80)

#### **Reference Specifications**

ASTM Specification F 1303 = Type II, Grade 1, Class A

Federal Specifications L-F475A (3) = Type II, Grade A

Canadian Specifications CCMC Spec. CSA-A126.3 = Grade 1, Type II

HUD/FHA Standards in W/L Thickness (Min. 10 mils) = Exceed

**Fire Test Data**

ASTM E-648 Critical Radiant Flux  $\geq 0.45$  watts/ cm<sup>2</sup> = Passes

ASTM E-662 NBS Smoke 450 or less = Passes

New York State DOS File # 09650-910718-4003 = Passes

**Installation**

Adhesive Type = Mannington Commercial V-81

Spread = Full Spread

Heat Weld - Weld Rods = 35 Solid Colors

Chemical Bond-Seam Sealer = Mannington Commercial MCS 32 with VST-96 Professional Applicator Kit

Install in accordance with Mannington Commercial's written instructions contained in the Mannington Professional Installation Guide.

**Traffic Performance**

Meets the requirements of the Americans with Disabilities Act for static coefficient of friction as manufactured. = Commercial Moderate, Heavy, Extra Heavy

Note: Dirt, wetness, finish selection and maintenance schedule may cause significant variation in actual performance.

**Maintenance**

Maintain in accordance with Mannington Commercial's written procedures contained in the Fields Maintenance and Warranty Brochure.

**Warranty**

Fields Limited 5-Year Commercial Warranty.

**Repeat/Seaming**

Random Repeat

Reverse Sheets for Seaming

Printed colors may vary from actual products. Please refer to actual product samples when making final color selections.

**Architectural Specifications**

Recommended specifications: All floors shown in the finish schedule or listed in the specification shall be Mannington Commercial Fields (Random Fields, Fine Fields, and/or Inspired Fields), manufactured by Mannington Resilient Floors, Salem, New Jersey 08079, color number \_\_\_\_\_ (indicate color number). The product should have an overall gauge of .082" nominal, a wearlayer thickness of .068" nominal, and be available in 6 ft. widths. The vinyl shall be manufactured in accordance with ASTM Specifications F-1303, Type II, Grade 1, Class A or Federal Specification L-F475A (3) as a Type II, Grade A product and shall be asbestos-free. The product shall offer a

Limited 5-Year Commercial Warranty as detailed in the Mannington Commercial Fields Maintenance & Warranty brochure. The recommended adhesive shall be Mannington Commercial V-81. Use either heat-welding with Mannington Commercial Heat-Welding Rods or chemical-sealing using Mannington Commercial MCS 32 Seam Sealer with Professional Applicator Kit VST-96 on all seams. Installation shall be as recommended in the Mannington Professional Installation Guide. Made in the U.S.A.

**For Installation, Specifications, Maintenance and Warranty Information, Call 1-800-FLOOR-85**

**For Product Literature or Samples, Call 1-800-241-2262**

**Mannington Mills, Inc.**

P.O. Box 30  
Salem, New Jersey 08079

**Mannington Mills, Inc.**

P.O. Box 67021  
3200 Erin Mills Parkway  
Mississauga, Ontario L5L 5W9  
Canada