

Festival Product Samples

6440 - Blue Pearl with Amethyst & Jade
6442 - Flint Gray with Taupe & Sand
6445 - Jade Stone with Amber & Spruce
6447 - Driftwood with Sand & Almond
6449 - Sandstone with Taupe & Fawn

For Installation, Specifications, Maintenance and Warranty Information, Call 1-800-FLOOR-85

For Product Literature or Samples, Call 1-800-241-2262

Patterned sheet vinyl - 12 ft. widths - Medium to light commercial traffic - Excellent stain resistance - Made in U.S.A.

Product Specifications

Gauge

Wearlayer Nominal Thickness, in. (mm) = .025 (0.64)
Overall Nominal Thickness, in. (mm) = .085 (2.16)

Weight

Average Weight, lbs./sy (kg/sm) = 3.8 (2.06)

Width

Width, ft. (m) = 12 (3.66)

Recommended Load Limit

Static Load Limit p.s.i. (kg/cm²) = 100 (7.04)

Reference Specifications

Federal Specification L-F-001641, Amend 2 = Class 1, Type III

ASTM Specification F 1303 = Type I, Grade 1, Class A

HUD/FHA Standards in W/L Thickness (Min. 10 mils) = Exceeds

Canadian Specification CCMC Spec. CSA-A126.3 = Type I, Grade 1

Fire Test Data

ASTM E-648 Critical Radiant Flux \geq 0.45 watts/cm² = Passes

ASTM E-662 NBS Smoke 450 or less = Passes

New York State DOS File # = 09650- 900123-2068

Installation

Recommended Adhesive Type = Mannington Commercial V-81

Spread Method = Full Spread

Chemical Bond Seam Sealer = Mannington MCS 32 Seam Sealer with VST-96 Professional Applicator Kit

Install in accordance with Mannington Commercial's written instructions contained in the Mannington Professional Installation Guide.

Traffic Performance

Meets the requirements of the Americans with Disabilities Act for static coefficient of friction as manufactured. = Light to Medium Commercial

Note: Dirt, wetness, finish selection and maintenance schedule may cause significant variation in actual performance.

Maintenance

Maintain in accordance with Mannington Commercial's written procedures contained in the CustomSpec II Maintenance & Warranty brochure.

Warranty

CustomSpec II Limited 5-year Commercial Warranty.

Limited 5-Year AquaLoc® Moisture Protection Warranty Against Damage Caused by Alkali and Moisture.

Repeat/Seaming

Bolero/Diamond Club

Pattern Match = 18" x 18"

Do not reverse.

Duet/Granulaire

Random Repeat

Reverse Sheets for Seaming

Festival

Pattern Match = 36" x 36"

Do not reverse.

Printed colors may vary from actual products. Please refer to actual product samples when making color selections.

Architectural Specifications

Recommended specifications: All floors shown in the finish schedule or listed in the specification shall be Mannington Commercial CustomSpec II, manufactured by Mannington Resilient Floors, Salem, New Jersey 08079, color number _____ (indicate color number). The product shall have an overall gauge of .085" (2.16mm) nominal and a clear wearlayer thickness of .025" (.64mm) nominal, and be available in 12 ft. widths. The product shall be manufactured with a moisture protection carrying a Limited 5-Year Commercial Warranty against discoloration from mold, mildew and alkali. The vinyl shall be manufactured in accordance with ASTM Specification F-1303, Type I, Class 1, Class A or Federal Specification LF-001641, Amend. 2, as a Class 1, Type

III product and shall be asbestos-free. The product shall offer a Limited 5-Year Commercial Warranty against manufacturing defects as detailed in the Mannington Commercial CustomSpec II Maintenance & Warranty brochure. The recommended adhesive shall be Mannington Commercial V-81. Seams to be chemically sealed using Mannington MCS-32 seam Sealer and Professional Applicator Kit VST-96. Installation shall be as recommended in the Mannington Professional Installation Guide. Made in the U.S.A.

For Installation, Specifications, Maintenance and Warranty Information, Call 1-800-FLOOR-85

For Product Literature or Samples, Call 1-800-241-2262

Mannington Mills, Inc.

P.O. Box 30

Salem, New Jersey 08079

Mannington Mills, Inc.

P.O. Box 67021

3200 Erin Mills Parkway

Mississauga, Ontario L5L 5W9

Canada