

Essentials™ VCT Product Samples

121 - Silver White
111 - Dalmatian
122 - Glacier
129 - Putty
131 - Oyster White
127 - Warm Beige
137 - Sandrift
133 - Almondine
107 - Bisque
113 - Cornsilk
103 - Goldenrod
123 - Wheat
117 - Fawn
138 - Woodrose
136 - Peaches & Cream
126 - Clay
130 - Wedgewood
124 - Evening Shadows
114 - Wood Violet
160 - Hyacinth
135 - Seaspray
140 - Caribbean
165 - Teal
120 - Horizon

For Installation, Specifications, Maintenance and Warranty Information, Call 1-800-FLOOR-85

For Product Literature or Samples, Call 1-800-241-2262

Vinyl Composition Tile - Through-pattern construction - Moderate to extra-heavy traffic - Made in U.S.A.

Product Specifications

Gauge

Overall Nominal Thickness, in. (mm) = .125 (3.18)

Package/Count

45/ctn

Weight

Average Weight

Lbs. per carton (kg/carton) = 65 (29.5)

Lbs. per tile (kg/tile) = 1.43 (0.65)

Size

Nominal Size, in. (cm) = 12 x 12 (30.48 x 30.48)

Recommended Load Limit

Static Load Limit, p.s.i. (kg/cm²) = 75 (5.28)

Reference Specifications

ASTM Specification F-1066 = Composition 1, Class 2

Federal Specification, SS-T-312 B(1) = Type IV, Composition 1

Canadian Specification, CCMC CSA-A126.1 = VCT Type A

Fire Test Data

ASTM E-648 Critical Radiant Flux, ≥ 0.45 watts/cm² = Passes

MIL STD 1623D Char length ≤ 10 in. = Passes

ASTM E-662, Smoke, ≤ 450 = Passes

New York State DOS File Number = 12050-930618-1076

Installation

Adhesive Type = Mannington Commercial V-11

Spread = 200 ft² gal

Install in accordance with Mannington Commercial's written instructions contained in the Mannington Professional Installation Guide.

Traffic Performance

Duty = Moderate, Heavy, Extra Heavy

Maintenance

Maintain in accordance with Mannington Commercial's written procedures contained in the Essentials & Inspirations Maintenance & Warranty brochure.

Warranty

Limited 5-Year Commercial Warranty for manufacturing defects and wear.

Colors

Printed colors may vary from actual products. Please refer to actual product samples when making color selections.

*Subject to white scratching. May require more frequent maintenance if used in field areas.

Architectural Specifications

Recommended specifications: All floors shown in the finish schedule or listed in the specification shall be Mannington Essentials/Inspirations Commercial Vinyl Composition Tile, manufactured by Mannington Resilient Floors, Salem, New Jersey 08079, color number _____(indicate color

number). The product shall have an overall gauge of .125" (3.18mm) nominal and be available in a 12" x 12" (30.48cm x 30.48cm) nominal size. The vinyl composition tile shall be manufactured in accordance with ASTM Specification F-1066, Composition 1, Class 2, or Federal Specification SS-T-312B(1), as a Type IV, Composition 1 product and shall be asbestos-free. The product shall offer a Limited 5-Year Commercial Warranty against manufacturing defects as detailed in the Mannington Commercial Essentials and Inspirations Maintenance & Warranty brochure. The recommended adhesive shall be Mannington Commercial V-11. Installation shall be as recommended in the Mannington Professional Installation Guide. Made in the U.S.A.

For Installation, Specifications, Maintenance and Warranty Information, Call 1-800-FLOOR-85

For Product Literature or Samples, Call 1-800-241-2262

Mannington Mills, Inc.

P.O. Box 30

Salem, New Jersey 08079

Mannington Mills, Inc.

P.O. Box 67021

3200 Erin Mills Parkway

Mississauga, Ontario L5L 5W9

Canada