

3M Epoxy Flooring System 8900 Series

Key Features of the 8900 Series

Static-Dissipative/Conductive

No Wax

Semi-gloss finish

Seamless

Best for industrial use

Superior wear resistance properties withstand forklifts and heavy floor traffic

For use on old or new concrete floors

Sizes available:

Thickness: 8 - 10 mils, 50 mils, 90 mils, 125 mils

3M™ 8900 Series Epoxy Flooring System

Available colors:

Off White

50 mil, 90 mil, 125 mil

Light Gray

50 mil, 90 mil and 125 mil

Oyster Gray

10 mil, 50 mil, 90 mil and 125 mil

Tower Gray

10 mil, 50 mil, 90 mil and 125 mil

Sky Blue

50 mil, 90 mil and 125 mil

Country Blue

10 mil, 50 mil, 90 mil and 125 mil

All flooring products are available in custom colors.

Installation for 8900 Series

The 3M™ 8900 ESD Epoxy Flooring System should be applied only by a 3M approved applicator. For customers who have an ESD epoxy floor purchased and installed from another manufacturer that is not performing properly, 3M Electrical Specialties Division offers refurbish and repair services.

Maintenance for 8900 Series

Install 3M Nomad or Carpet Mats at all room entry ways to prevent debris from entering the room. Dust mop the 8900 ESD floor daily with a clean, dry dust mop. If needed, damp mop with clean mop heads and clean, warm water 3M Spangle Neutral Floor Cleaner diluted in accordance with the directions on the label. An automatic scrubber or floor buffer may be used with 3M Spangle Neutral Floor Cleaner diluted in accordance with the directions on the label. Use only 3M White, Red or Tan Line Buffer Pads.

Limited Warranty for 8900 Series

3M expressly warrants that the 3M 8900 ESD Epoxy Flooring System will maintain its electrical properties for a period of six (6) years from the date of purchase and its surface integrity for two (2) years from the date of installation and the 3M 8900 ESD Epoxy Flooring System will be free of defects in materials (parts) and workmanship (labor). If 3M receives notice of such a defect during the applicable warranty period, 3M will replace at its expense such ESD Epoxy Flooring System which it determines to be defective. Defective products must be returned to 3M with proof of purchase date or, if the epoxy is already installed, product defects and proof of purchase must be verified by 3M.

Warranty Exclusions for 8900 Series

THE FOREGOING EXPRESS WARRANTY IS MADE IN LIEU OF ALL OTHER PRODUCT WARRANTIES, EXPRESS AND IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE WHICH ARE SPECIFICALLY DISCLAIMED. The express warranty will not apply to defects or damage due to accidents, neglect, misuse, alterations, operator error, or failure to properly maintain, clean, or repair products.

Limit of Liability for 8900 Series

In no event will 3M or any seller be responsible or liable for special, incidental, or consequential losses or damages, under any legal theory including but not limited to contract, negligence or strict liability. Fulfillment by 3M of its express warranty obligations described above will be purchaser's exclusive remedy and will be 3M's and seller's limit of liability for any breach of warranty or otherwise.

3M Electrical Specialties Division

3M Center, Building 148-35-04
6801 River Place Blvd.
Austin, TX 78726-9000
(800) 665-7862, ext. 101

Sweet's Catalog: 09650/THR

Buyline: 8102