

Specifications

Colors

Taraflex SPORT M

Sand 6367 T/C
Horizon 6426 T
Green 6512 T/C
Orange 6172 T
Blue 6430 T/C
Red 6180 T/C
Hawaii Grey 6777 T/C
Camel 6393 C
Silver Grey 6758 T/C
Bordeaux 6103 T

Taraflex Track

Blue 6430
Brick 6118

Taraflex Surface

Sand 6367 T
Brick 6118 T
Green 6512 T
Horizon 6426 T
Orange 6172 T

Action Sport

Sand 6367 C
Hawaii Grey 6777 C
Red 6180 C
Blue 6430 C

T = Tapis texture

C = Calf texture

Product Offering

Taraflex Sport M, Track, Surface, and Action Sport have homogeneous 100% pure vinyl wear layers combined with a closed-cell vinyl foam backing, reinforced with a fiberglass interlayer for added dimensional stability. Contact your Taraflex representative for further details on the Taraflex Sports Flooring products.

Quality Assurance

All Taraflex products are made to the industry's highest quality standards. Installation of Taraflex products shall only be done by a qualified flooring contractor approved by Taraflex.

Product Handling

Unless otherwise specified by Taraflex, sports flooring products should not be delivered to the job site sooner than one month prior to the installation date. Taraflex rolls are sequentially identified by dye lot and should be installed accordingly. To protect the foam backing, rolls should be stored in an upright position.

Subfloor

Concrete subfloors must be equipped with an industry approved vapor barrier. Subfloors must be inspected for proper tolerance (1/8" in 10' radius) and moisture levels (24 hrs./1000 sq. ft.: 3.0 max.). All discrepancies should be reported in writing to the general contractor. Subfloor preparation is the sole responsibility of the general contractor. Consult the Taraflex installation manual for further details.

Adhesives

Only use adhesives approved by Taraflex. Taraflex will not guarantee product performance when used with non-approved adhesive substitutes. For adhesive performance questions, refer to adhesive manufacturer's recommendations.

Installation

The installation of Taraflex Sports Flooring should be done according to written instructions provided by Taraflex. Consult the Taraflex installation manual for further details.

Finishing Materials

Game line paint and seaming techniques shall be recommended by Taraflex.

Maintenance

Initial maintenance shall be done no sooner than 72 hours following product and game line installation. **Initial maintenance** shall consist of a thorough cleaning using a low speed commercial scrubber equipped with a light scouring pad in the case of the "calf" texture or a soft nylon bristle brush in the case of the "tapis" texture. This should be done employing a neutral based cleaning solution (i.e., 3 to 4 ounces of cleaning solution for 1 gallon of lukewarm water). After cleaning, rinse and let dry. To preserve the playing characteristics, sealants or floor finishing solutions should not be used on Taraflex flooring. **Regular maintenance** should include daily sweeping and periodical damp mopping. **When the flooring becomes tarnished or sticky**, it should be mechanically cleaned as described in the "initial maintenance" procedure. For detailed maintenance recommendations, please consult our *Maintenance Guide*.

Warranty

Taraflex offers a two (2) year warranty for Taraflex Sport M, Track, Surface, Action Sport and Isolsport. This coverage is limited to the normal use and maintenance of the product. This warranty will become null and void if the subfloor conditions and installation procedures do not conform to those prescribed by Taraflex.

Limitation of Liability

Taraflex shall not be liable for any injury, loss or damage, whether direct, indirect, special, incidental or consequential, arising out of the furnishing of, the use of, or any inability to use the Taraflex Sports Flooring System provided therefrom. The remedies of the purchaser set forth herein are exclusive, and the liability of Taraflex with respect to any contractor's sale or anything done in connection therewith, whether in contract, in tort, negligence, under any warranty or otherwise, shall not, except as expressly provided herein, exceed the cost of replacement of the Taraflex Sports Flooring System upon which such liability is based. Buyer assumes all risks and liability for damage to persons or property resulting from buyer's use of the material.

Christian Kuhn (Sales Manager)

TARAFLEX Sports Flooring

5825 Glenridge Drive
Building 3, Suite 101
Atlanta, GA 30328 USA

Phone: 1-800-727-7505

404-845-3445

Fax: 404-845-3446

Sweet's BuyLine: 4102