

09782/ACC
BuyLine 7777

PP-PRODUCT PRESENTATION

SEE FOR YOURSELF

ASI detectable warning systems have surpassed the competition in the most stringent industry tests that prove no other detectable warning system comes close to ASI in wear, impact, chemical and slip resistance, plus tensile and compressive strength.

ASI detectable warning tiles are a fiberglass reinforced composite – a material often used in failure-critical structural applications that are subjected to long term exposure to harsh outdoor environments. ASI tiles are rigid, colorfast and UV resistant. The tiles are offered in our standard safety yellow, custom colors are available to meet your special applications and aesthetic requirements.

DT-DOCUMENT

CODE ACCEPTABILITY

ASI tiles are a *raised truncated dome* configuration which complies with Federal Law Title III, Section 4.29, of the Americans with Disabilities Act Accessibility Guidelines (ADAAG) **and** Title 24 CAC of California State Accessibility Standards. As mandated, the raised truncated domes are 2.35" on center, 0.9" in diameter, and 0.2" in height.

USES & APPLICATIONS

ASI Tiles are found wherever there is a safety concern for the blind/visually impaired. This includes transit/platforms (platforms that cannot use handrails), hazardous vehicular areas, uncurbed sidewalks/street intersections, curb ramps, and edges of reflecting pools.

OP-OVERALL PRODUCT IN PLACE

SAFETY

With a lifespan longer than any other detectable warning tile on the market today, safety is assured with ASI in any application. The bright yellow tiles create a color contrast with the adjacent floor surface, which the visually impaired can easily detect. The tile also provides an audible warning with the click of cane. Add the security of the tile's dome pattern and you've got the safest detectable warning system available.

In addition, ASI Tiles meet U.S. and Canadian building codes for fire resistance/flammability with Flame Spreads under 25 and Smoke Developed under 450.

AI-ASSEMBLY, INSTALLATION

INSTALLATION

ASI Tiles are two feet by four feet by one-eighth inch thick – for quick, easy installation. The large size of the tile provides for fewer seams, as well as a more uniformly attractive appearance. The tile can be surface applied or recessed flush depending on the application.

Mechanical fasteners are used to secure the tile to the substrate. Mounting holes for the fasteners are factory molded into the tile for easy application. Construction Grade elastomeric adhesive is optional.

CC-CODE ACCEPTABILITY, CERTIFICATION

WARRANTY

ASI provides a five year limited warranty on the tile.

If you have questions regarding ASI tile specifications, applications, installation, or pricing, call us today. We look forward to discussing the details of your project with you. Call 1-800-385-4363.

ASI

ACCESS SOLUTIONS, INC.

400 West Cummings Park

Unit 1725

Woburn, MA 01801

Tel: 1-800-385-4363

Fax: 1-800-385-2128