

SEAL-KRETE® Waterproofing Sealer				
LIQUID PROPERTIES	TEST RESULTS	FILM APPEARANCE	TEST RESULTS	GENERAL COVERA
				MATERIAL
Solids	10% Solids	Clear	Slight Gloss	Stucco/
Light Stability	Excellent	Light Stability	Excellent	Simulated Brick
Mechanical Stability	Excellent	Water Resistance	Excellent	Concrete (Poured)
Diluent	Water	Odor	None	Concrete Block
Storage Ability	2 Years (Minimum)	Tensile Strength	Excellent	Brick
Appearance	Milky White	Freeze/Thaw Stability	Excellent	Porous Tile
Odor	Very Low	Mechanical Stability	Excellent	Wood Shingles
Film Forming Temperature	22°C/73°F without use of coalescing solvent	Fadometer Study	Approximately .05% at 312 hours of test	Wood Siding
Coverage per Gallon	Approximately 100 to 300 sq. ft. per gallon (depending on porosity and type substrate)			Adobe
				Chalky Surfaces
				Vinyl Siding

*Actual coverage will vary d
upon porosity of materials
Second Coat Application: A
to above figures.

GE GUIDELINES
COVERAGE
(sq. ft./gallon)*
175
200
100
150
200
125
200
150
300
300

depending

.

dd 50%