

SRF 7510 ELECTRONIC SENSOR DRINKING FOUNTAIN

STANDARD FEATURES

- Complies with ADA front approach requirement.
- Classic sculptured lines made of heavy gauge stainless steel with No. 4 satin finish.
- Chrome plated non squirt push button operated bubbler.
- HF version incorporates an infrared sensor which activates water flow when a user enters the sensor's range and continues until user leaves. "Delayed start" feature prevents accidental activation.
- Refrigeration unit provided with leads for direct connection inside terminal enclosure.
- RWC-8 chiller provides refrigeration.
- Stainless steel with bronzetone finish available for an additional cost.

SHIPPING DIMENSIONS

SRF-7510-01 Fountain & Grille – 33" x 21" x 17" (838 mm x 533 mm x 432 mm)

SRF-7552-01 Fountain & Grille – 33" x 21" x 17" (838 mm x 533 mm x 432 mm)

SRF-9000 Mounting Frame* – 5" x 16" x 35" (127 mm x 406 mm x 889 mm)

RWC-8 Chiller – 12" x 16" x 21" (305 mm x 406 mm x 533 mm)

** Mounting frame can be shipped in advance of fountains, grille and chiller for rough-in installation.*

SHIPPING WEIGHTS

SRF-7510-01 Fountain & Grille – 45 lbs. (20.4 kg)

SRF-7552-01 Fountain & Grille – 45 lbs. (20.4 kg)

SRF-9000 Mounting Frame – 17 lbs. (7.7 kg)

RWC-8 Chiller – 56 lbs. (25.4 kg)

SUNROC CORPORATION

60 Starlifter Ave.

Kent County Aeropark

Dover, DE 19901

Tel: 302-678-7800

Fax: 302-678-7809