

MR-MANUFACTURER-USG Interiors, Inc.

PP-PRODUCT PRESENTATION-ACOUSTONE® Medium-Textured Ceiling Panels

- * "F" Fissured: Moderately planed, random fissures, for a natural-chiseled look.
- * Class A and FIRECODE® (for fire-rated systems).
- * Flame spread/smoke developed: 25/15.
- * Weight:
 - 1.25 lb./sq. ft. (6.10 kg/sq. m) (Class A).
 - 1.30 lb./sq. ft. (6.35 kg/sq. m) (FIRECODE).
- * Thermal resistance: R-2.12.
- * Maximum backloading: .75 lb./sq. ft.(3.66 kg/sq. m).
- * Durability: ACOUSTONE surface resists scrapes commonly caused by accessing ceiling panels.
- * Metric sizes: All products are available in metric sizes. To specify, add "ME" before the standard item number.
- * Products are available in the following edges:
 - Square (SQ), Shadowline (SL), Finesline (FL), Bevel Edge/Kerf (BESK) and Square Edge/Kerf (SESK). See the Grid/Edge Selector Guide in Corporate Showcase Screen #6.

UA-USES, APPLICATIONS-

- * Closed-plan offices.
- * Open-plan offices.
- * Lobbies.
- * Retail stores.
- * Restaurants.
- * High visibility ceilings.

AI-ASSEMBLY, INSTALLATION-

- * Install panels with Square edge in DONN® DX® or fire-rated DXL™ 15/16" (23 mm) exposed suspension, DXW 1-1/2" (38 mm) exposed suspension, or CENTRICITEE™ or MERIDIAN® 9/16" (14 mm) exposed suspension.
- * Install panels with Shadowline edge in DONN DX or fire-rated DXL 15/16" (23 mm) exposed suspension.
- * Install panels with FINELINE edge in DONN FINELINE® or FINELINE 1/8 9/16" (14 mm) exposed suspension, or CENTRICITEE or MERIDIAN 9/16" (14 mm) exposed suspension.
- * Install tile with Square Edge/Kerf or Bevel Edge/Kerf in DONN Concealed DX suspension.

MF-MATERIALS, FINISHES-

- * Materials-
 - ACOUSTONE molded mineral fiber.
- * Colors-
 - White plus 24 standard colors.
 - Exclusive clear-through color process masks nicks and scratches.
- * Call Customer Relations at 1-800-950-3839 for samples.
- * Accessory systems-
 - DONN DX 15/16" (23 mm) exposed suspension.
 - DONN DXL fire-rated 15/16" (23 mm) exposed suspension.
 - DONN DXW 1-1/2" (38 mm) exposed suspension.
 - DONN CENTRICITEE non-fire-rated or fire-rated 9/16" (14 mm) exposed suspension.
 - DONN MERIDIAN 9/16" (14 mm) exposed suspension with rounded reveal.
 - DONN FINELINE non-fire-rated or fire-rated, slotted 9/16" (14 mm) exposed suspension.

- DONN FINELINE 1/8 slotted 9/16" (14 mm) exposed suspension.
- DONN Concealed DX non-fire-rated or fire-rated suspension.

CS-COATINGS, SURFACING-

* ENVIROSENSE™ with INTERSEPT® (new, surface-active, broad spectrum antimicrobial): All products are available with INTERSEPT. To specify, use the standard item number followed by the word "INTERSEPT."

TS-TECHNICAL SUPPORT-

* Call Customer Relations at 1-800-950-3839.

CC-CODES, CERTIFICATION-

* ASTM form/spec. Type 3, Form 1, Class 25.
* Meets ASTM E1264.

OM-OPERATION, MAINTENANCE-

* Can be cleaned easily with a soft brush or vacuum.