

MR-MANUFACTURER-USG Interiors, Inc.

PP-PRODUCT PRESENTATION-AURATONE® Medium-Textured Ceiling Panels

- * Omni: Lightly fissured, heavily perforated.
- * Omni High-NRC: Same surface as Omni Fissured; excellent NRC's combined with optimum density.
- * Omni High-CAC: Same surface as Omni Fissured; excellent CAC ratings for privacy in closed-plan.
- * Natural Fissured II: Deeply fissured, moderately perforated.
- * Fissured: A subtle pattern of fissuring combined with random perforations.
- * Class A and FIRECODE® (for fire-rated systems).
- * Flame spread/smoke developed:
 - 25/10 (Omni).
 - 15/10 (Natural Fissured II).
- * Weight:
 - .69-.81 lb./sq. ft. (3.37-3.95 kg/sq. m) (Class A 5/8" {16 mm} panels).
 - 1.00 lb./sq. ft. (4.88 kg/sq. m) (Class A and High-NRC 3/4" {19 mm} panels).
 - 1.10 lb./sq. ft. (5.37 kg/sq. m) (Class A 5/8" {16 mm} tile).
 - 1.40 lb./sq. ft. (6.83 kg/sq. m) (Class A 3/4" {19 mm} tile).
 - 1.15 lb./sq. ft. (5.61 kg/sq. m) (FIRECODE 5/8" {16 mm} panels and tile).
 - 1.37 lb./sq. ft. (6.69 kg/sq. m) (FIRECODE 3/4" {19 mm} panels).
 - 1.40 lb./sq. ft. (6.83 kg/sq. m) (FIRECODE 3/4" {19 mm} tile).
 - 1.25 lb./sq. ft. (6.10 kg/sq. m) (PREMIER FIRECODE 7/8" {22 mm} panels).
- * Thermal resistance:
 - R-2.18 (3/4" {19 mm} products).
 - R-1.85 (5/8" {16 mm} products).
- * Maximum backloading: .75 lb./sq. ft. (3.66 kg/sq. m).
- * Metric sizes: All products are available in metric sizes. To specify, add "ME" before the standard item number.
- * Products are available in the following edges:
Square (SQ), Shadowline Tapered (SLT), Interline Tapered (ILT), Fineline (FL), Bevel Edge/Kerf (BESK) and Tongue & Groove Flange (TGF). See the Grid/Edge Selector Guide in Corporate Showcase Screen #6.

UA-USES, APPLICATIONS-

- * Open-plan offices.
- * Closed-plan offices.
- * Lobbies.
- * Shopping centers and stores.
- * Restaurants.

AI-ASSEMBLY, INSTALLATION-

- * Install panels with Square edge in DONN® DX® or fire-rated DXL™ 15/16" (23 mm) exposed suspension, DXW 1-1/2" (38 mm) exposed suspension, or CENTRICITEE™ or MERIDIAN® 9/16" (14 mm) exposed suspension.
- * Install panels with Shadowline Tapered edge in DONN DX or fire-rated DXL 15/16" (23 mm) exposed suspension.
- * Install panels with Interline Tapered edge in DONN CENTRICITEE or MERIDIAN 9/16" (14 mm) exposed suspension.
- * Install panels with FINELINE edge in DONN FINELINE® or FINELINE 1/8 9/16" (14 mm)

exposed suspension, or CENTRICITEE or MERIDIAN 9/16" (14 mm) exposed suspension.

* Install tile with Bevel Edge/Kerf in DONN Concealed DX suspension.

* Install tile with Tongue & Groove Flange edge using adhesive or staple-up method.

* Install tile with Staple Flange edge using staple-up method.

MF-MATERIALS, FINISHES-

* Materials-

- AURATONE water-felted mineral fiber.

* Colors-

- White plus 24 standard colors (Omni).

- White (Natural Fissured II).

* Call Customer Relations at 1-800-950-3839 for samples.

* Accessory systems-

- DONN DX 15/16" (23 mm) exposed suspension.

- DONN DXL fire-rated 15/16" (23 mm) exposed suspension.

- DONN DXW 1-1/2" (38 mm) exposed suspension.

- DONN CENTRICITEE non-fire-rated or fire-rated 9/16" (14 mm) exposed suspension.

- DONN MERIDIAN 9/16" (14 mm) exposed suspension with rounded reveal.

- DONN FINELINE non-fire-rated or fire-rated, slotted 9/16" (14 mm) exposed suspension.

- DONN FINELINE 1/8 slotted 9/16" (14 mm) exposed suspension.

- DONN Concealed DX non-fire-rated or fire-rated suspension.

CS-COATINGS, SURFACING-

* Optional plastic coating (available only on white products) is Gardner-Scrubbability-tested to 3,000 cycles.

* ENVIROSENSE™ with INTERSEPT® (new, surface-active, broad spectrum antimicrobial): All products are available with INTERSEPT. To specify, use the standard item number followed by the word "INTERSEPT."

TS-TECHNICAL SUPPORT-

* Call Customer Relations at 1-800-950-3839.

CC-CODES, CERTIFICATION-

* ASTM form/spec. Type 3, Form 2, Class 25.

* Meets ASTM E1264.

OM-OPERATION, MAINTENANCE-

* Can be cleaned easily with a soft brush or vacuum.