

## **MR-MANUFACTURER-USG Interiors, Inc.**

### **PP-PRODUCT PRESENTATION-ACOUSTONE® Richly-Textured Ceiling Panels**

- \* GLACIER™: Distinctive rough texture with rich surface detail.
- \* Class A and FIRECODE® (for fire-rated systems).
- \* Flame spread/smoke developed: 25/15.
- \* Weight:
  - 1.25 lb./sq. ft. (6.10 kg/sq. m) (Class A).
  - 1.30 lb./sq. ft. (6.35 kg/sq. m) (FIRECODE).
- \* Thermal resistance: R-2.12.
- \* Maximum backloading: .75 lb./sq. ft. (3.66 kg/sq. m).
- \* Durability: ACOUSTONE surface resists scrapes commonly caused by accessing ceiling panels.
- \* Metric sizes: All products are available in metric sizes. To specify, add "ME" before the standard item number.
- \* Products are available in the following edges:  
Square (SQ), Shadowline (SL), Finline (FL) and Square Edge/Kerf (SESK). See the Grid/Edge Selector Guide in Corporate Showcase Screen #6.

### **UA-USES, APPLICATIONS-**

- \* Closed-plan offices.
- \* Open-plan offices.
- \* Lobbies.
- \* Retail stores.
- \* Restaurants.
- \* High visibility ceilings.

### **AI-ASSEMBLY, INSTALLATION-**

- \* Install panels with Square edge in DONN® DX® or fire-rated DXL™ 15/16" (23 mm) exposed suspension, DXW 1-1/2" (38 mm) exposed suspension, or CENTRICITEE™ or MERIDIAN® 9/16" (14 mm) exposed suspension.
- \* Install panels with Shadowline edge in DONN DX or fire-rated DXL 15/16" (23 mm) exposed suspension.
- \* Install panels with FINELINE edge in DONN FINELINE® or FINELINE 1/8 9/16" (14 mm) exposed suspension, or CENTRICITEE or MERIDIAN 9/16" (14 mm) exposed suspension.
- \* Install tile with Square Edge/Kerf in DONN Concealed DX suspension.

### **MF-MATERIALS, FINISHES-**

- \* Materials-
  - ACOUSTONE molded mineral fiber.
- \* Colors-
  - Panels: White plus 24 standard colors.
  - Tile: White plus Earthtone colors.
  - Exclusive clear-through color process masks nicks and scratches.
- \* Call Customer Relations at 1-800-950-3839 for samples.
- \* Accessory systems-
  - DONN DX 15/16" (23 mm) exposed suspension.
  - DONN DXL fire-rated 15/16" (23 mm) exposed suspension.
  - DONN DXW 1-1/2" (38 mm) exposed suspension.
  - DONN CENTRICITEE non-fire-rated or fire-rated 9/16" (14 mm) exposed suspension.
  - DONN MERIDIAN 9/16" (14 mm) exposed suspension with rounded reveal.

- DONN FINELINE non-fire-rated or fire-rated, slotted 9/16" (14 mm) exposed suspension.
- DONN FINELINE 1/8 slotted 9/16" (14 mm) exposed suspension.
- DONN Concealed DX non-fire-rated or fire-rated suspension.

**CS-COATINGS, SURFACING-**

\* ENVIROSENSE™ with INTERSEPT® (new, surface-active, broad spectrum antimicrobial): All products are available with INTERSEPT. To specify, use the standard item number followed by the word "INTERSEPT."

**TS-TECHNICAL SUPPORT-**

\* Call Customer Relations at 1-800-950-3839.

**CC-CODES, CERTIFICATION-**

\* ASTM form/spec. Type 3, Form 1, Class 25.

\* Meets ASTM E1264.

**OM-OPERATION, MAINTENANCE-**

\* Can be cleaned easily with a soft brush or vacuum.