

## **MR-MANUFACTURER-USG Interiors, Inc.**

### **PP-PRODUCT PRESENTATION-AURATONE® Design-Textured Ceiling Panels**

- \* Facets: Symmetrical, woven texture on a generous scale.
- \* Mosaic: Soft, nonrepeating rivulets of texture with minute perforations.
- \* Touchstone: Shading and three-dimensional fissures.
- \* Aspen: Random, naturally sculptured appearance.
- \* Tahoe: Naturally sculptured, softly rounded texture.
- \* Class A and FIRECODE® (for fire-rated systems).
- \* Flame spread/smoke developed: 25/10.
- \* Weight: .81 lb./sq. ft. (3.95 kg/sq. m) (Facets and Mosaic panels; Tahoe and Touchstone Class A panels).
  - 1.00 lb./sq. ft. (4.88 k g/sq. m) (Aspen Class A panels).
  - 1.37 lb./sq. ft. (6.69 kg/sq. m) (Aspen FIRECODE panels).
- \* Thermal resistance: R-1.85 (Facets, Mosaic and Touchstone).
  - Up to R-2.18 (Aspen and Tahoe).
- \* Maximum backloading: .75 lb./sq. ft. (3.66 kg/sq. m).
- \* Metric sizes: All products are available in metric sizes. To specify, add "ME" before the standard item number.
- \* Products are available in the following edges:
  - Square (SQ), Shadowline Tapered (SLT), Interline Tapered (ILT) and Fineline (FL). See the Grid/Edge Selector Guide in Corporate Showcase Screen #6.

### **UA-USES, APPLICATIONS-**

- \* Open-plan offices.
- \* Closed-plan offices.
- \* Lobbies.
- \* Shopping centers and stores.
- \* Restaurants.

### **AI-ASSEMBLY, INSTALLATION-**

- \* Install panels with Square edge in DONN® DX® or fire-rated DXL™ 15/16" (23 mm) exposed suspension, DXW 1-1/2" (38 mm) exposed suspension, or CENTRICITEE™ or MERIDIAN® 9/16" (14 mm) exposed suspension.
- \* Install panels with Shadowline Tapered edge in DONN DX or fire-rated DXL 15/16" (23 mm) exposed suspension.
- \* Install panels with Interline Tapered edge in DONN CENTRICITEE or MERIDIAN 9/16" (14 mm) exposed suspension.
- \* Install panels with FINELINE edge in DONN FINELINE® or FINELINE 1/8 9/16" (14 mm) exposed suspension, or CENTRICITEE or MERIDIAN 9/16" (14 mm) exposed suspension.

### **MF-MATERIALS, FINISHES-**

- \* Materials-
  - AURATONE water-felted mineral fiber.
- \* Colors-
  - White plus 24 standard colors (Facets, Mosaic, Aspen and Tahoe).
  - Designer White (Touchstone).
- \* Call Customer Relations at 1-800-950-3839 for samples.
- \* Accessory systems-
  - DONN DX 15/16" (23 mm) exposed suspension.
  - DONN DXL fire-rated 15/16" (23 mm) exposed suspension.

- DONN DXW 1-1/2" (38 mm) exposed suspension.
- DONN CENTRICITEE non-fire-rated or fire-rated 9/16" (14 mm) exposed suspension.
- DONN MERIDIAN 9/16" (14 mm) exposed suspension with rounded reveal.
- DONN FINELINE non-fire-rated or fire-rated, slotted 9/16" (14 mm) exposed suspension.
- DONN FINELINE 1/8 slotted 9/16" (14 mm) exposed suspension.
- DONN Concealed DX non-fire-rated or fire-rated suspension.

**CS-COATINGS, SURFACING-**

- \* Optional plastic coating (available only on white products) is Gardner-Scrubability-tested to 3,000 cycles.
- \* ENVIROSENSE™ with INTERSEPT® (new, surface-active, broad spectrum antimicrobial): All products are available with INTERSEPT. To specify, use the standard item number followed by the word "INTERSEPT."

**TS-TECHNICAL SUPPORT-**

- \* Call Customer Relations at 1-800-950-3839.

**CC-CODES, CERTIFICATION-**

- \* ASTM form/spec. Type 3, Form 2, Class 25.
- \* Meets ASTM E1264.

**OM-OPERATION, MAINTENANCE-**

- \* Can be cleaned easily with a soft brush or vacuum.