MR-MANUFACTURER-USG Interiors, Inc.

PP-PRODUCT PRESENTATION-AURATONE® Scored Ceiling Panels

- * PEDESTALS™ I: Triple step-cut detailing only at panel edges.
- * PEDESTALS IV: Triple step-cut 12" x 12" (300x300 mm) modules.
- * PEDESTALS IX: Smaller 8" x 8" (200x200 mm) triple step-cut modules.
- * Class A.
- * Flame spread/smoke developed: 25/10.
- * Weight: 1.00 lb./sq. ft. (4.88 kg/sq. m).
- * Thermal resistance: Up to R-2.18.
- * Maximum backloading: .75 lb./sq. ft. (3.66 kg/sq. m).
- * Metric sizes: All products are available in metric sizes. To specify, add "ME" before the standard item number.
- * Products are available in the following edge:

PEDESTALS Edge (PE). See the Grid/Edge Selector Guide in Showcase Screen #3.

* Products are available in the following face styles:

PEDESTALS I, PEDESTALS IV, and PEDESTALS IX. See Face-Cut Configurations in Corporate Showcase Screen #7.

UA-USES, APPLICATIONS-

- * Open-plan offices.
- * Closed-plan offices.
- * Lobbies.
- * Shopping centers and stores.
- * Restaurants.

AI-ASSEMBLY, INSTALLATION-

* Install panels in DONN® CENTRICITEE™ or MERIDIAN® 9/16" (14 mm) exposed suspension.

MF-MATERIALS, FINISHES-

- * Materials-
- AURATONE water-felted mineral fiber.
- * Colors-
- White, Manila, Silvertone, Parchment, Taupe, Mist.
- * Call Customer Relations at 1-800-950-3839 for samples.
- * Accessory systems-
- DONN CENTRICITEE 9/16" (14 mm) exposed suspension.
- DONN MERIDIAN 9/16" (14 mm) exposed suspension with rounded reveal.

CS-COATINGS, SURFACING-

- * Optional plastic coating (available only on white products) is Gardner-Scrubbability-tested to 3,000 cycles.
- * ENVIROSENSE™ with INTERSEPT® (new, surface-active, broad spectrum antimicrobial): All products are available with INTERSEPT. To specify, use the standard item number followed by the word "INTERSEPT."

TS-TECHNICAL SUPPORT-

* Call Customer Relations at 1-800-950-3839.

CC-CODES, CERTIFICATION-

* ASTM form/spec. Type 3, Form 2, Class 25.

* Meets ASTM E1264.

OM-OPERATION, MAINTENANCE-

* Can be cleaned easily with a soft brush or vacuum.