

MR-MANUFACTURER-USG Interiors, Inc.

PP-PRODUCT PRESENTATION-AURATONE® Linear-Scored Ceiling Panels

- * DESIGNER SQUARES™ II: Six 3"x24" (75x600 mm) linear bars.
- * DESIGNER SQUARES™ IV: Eleven 1"x24" (25x600 mm) linear bars.
- * ILLUSION Four/48: 6"x48" (150x1200 mm) linear strips.
- * Class A and FIRECODE® (for fire-rated systems).
- * Flame spread/smoke developed: 25/10 (Natural Fissured II, Omni Fissured and Aspen texture).
- * Weight: 1.00 lb./sq. ft. (4.88 kg/sq. m) (PEDESTALS panels).
.69-.81 lb./sq. ft. (3.37-3.95 kg/sq. m) (PROFILE panels).
1.37 lb./sq. ft. (6.69 kg/sq. m) (ILLUSION panels).
- * Thermal resistance: Up to R-2.18 (PEDESTALS panels).
R-1.52 to R-1.85 (PROFILE panels).
Up to R-1.52 (DESIGNER SQUARES panels).
R-2.18 (ILLUSION panels with Omni Fissured and Aspen texture).
- * Maximum backloading: .75 lb./sq. ft. (3.66 kg/sq. m).
- * Metric sizes: All products are available in metric sizes. To specify, add "ME" before the standard item number.
- * Products are available in the following edges:
PEDESTALS (PE), Interline Tapered (ILT), Shadowline (SL), Fineline (FL) and Shadowline Tapered (SLT). See the Grid/Edge Selector Guide in Showcase Screen #3.
- * Products are available in the following face styles:
DESIGNER SQUARES II, DESIGNER SQUARES IV and ILLUSION Four/48. See Face-Cut Configurations in Corporate Showcase Screen #7.

UA-USES, APPLICATIONS-

- * Open-plan offices.
- * Lobbies.
- * Shopping centers and stores.
- * Restaurants.
- * Expansive ceiling areas.

AI-ASSEMBLY, INSTALLATION-

- * Install PEDESTALS panels in DONN® CENTRICITEE™ or MERIDIAN® 9/16" (14 mm) exposed suspension.
- * Install panels with Shadowline Tapered edge in DONN® DX® or fire-rated DXL™ 15/16" (23 mm) exposed suspension.
- * Install panels with Interline Tapered edge in DONN CENTRICITEE™ or MERIDIAN® 9/16" (14 mm) exposed suspension.
- * Install panels with FINELINE edge in DONN FINELINE® or FINELINE 1/8 9/16" (14 mm) exposed suspension, or CENTRICITEE™ or MERIDIAN® 9/16" (14 mm) exposed suspension.

MF-MATERIALS, FINISHES-

- * Materials-
 - AURATONE water-felted mineral fiber.
- * Colors-
 - White, Manila, Silvertone, Parchment, Taupe, Mist.
- * Call Customer Relations at 1-800-950-3839 for samples.
- * Accessory systems-
 - Donn DX 15/16" (23 mm) exposed suspension.
 - Donn DXL fire-rated 15/16" (23 mm) exposed suspension.

- Donn CENTRICITEE non-fire-rated or fire-rated 9/16" (14 mm) exposed suspension.
- Donn MERIDIAN 9/16" (14 mm) exposed suspension with rounded reveal.
- Donn FINELINE non-fire-rated or fire-rated, slotted 9/16" (14 mm) exposed suspension.
- Donn FINELINE 1/8 slotted 9/16" (14 mm) exposed suspension.

CS-COATINGS, SURFACING-

- * Optional plastic coating (available only on white products) is Gardner-Scrubability-tested to 3,000 cycles.
- * ENVIROSENSE™ with INTERSEPT® (new, surface-active, broad spectrum antimicrobial): All products are available with INTERSEPT. To specify, use the standard item number followed by the word "INTERSEPT."

TS-TECHNICAL SUPPORT-

- * Call Customer Relations at 1-800-950-3839.

CC-CODES, CERTIFICATION-

- * ASTM form/spec. Type 3, Form 2, Class 25.
- * Meets ASTM E1264.

OM-OPERATION, MAINTENANCE-

- * Can be cleaned easily with a soft brush or vacuum.