

MR-MANUFACTURER-USG Interiors, Inc.

PP-PRODUCT PRESENTATION-ACOUSTONE® Scored Ceiling Panels

- * Frost RENDITIONS™ I (A & B): Refined beveled corners.
- * Frost RENDITIONS II (A & B): Contemporary square corner design created by non-intersecting etched lines.
- * Frost RENDITIONS III (A & B): Rounded corners punctuated by skip-scoring and concentric dots.
- * Frost RENDITIONS Straight Line: Used in conjunction with RENDITIONS I, II, and III panels to extend line lengths.
- * Class A.
- * Flame spread/smoke developed: 25/15.
- * Weight: 1.25 lb./sq. ft. (6.10 kg/sq. m).
- * Thermal resistance: R-2.12.
- * Maximum backloading: .75 lb./sq. ft. (3.66 kg/sq. m).
- * Durability: ACOUSTONE surface resists scrapes commonly caused by accessing ceiling panels.
- * Metric sizes: All products are available in metric sizes. To specify, add “ME” before the standard item number.
- * Products are available in the following edge:
FINELINE (FL). See the Grid/Edge Selector Guide in Corporate Showcase Screen #6.
- * Products are available in the following face styles:
RENDITIONS I (A), RENDITIONS II (A), RENDITIONS III (A), RENDITIONS I (B), RENDITIONS II (B), RENDITIONS III (B) and RENDITIONS Straight Line. See Face-Cut Configurations in Corporate Showcase Screen #7.

UA-USES, APPLICATIONS-

- * Closed-plan offices.
- * Open-plan offices.
- * Lobbies.
- * Retail stores.
- * Restaurants.
- * High visibility ceilings.

AI-ASSEMBLY, INSTALLATION-

- * Install Frost RENDITIONS panels in DONN® FINELINE® or FINELINE 1/8 9/16" (14 mm) exposed suspension.

MF-MATERIALS, FINISHES-

- * Materials-
 - ACOUSTONE molded mineral fiber.
- * Colors-
 - White plus 24 standard colors.
 - Exclusive clear-through color process masks nicks and scratches.
- * Call Customer Relations at 1-800-950-3839 for samples.
- * Accessory systems-
 - DONN FINELINE slotted 9/16" (14 mm) exposed suspension.
 - DONN FINELINE 1/8 slotted 9/16" (14 mm) exposed suspension.

CS-COATINGS, SURFACING-

- * ENVIROSENSE™ with INTERSEPT® (new, surface-active, broad spectrum antimicrobial): All

products are available with INTERSEPT. To specify, use the standard item number followed by the word "INTERSEPT."

TS-TECHNICAL SUPPORT-

* Call Customer Relations at 1-800-950-3839.

CC-CODES, CERTIFICATION-

* ASTM form/spec. Type 3, Form 1, Class 25.

* Meets ASTM E1264.

OM-OPERATION, MAINTENANCE-

* Can be cleaned easily with a soft brush or vacuum.