

MR-MANUFACTURER-USG Interiors, Inc.

PP-PRODUCT PRESENTATION-Gypsum Lay-In Ceiling Panels

- * Washable, inexpensive ceilings for interior and exterior applications.
- * USDA acceptance for food processing areas (vinyl facing).
- * Fire resistance at no extra cost.
- * White vinyl facing: Embossed stipple pattern, 2-mil-thick vinyl.
- * Unfinished paper: Natural color paper facing.
- * Painted Snowdrift: White surface.
- * FIRECODE® (for fire-rated systems).
- * Flame spread/smoke developed: 20/5 (Stipple Pattern and CLEAN ROOM™ Vinyl Facing).
15/0 (Paper Facing).
- * Weight: 2.00 lb./sq. ft. (9.76 kg/sq. m).
- * Thermal resistance: Up to R-0.45.
- * Maximum backloading: .75 lb./sq. ft. (3.66 kg/sq. m).
- * Metric sizes: All products are available in metric sizes. To specify, add "ME" before the standard item number.
- * Products are available in the following edge:
Square (SQ). See the Grid/Edge Selector Guide in Corporate Showcase Screen #6.

UA-USES, APPLICATIONS-

- * Restaurants.
- * Kitchens.
- * Laboratories.
- * Washrooms.
- * Hospitals.
- * Nursing homes.
- * Protected outdoor applications (covered entryways; covered parking garages).

AI-ASSEMBLY, INSTALLATION-

- * Install panels with Square edge in DONN® DX® or fire-rated DXL™ 15/16" (23 mm) exposed suspension, DXW 1-1/2" (38 mm) exposed suspension, DONN CENTRICITEE™ or MERIDIAN® 9/16" (14 mm) exposed suspension, or corrosion-resistant ZX, ZXA, or AX 15/16" (23 mm) exposed suspension.

MF-MATERIALS, FINISHES-

- * Materials-
 - Gypsum core.
- * Colors-
 - Stipple Pattern Vinyl Colors:
White, Silvertone and Manila. Contact your USG representative for more information.
- * Call Customer Relations at 1-800-950-3839 for samples.
- * Accessory systems-
 - DONN DX 15/16" (23 mm) exposed suspension.
 - DONN DXL fire-rated 15/16" (23 mm) exposed suspension.
 - DONN DXW 1-1/2" (38 mm) exposed suspension.
 - DONN CENTRICITEE non-fire-rated or fire-rated 9/16" (14 mm) exposed suspension.
 - DONN MERIDIAN 9/16" (14 mm) exposed suspension with rounded reveal.
 - DONN ZXA corrosion-resistant 15/16" (23 mm) exposed suspension.
 - DONN ZXLA corrosion-resistant, fire-rated 15/16" (23 mm) exposed suspension.
 - DONN AX corrosion-resistant, aluminum 15/16" (23 mm) exposed suspension.

CS-COATINGS, SURFACING-

TS-TECHNICAL SUPPORT-

* Call Customer Relations at 1-800-950-3839.

CC-CODES, CERTIFICATION-

* ASTM form/spec. Type 3, Form A, Class 3.

* Meets ASTM E1264.

OM-OPERATION, MAINTENANCE-

* Can be cleaned easily with a damp sponge.