### MR-MANUFACTURER - USG Interiors, Inc.

For specifications on this product, 1.) close this product Snapshot, 2.) click on the Manufacturer's Showcase button, 3.) select the screen, *Specification: ACOUSTONE Ceilings* from the drop-down Showcase list that appears in the upper right of your screen.

# PP-PRODUCT PRESENTATION - DONN® MERIDIAN® suspension grid

- \* Combines the esthetics of more expensive screw-slot grid with the function and utility of exposed grid.
- \* Unique, rounded 5/32" (4 mm) reveal softens the effect of grid lines to enhance the finished look
- \* Automatic centering of panels and light fixtures.
- \* High tensile steel connection clips on cross tee ends provide plug-in positive-lock insertion for quick installation.
- \* Exceptional tension and compression connection values without additional wires, clips, fasteners or pins.
- \* Cross tees with override ends resist twisting and give a professionally finished appearance.
- \* Metric sizes: All products are available in metric sizes. To specify, add "ME" before the standard item number.

#### **UA-USES, APPLICATIONS**

MERIDIAN for interior use only. See Ceiling Systems catalog *SA-905* and DONN Suspension Systems catalog *SA-904* for specific applications.

#### AI-ASSEMBLY, INSTALLATION

DONN MERIDIAN grids are designed for use with Square, Fineline, Fineline Bevel and Interline Tapered edge panels in exposed suspension. Level components and tie to structural members with hanger wire max. 48" (1200 mm) o.c. Install in accordance with ASTM C636 and manufacturer's instructions.

# MF-MATERIALS, FINISHES

- \* Material-
- Double web intermediate-duty steel
- \* Finishes-
- 32 standard finishes
- Call Customer Relations at 1-800-950-3839 for samples.

# **CS-COATINGS, SURFACING**

Proven corrosion-resistant coating.

### TS-TECHNICAL SUPPORT

Call Customer Relations at 1-800-950-3839.

## **CC-CODES, CERTIFICATION**

ASTM C635.

#### **OM-OPERATION, MAINTENANCE**

Can be cleaned easily with a soft cloth.