

				Tested							Tested	
				Load							Load	
				(lbs./LF)							(kg/m)	
				4' Hanger	5' Hanger	6' Hanger					1200 mm	1500 mm
Item No.	Class	Length	Height	Spacing	Spacing	Spacing	Item No.	Class	Length	Height	Spacing	Spacing
Main Tee							Main Tee					
DX 24	Intermediate	12'	1-1/2"	12.5	6.1	3.6	MEDX 24	Intermediate	3600 mm	38 mm	18.6	9.1
DX 26	Heavy Duty	12'	1-1/2"	16.5	7.3	4.9	MEDX 26	Heavy Duty	3600 mm	38 mm	24.5	10.9
Cross Tee							Cross Tee					
DX 216		2'	1"	14.8			MEDX 216		600 mm	25 mm	22	
DX 316		3'	1"	7.7			MEDX 316		900 mm	25 mm	11.5	
DX 416		4'	1"	4.2			MEDX 416		1200 mm	25 mm	6.3	
DX 422		4'	1-1/2"	9.1			MEDX 422		1200 mm	38 mm	13.5	
DX 522		5'	1-1/2"	4.3			MEDX 522		1500 mm	38 mm	6.4	
DX 424		4'	1-1/2"	13.8			MEDX 424		1200 mm	38 mm	20.5	
DX 524		5'	1-1/2"	7.1			MEDX 524		1500 mm	38 mm	10.6	
Load test data shows uniform load in lbs./LF (kg/m) based on simple span												
tests in accordance with ASTM C635 deflection limit of L/360. For DXL/DXLA												
load data, see technical data offered by your USG Interiors representative.												

