

Item No.	Length	Height	Tested Load
			(lbs./LF)
Tee Splines			
DE 209	2'	1/2"	3.4
DT 316	3'	1"	10
DT 416/			
DE 415	4'	1"	5
DT 416/			
DEN 415	4'	1"	3
BPA 216	2'	1"	20
BPA 316	3'	1"	6
BPA 416	4'	1"	4.5
BPA 224	2'	1-1/2"	35
BPA 324	3'	1-1/2"	16
BPA 424	4'	1-1/2"	6
BPA 524	5'	1-1/2"	3.5
FCC/FCZ	2'	3/4"	5.5
Metric sizes:			
			(kg/m)
Tee Splines			
MEDE 209	600 mm	13 mm	5.1
MEDT 316	900 mm	25 mm	14.9
MEDT 416/			
DE 415	1200 mm	25 mm	7.4
MEDT 416/			
DEN 415	1200 mm	25 mm	4.5
MEBPA 216	600 mm	25 mm	29.8
MEBPA 316	900 mm	25 mm	8.9
MEBPA 416	1200 mm	25 mm	6.7
MEBPA 224	600 mm	38 mm	52.1
MEBPA 324	900 mm	38 mm	23.8
MEBPA 424	1200 mm	38 mm	8.9
MEBPA 524	1500 mm	38 mm	5.2
MEFCC/FCZ	600 mm	19 mm	8.2
Load test data shows uniform load in lbs./LF (kg/m)			
based on simple span tests in accordance with			
ASTM C635 deflection limit of L/360.			