

				Tested								Tested			
				Load								Load			
				(lbs./LF)								(kg/m)			
				3'	4'	5'	6'	Metric sizes:				900 mm	1200 mm	1500 mm	1800 mm
Item No.	Class	Length	Height	Hanger Spacing	Hanger Spacing	Hanger Spacing	Hanger Spacing	Item No.	Class	Length	Height	Hanger Spacing	Hanger Spacing	Hanger Spacing	Hanger Spacing
Main Tee								Main Tee							
ZXA/ZXLA 24	Intermediate	12'	1-1/2"		12.4	6.1	3.6	MEZXA/MEZXLA 24	Intermediate	3600 mm	38 mm		18.5	9.1	5.4
ZXA/ZXLA 26	Heavy Duty	12'	1-1/2"		16	7.3	4.9	MEZXA/MEZXLA 26	Heavy Duty	3600 mm	38 mm		23.8	10.9	7.3
Cross Tee								Cross Tee							
ZXA/ZXLA 224		2'	1-1/2"		65			MEZXA/ZXLA 224		600 mm	38 mm		96.7		
ZXA/ZXLA 424		4'	1-1/2"		13.7			MEZXA/ZXLA 424		1200 mm	38 mm		20.4		
ZXA/ZXLA 524		5'	1-1/2"		6.4			MEZXA/ZXLA 524		1500 mm	38 mm		9.5		
Main Tee								Main Tee							
AX 26	Light Duty	12'	1-1/2"	16	6.9			MEAX 26	Light Duty	3600 mm	38 mm	23.8	10.3		
Cross Tee								Cross Tee							
AX 224		2'	1-1/2"	22.8				MEAX 224		600 mm	38 mm	33.9			
AX 424		4'	1-1/2"	5.2				MEAX 424		1200 mm	38 mm	3.7			
Load test data shows uniform load in lbs./LF (kg/m) based on simple span tests in accordance with ASTM C635 deflection limit of L/360.															