### MR-MANUFACTURER - USG Interiors, Inc.

### PP-PRODUCT PRESENTATION - DONN® Marine Wall System

- Lower cost than fixed wall systems
- Versatility
- Durability
- Rust-resistance
- Smooth surface---no protruding batten strips
- Relocatability
- Superior STC performance
- Superior fire ratings/the best in the industry
- Wiring can run vertically or horizontally in the wall
- Partitions frame top, side, intersecting and full-height glazing
- Features--
- Cavity depth: 2"
- Wall thickness: 3 3/4"
- STC range: 38-50
- Fire rating: Class A, vinyl

### **UA-USES, APPLICATIONS**

- Marine bulkheads

## AI-ASSEMBLY, INSTALLATION

- Only five components required for basic wall system
- Fast, easy progressive installation

### MF-MATERIALS, FINISHES

### Components -

- Panels

Metal-Faced Joiner Panels (24-ga. steel panel over 1/2" thick gypsum core, 24" or 30" wide, square edge)

Metal-Faced "C" Panels for overhead use (24-ga. steel panel over 1/2" thick gypsum core, 30" x 30")

- Studs

Steel (24-ga. galvanized steel, 2" depth, holes punched for utility passage)

- Overhead Track

Steel (3" or 3-3/8" width, 1-3/8" return)

- Deck Track

Steel (2" width, 1" return)

- Spacer Channels (Optional)

Steel (24" or 30" lengths)

#### Finishes -

- 9 standard baked enamel colors
- 14 laminated vinyl finishes including solids, textures and woodgrains; also custom colors
- Porcelain enamel
- Chalkboard
- Stainless steel
- Optional flush outside corners
- Optional trimless inside corners
- Call Customer Relations at 1-800-950-3839 for samples

#### Accessories -

- Door Frames

Steel (18-ga., non-handed, reversible)

- Glazing

Steel (throated for installation without regard to module)

Floor Base

Steel snap-on base

Vinyl or rubber base by others

Vinyl

Steel

# **CS-COATINGS, SURFACING**

- Overhead track, deck track, door frames, glazing and trim painted
- Vinyl floor base and trim PVC

## TS-TECHNICAL SUPPORT

- Call Technical Services at 1-216-722-8773

## **CC-CODES, CERTIFICATION**

- ASTM D2794 (impact resistance)
- ASTM E84 (flame spread)
- ASTM E90 (STC)
- ASTM E119 (fire endurance and hose stream)

## **OM-OPERATION, MAINTENANCE**

- Call Technical Services at 1-216-722-8773