Sheet1

TEXT,C,55

É!!!!!!!!!!!!!!»

SPECIFICATIONS

==========

CAPACITY 320MB / 525MB / 1000MB

RECORDING MODE NRZI

RECORDING DENSITY 16,000 BPI
DATA TRANSFER RATE 12MB/min
START/STOP TIME 300 MS MAXIMUM

ENVIRONMENTAL SPECIFICATIONS

TEMPERATURE 5øC - 45øC (41øF - 113øF)

RELATIVE HUMIDITY 20% - 80% NON-CONDENSING

ALTITUDE -1000 - 15,000 FT SHOCK .5G 11 MSEC VIBRATION .5G 5~55Hz

TAPE START SURGE CURRENT 3.5 AMPS MAXIMUM

OPERATIONAL CURRENT 1 AMP TYPICAL (STREAMING)

USER SELECTABLE JUMPER SETTINGS

SCSI ID

---- -

ÉIIIIIIIIÑIIIIIIIIIN

° SCSI ID ³ SB2-3 ³ SB2-2 ³ SB2-1 ⁰

0 0 3 ON 3 ON 3 ON *0 0 1 3 ON 3 ON 3 OFF 0 0 2 3 ON 3 OFF 3 ON 0

° 5 3 OFF 3 ON 3 OFF ° ° ° 6 3 OFF 3 OFF 3 ON °

6 ³ OFF ³ OFF ³ OFF ⁶
 7 ³ OFF ³ OFF ⁶

È[[[[[[[]]]]]]]]]

PARITY

ÉIIIIIIIIÑIIIIIIIIIIIIIIIIIIII

o SETTING 3 SB2-4

Sheet1

OTHER SETTINGS

° SB2-5 3 FACTORY USE ONLY °

° SB2-6 3 FACTORY USE ONLY °

È[[[[[[[]]]]]]]]

* DENOTES DEFAULT SETTINGS

TERMINATION

========

IF THE DRIVE IS NOT THE LAST DEVICE ON THE SCSI CHAIN, THE TERMINATOR PACKS AT LOCATIONS BR1 AND BR2, MUST BE REMOVED. OTHERWISE, THE TERMINATOR PACKS SHOULD REMAIN INSTALLED, AS THEY ARE BY DEFAULT.