TEXT,C,55

```
ÉÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍ»
ºPANASONIC JU-257A   1.44MB FLOPPY DRIVEº
ÈÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍ¼
```

PHYSICAL SPECIFICATIONS
==========

CAPACITY	1.44MB
TRANSFER RATE (KBIT/SEC)	500
AVERAGE LATENCY (MSEC)	100
ACCESS TIME (MSEC)	
TRACK TO TRACK	3
ROTATIONAL SPEED (RPM)	300
TRACK DENSITY (TPI)	135

PHYSICAL DIMENSIONS
==========

HEIGHT	1"
WIDTH	4"
DEPTH	5.9"

USER-SELECTABLE JUMPER SETTINGS
==========

```
ÉÍÍÍÍÍÍÍÍÍÑÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍÍ»
º SETTING ³MEANING                                    º
ÇÄÄÄÄÄÄÄÄÄÄÅÄÄÄÄÄÄÄÄÄÄ
```