



NORTH

FOUNDATION & FLOOR FRAMING PLAN
1/8" = 1'0"

GENERAL NOTES

1. FILL ZONES OF HOLLOW BRICK MASONRY, SHOWN THIS ON PLAN CONCRETE GROUT. INSTALL 4#5 VERTICAL IN APPROPRIATE CELLS.
2. SYMBOL, SHOWN THIS ON PLAN = CONSTRUCTION OR CONSTRUCTION JOINT.
3. MINIMUM CLEAR COVER TO REINFORCEMENT: FOUNDATION 3", WALLS & SLABS 1 1/2", SLABS ON GRADE (TOP OF SLAB TO W.W.F. TYPICAL) = 1 1/2".
4. FOR MASONRY CONTROL JOINTS, LOCATIONS & DETAILS REFR. ARCH. DRWG'S.
5. FOR LOCATIONS, SIZES, & DETAILS OF LINTELS ETC. NOT SHOWN OR FULLY DESCRIBED ON THESE SHEETS, REFER TO SHEET A7.
6. REFER TO ARCHITECTURAL & MECHANICAL DRAWINGS FOR OPENINGS THROUGH, UNLESS OTHERWISE NOTED FRAME OPENINGS W/ 3"x14" L'S, AS REQUIRED.

FOUNDATION & FLOOR FRAMING PLAN

ADDITION TO CACHE LA POUDRE ELEMENTARY SCHOOL
LA PORTE, COLORADO

5/15/72
7/15

