

Active Processes Definitions

Note: These are applications, DAs, etc. which are currently running on the machine

- *Process Name* : Name of file from which the process came
 - ◊ *Serial Number* = In hex, used to communicate with other processes
 - ◊ *Type* = Finder type of file which originated the process
 - ◊ *Creator* = Finder creator of file which originated the process
 - ◊ *Partition Start* = Address of process in memory in hex
 - ◊ *Partition Length* = Length of process in bytes
 - ◊ *Partition FreeMem* = Free memory available within space allocated to process in bytes. Corresponds to white space in "About this Macintosh" next to the program's name
 - ◊ *Path Name* = Location of file
 - ◊ *Launched By* = Who/what launched the process
 - ◊ *Attributes* :
 - + *Can Multi-Launch* = Yes/No [System 7]
 - + *Can accept Suspend/Resume Events* = Yes/No
 - + *Can operate in Background* = Yes/No
 - + *Can operate in Foreground* = Yes/No [System 7]
 - + *Can perform own Activate tasks* = Yes/No
 - + *Is notified when Sub-Process ends* = Yes/No [System 7]
 - + *Can receive Mouse Events in Background* = Yes/No [System 7]
 - + *Is 32 Bit compatible* = Yes/No [System 7]
 - + *Is High Level Event aware* = Yes/No [System 7]
 - + *Can receive High Level Events across a Network* = Yes/No [System 7]
 - + *Can recognize Stationary Documents* = Yes/No [System 7]