hawk 2XL Fast and Fast Wide SCSI-2 Interfaces



- · Formatted capacities of 2.15 and 1.05 Gbytes
- · 5,400 RPM spindle with 5.54 msec average latency
- · SCSI-3 SPI and SCAM Plug-n-Play compliant
- · Fast SCSI-2 and Fast Wide SCSI-2 high performance interface
- · Advanced SCSI Architecture II (ASA II)
- · Embedded servo and PRML channel



hawk 2XL Fast and Fast Wide SCSI-2 Interfaces 3.5 INCH FAMILY, HALF-HEIGHT



	ST31051 Hawk 2XL	ST32151 Hawk 2XL
Capacity		
Formatted Mbytes (512 bytes/sector)	1,050	2,147
Interface		
		Fast SCSI-2 8- and 16 bit
Performance		
Internal Transfer Rate, ZBR (Mbits/sec) External Transfer Rate (Mbytes/sec) Multisegmented Cache Buffer (Kbytes) Track-to-Track Seek, Read/Write (msec)	40 to 70 10/20 256 (8 bit) 512 (16 bit) 1	40 to 70 10/20 256 (8 bit) 512 (16 bit) 1
Average Seek, Read/Write (msec) Maximum Seek (msec) Spindle Speed (RPM) Average Latency (msec) Configuration/Organization	9/10.5 22 5,411 5.54	9/10.5 22 5,411 5.54
Discs Read/Write Heads Servo Heads Bytes per Sector (typ) Cylinders Recording Method Reliability and Data Integrity	2 4 Embedded 512 4,569 RLL (0,4,4)	4 8 Embedded 512 4,569 RLL (0,4,4)
MTBF (power on hours) Nonrecoverable Read Errors per Bits Read Auto-Park Limited Warranty (yrs)	500,000 1 per 10 ¹⁴ yes 3	500,000 1 per 10 ¹⁴ yes 5
Power Requirements +12 VDC ±5% (amps typ)	0.38 2 0.7 6.3	0.38 2 0.7 6.5
Environmental		
Operating Temperature (°C) Nonoperating Temperature (°C)	5 to 55 -40 to 70	5 to 55 -40 to 70
Physical	4/05 /	1/05 /
Height (inches/mm) Width (inches/mm) Depth (inches/mm) Weight (lb/kg)	1/25.4 4/101.6 5.74/146.1 1.5/0.68	1/25.4 4/101.6 5.74/146.1 1.5/0.68