

## Dual Port ISA High Speed RS-232 Interface

 $\epsilon$ 





Model OMG-DATASHARK

**\$149** 

- ✓ Dual Port High Speed RS-232 Interface
- ✓ 16650 Buffered UART Standard With 32 Byte FIFO Reduces Processor Interrupts
- ✓ High Speed Support for Up to 460.8 kBPS Using Enhanced Line Drivers and Receivers
- ✓ Configurable to Addresses Including COM1: - COM4: and Interrupts (3-5, 9-12, and 15) for Easy Integration
- ✓ Configurable to Non Standard Addresses to Eliminate Address Conflicts; 16 Bit Address Decoding Eliminates Windows Video Adapter Conflicts
- Standard PC Data Rates Supported to Provide Compatibility with Legacy Applications
- Second Port Can Be Disabled

Take advantage of today's high speed modems and eliminate the data communications bottleneck within your PC. The OMG-DATASHARK provides two RS-232 serial ports, flexible configuration, and supports data rates up to 460K bps. Configure the card to use standard COM1: - COM4: addresses or any one of eight additional available



Shown smaller than actual size

addresses for each port. The OMG-DATASHARK also utilizes full 16 bit I/O address decoding to avoid video address conflicts. Individually selectable IRQs (3-5, 9-12, and 15) can be matched to your available system resources.

A serial utility diskette is supplied with the OMG-DATASHARK which includes all the Windows and DOS tools necessary to verify the installation and operation of the board. Windows utilities include .INF files for Windows installation and also a Windows NT COM: Port Installation Utility. DOS utilities include a diagnostic program to verify card address and examine the UART, a diagnostic serial loopback test program and an interrupt driven DOS serial port driver.

## **Specifications**Communications chip:

16C650 UART

Number of Ports: Two RS-232 Max. Data Rate: 460.8 kBPS Max. Data Distance: Up to 50 ft.

Operating Temperature: 0 to 122 °F (-18 to 50 °C) Storage Temperature: -4 to 158 °F (-20 to 70 °C) Humidity Range: 10-90% R.H.

**Current Specifications:** 

+5 V @ 180 mA, ±12 V @ 50 mA ea

**Connector(s)**: (2) DB-9P **Physical Dimensions**:

4.9" L x 3.3" H (12.45 x 8.38 cm)

To Order (Specify Model Number)		
Model No.	Price	Description
OMG-DATASHARK	\$149	Dual Port High Speed RS-232 interface

Comes with complete operator's manual and serial utility disk.

Ordering Example: OMG-DATASHARK dual port high speed RS-232 interface, \$149.