

**producer**

<b>COLLABORATORS</b>
----------------------

	<i>TITLE :</i> producer	
<i>ACTION</i>	<i>NAME</i>	<i>DATE</i>
WRITTEN BY		February 12, 2023
		<i>SIGNATURE</i>

<b>REVISION HISTORY</b>
-------------------------

NUMBER	DATE	DESCRIPTION	NAME

# Contents

<b>1</b>	<b>producer</b>	<b>1</b>
1.1	producer.adoc	1
1.2	producer.library/GetProducer	1
1.3	producer.library/FreeProducer	2
1.4	producer.library/LoadDesignerData	3
1.5	producer.library/FreeDesignerData	3
1.6	producer.library/OpenProducerWindow	4
1.7	producer.library/CloseProducerWindow	4
1.8	producer.library/SetProducerWindowFileName	5
1.9	producer.library/SetProducerWindowAction	5
1.10	producer.library/SetProducerWindowLineNumber	6
1.11	producer.library/ProducerWindowUserAbort	6
1.12	producer.library/ProducerWindowWriteMain	7
1.13	producer.library/AddLocaleString	7
1.14	producer.library/FreeLocaleStrings	8
1.15	producer.library/WriteLocaleCT	8
1.16	producer.library/WriteLocaleCD	9

# Chapter 1

## producer

### 1.1 producer.adoc

```
GetProducer ()
FreeProducer ()
LoadDesignerData ()
FreeDesignerData ()
OpenProducerWindow ()
CloseProducerWindow ()
SetProducerWindowFileName ()
SetProducerWindowAction ()
SetProducerWindowLineNumber ()
ProducerWindowUserAbort ()
ProducerWindowWriteMain ()
AddLocaleString ()
FreeLocaleStrings ()
WriteLocaleCT ()
WriteLocaleCD ()
```

### 1.2 producer.library/GetProducer

NAME  
GetProducer - Add a dynamic node host.

---

## SYNOPSIS

```
pn = GetProducer ( void );  
d0  
  
struct ProducerNode * pn;
```

## FUNCTION

This function creates a new Producer.

## INPUTS

## RETURNS

pn - pn to be used in just about every Producer operation.

## EXAMPLE

```
pn = GetProducer();  
if (pn)  
{  
    /*  
  
    */  
    FreeProducer(pn);  
}
```

## SEE ALSO

FreeProducer()

### 1.3 producer.library/FreeProducer

## NAME

FreeProducer - Free all data and close down producer

## SYNOPSIS

```
void FreeProducer ( pn );  
A0  
  
struct ProducerNode *pn;
```

## FUNCTION

This gets rid of all data

## INPUTS

pn - ProducerNode allocated.

## EXAMPLE

```
pn = GetProducer();  
if (pn)  
{  
    /*
```

```
 */
FreeProducer (pn);
}
```

RETURNS

SEE ALSO

GetProducer()

## 1.4 producer.library/LoadDesignerData

NAME

LoadDesignerData - Load a file into a ProducerNode.

SYNOPSIS

```
res = LoadDesignerData ( pn, filename );
                        a0 A1
```

```
long res;
struct ProducerNode *pn;
char * filename;
```

FUNCTION

Load a designerfile into the ProducerNode supplied.

INPUTS

```
pn          - Your ProducerNode.
filename - Filename to load
```

RETURNS

res - 0 if OK, error code otherwise.

SEE ALSO

FreeDesignerData()

## 1.5 producer.library/FreeDesignerData

NAME

FreeDesignerData - frees all data loaded into a ProducerNode

SYNOPSIS

```
ExpungeDataBases ( pn );
                  A0
```

```
struct ProducerNode *pn;
```

---

## FUNCTION

Free all allocated memory for data structures.

## INPUTS

pn - Your ProducerNode

## SEE ALSO

LoadDesignerData()

## 1.6 producer.library/OpenProducerWindow

## NAME

OpenProducerWindow - Open producers window.

## SYNOPSIS

```
res = OpenProducerWindow( pn, title );  
                                A0 A1
```

```
long res;  
struct ProducerNode * pn;  
char * title;
```

## FUNCTION

This function attempts to open a window associated with the supplied ProducerNode. This window is now the standard look for the Producers.

## RETURNS

res - 1 if success, 0 if failure.

## SEE ALSO

CloseProducerWindow()

## 1.7 producer.library/CloseProducerWindow

## NAME

CloseProducerWindow - Close Window associated with a producer.

## SYNOPSIS

```
CloseProducerWindow (pn);  
                                A0
```

```
struct ProducerNode *pn;
```

## FUNCTION

This function is used to close your producer window. It will be done automatically when you free your producer.

---

## INPUTS

pn ProducerNode handle.

## RETURNS

## SEE ALSO

OpenProducerWindow()

## 1.8 producer.library/SetProducerWindowFileName

## NAME

SetProducerWindowFileName - Set text in gadget in producer window..

## SYNOPSIS

```
SetProducerWindowFileName( pn, filename );
                          A0 A1
```

```
struct ProducerNode *pn
char *filename
```

## FUNCTION

This function is used to change the contents of the FileName gadget in the producer window.

## INPUTS

pn - Producer.  
filename - Text to place.

## RETURNS

## SEE ALSO

SetProducerWindowAction()  
,  
SetProducerWindowLineNumber()

## 1.9 producer.library/SetProducerWindowAction

## NAME

SetProducerWindowAction - Set text in gadget in producer window..

## SYNOPSIS

```
SetProducerWindowAction( pn, action );
                          A0 A1
```

```
struct ProducerNode *pn;
char *action;
```

## FUNCTION

This function is used to change the contents of the Action gadget in the producer window.

## INPUTS

pn - Producer.  
action - Text to place.

## RETURNS

## SEE ALSO

```
SetProducerWindowFileName()  
,  
SetProducerWindowLineNumber()
```

## 1.10 producer.library/SetProducerWindowLineNumber

## NAME

SetProducerWindowLineNumber - Set text in gadget in producer window..

## SYNOPSIS

```
SetProducerWindowLineNumber( pn, number );  
A0 D0
```

```
struct ProducerNode *pn;  
long number;
```

## FUNCTION

This function is used to change the contents of the LineNumber gadget in the producer window.

## INPUTS

pn - Producer.  
LineNumber - Number to place.

## RETURNS

## SEE ALSO

```
SetProducerWindowAction()  
,  
SetProducerWindowLineNumber()
```

## 1.11 producer.library/ProducerWindowUserAbort

## NAME

ProducerWindowUserAbort - See if user has aborted the production.

## SYNOPSIS

```
ret = ProducerWindowUserAbort( pn );
                                A0
```

```
struct ProducerNode *pn;
long ret;
```

**FUNCTION**

This function is used to change test whether the user has requested an abort by the closegadget, the abortgadget or by pressing 'A'.

**INPUTS**

pn - Producer.

**RETURNS**

1 if user aborts, 0 otherwise.

## 1.12 producer.library/ProducerWindowWriteMain

**NAME**

ProducerWindowWriteMain - See if user wishes to overwrite main file.

**SYNOPSIS**

```
ret = ProducerWindowWriteMain( pn, filename );
                                A0 A1
```

```
struct ProducerNode *pn;
char * filename;
long ret;
```

**FUNCTION**

This function is used to find out if the already exists a Main file. If it does then this will allow the user to choose whether to overwrite it or not. None and All are handled as well.

**INPUTS**

pn - Producer.  
filename - Prospective Main filename.

**RETURNS**

1 if user selects write file, 0 otherwise.

## 1.13 producer.library/AddLocaleString

**NAME**

AddLocaleString - Add string to locale list.

**SYNOPSIS**

```
ret = AddLocaleString( pn, string, label, comment );
                        A0 A1      D0      D1
```

```
struct ProducerNode *pn;
```

```
long ret;
```

#### FUNCTION

This function is used to add a string to the list of strings that will be written in any .cd or .ct file you produce in the Producer.

This list is available in the ProducerNode and should be converted into the default strings in your program. This list also contains extra strings defined in the locale window in the Designer. The first item in the list has label with value 0.

#### INPUTS

pn - Producer.  
string - Text.  
label - Label to be used in code.  
comment - Comment to be placed in .cd and .ct files.

#### RETURNS

1 if OK, 0 otherwise.

## 1.14 producer.library/FreeLocaleStrings

#### NAME

FreeLocaleStrings - Free locale list.

#### SYNOPSIS

```
FreeLocaleStrings( pn );  
A0
```

```
struct ProducerNode *pn;
```

#### FUNCTION

This will free all locale strings, you will probably never need it.

#### INPUTS

pn - Producer.

#### RETURNS

## 1.15 producer.library/WriteLocaleCT

#### NAME

WriteLocaleCT - Write .ct file.

#### SYNOPSIS

```
WriteLocaleCT( pn );  
A0
```

```
struct ProducerNode *pn;
```

#### FUNCTION

---

This will write a .ct file for use in flexcat etc.

**INPUTS**

pn - Producer.

**RETURNS**

1 if OK, 0 otherwise.

## 1.16 producer.library/WriteLocaleCD

**NAME**

WriteLocaleCD - Write .CD file

**SYNOPSIS**

```
WriteLocaleCD( pn );  
              A0
```

```
struct ProducerNode *pn;
```

**FUNCTION**

This will write a .cd file for use in flexcat etc.

**INPUTS**

pn - Producer.

**RETURNS**

1 if OK, 0 otherwise.

---