

Alcuin

Stephan Schupfer

Copyright © 1996 Stephan Schupfer

COLLABORATORS

	<i>TITLE :</i> Alcuin		
<i>ACTION</i>	<i>NAME</i>	<i>DATE</i>	<i>SIGNATURE</i>
WRITTEN BY	Stephan Schupfer	February 12, 2023	

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME

Contents

1	Alcuin	1
1.1	Alcuin Usage Guide	1
1.2	Overview	2
1.3	Registration	2
1.4	Support	3
1.5	Installation	3
1.6	How to download a copy of the ROM	3
1.7	Needed	5
1.8	Using Alcuin	5
1.9	Start from Workbench	5
1.10	Start from CLI	7
1.11	The Keyboard	7
1.12	The Menu	7
1.13	Transfer files	8
1.14	Using cards	8
1.15	About the emulation	9
1.16	Known bugs	9
1.17	Legal	9
1.18	bugreports	10
1.19	Thanks	11
1.20	The Author	11
1.21	FAQ	12
1.22	History	12
1.23	Future	12

Chapter 1

Alcuin

1.1 Alcuin Usage Guide

ALCUIN

Version 1.0

A Saturn CPU emulator for Amiga computers
used to emulate HP 48 S/SX/G/GX calculators

© Copyright 1996 Stephan Schupfer

Overview

What is Alcuin ?

Registration

Limits of the unregistered version

Support

Where to find Alcuin ?

Installation

How to install Alcuin ?

Usage

How to use Alcuin

About the emulation

How to use Alcuin

Bugs

Known bugs

FAQ

Frequently Asked Questions

Copyright

Copyright etc..

Bug reports
How to Report Bugs ?

Credits
The author wishes to thank ...

The author
About the Author

History
History of Alcuin

Future
Future of Alcuin

1.2 Overview

Alcuin is a multitasking HP48 CPU emulator for the Amiga. The emulation runs as a normal task under the Amiga operating system, so that Amiga and Alcuin can be used concurrently. If you get a rom dump from a HP 48 (S/SX/G/GX) calculator, you be able to emulate these calculators on your amiga.

Attention

This emulator is capable of providing a faithful replication of the HP48. In order to do so, it requires a copy of the ROM software from YOUR calculator. In order to avoid breaking copyright laws, and upsetting HP, you MUST BE THE PROUD OWNER OF AN HP48 before running this program.

1.3 Registration

Alcuin is SHAREWARE. To ease your decision wheather to pay the unregistered version has some limitiations:

- No filetransfer is supported
- The emulator is not loading its state - so everytime you startup the emulator is doing a reset, which takes some time.
(with state-file the emulator is immediately ready to use, to continue work where you stopped last time)
- Plug-in modules won't be loaded.

The shareware fee is ATS 200.- or DM 30.- or US\$ 20.- for users in europe. Outside europe the fee is US\$25.-.

Registered users receive a personal keyfile, which enables the missing functions. This keyfile will work with all future versions of Alcuin, so as a registered user you can always download the most recent freely distributable version.

How to become a registered user ?

The simple way is to fill in the file "OrderForm", to print it out, sign it (in this order, if possible), put it in an envelope together with the registration fee and send it to

me
. I won't accept order forms which are not signed.

The keyfile will be sent to you either uuencoded via EMail (prefered) or on floppy disk (as you like it).

1.4 Support

The newest version of Alcuin is on AMINET in the Directory: misc/emu

I also think about adding a page to my homepage in the www.

<http://www.ping.at/members/schupfer/> or
<http://www.sbox.tu-graz.ac.at/home/schupfer/>

1.5 Installation

First take a look what is needed
, to see if your Amiga is able to run Alcuin.

To Install the Program on your Harddisk use the supplied Installerprogramm. Then

make a copy of the ROM of your HP

The created file is called rom.dump.

Rename it to Alcuin_ROM and copy it in the directory created by the installer called Alcuin:.

Now are you ready to start the emulator.

1.6 How to download a copy of the ROM

HOW TO DOWNLOAD A COPY OF THE ROM

=====

The emulator works by executing an image of the HP48 ROM. In order to run the emulator you must have a version of your ROM on the system.

* This includes the HIDDEN ROM. Please don't use DUMP programs, that *
* don't dump the HIDDEN ROM. The emulator won't run. *

To get a memory dump you need to do the following:

- Download the file 'romdump/ROMDump' to your HP.
- To capture a complete ROM, start kermit, or any other terminal programm which is capable to emulate the kermit protocol, on your computer, connect your calculator with your computer, set the speed to 9600 baud and enable 'log session' to save the received data, then 'connect'.
- On a HP48 S/SX type '#0h #7FFF0h ROMDump',
on a HP48 G/GX type '#0h #FFFF0h ROMDump'.
This will take about 15 minutes on the S/SX, 30 minutes on the G/GX.
- When done, save if necessary the 'log-file' and quit your terminal programm.

Your ROM should now be in a file called 'session.log' or simmilar.

Now you have a file containing lines like

```
#00000:2369B108DADF1008
...
```

This has to be converted to a binary ROM for Alcuin.

Run the command: 'dump2rom session.log'

This will convert your dump into a rom file readable by the emulator called 'rom.dump'.

CHECK the file with the program 'checkrom'.

Type: 'checkrom rom.dump'. It should say:

```
ROM Version is HP48-A
ROM CRC reads 0xcb76 (for Rev. A, will be different for other ROMs)
IROM OK: ROM CRC test passed.
```

or

```
ROM Version is HP48-R
ROM CRC 1 reads 0xdfed (for Rev. R, will be different for other ROMs)
ROM CRC 2 reads 0xf0b1 (          --- " ---          )
IROM OK: ROM CRC test passed.
```

If the test failed, something went wrong transferring the ROM. Don't start thinking about the size or the nibbles in 'rom.dump'. That's all correct. Do the Transfer again.

If you know how to do it, you could of course only transfer the 'broken' part of the dump, using e.g. '#60000h #60080h ROMDump' and fix these lines in 'session.log'.

1.7 Needed

To use Alcuin you need :

- The Amiga must have at least a 68020 processor.
(All programmms are compiled for 68020-40 CPUs)
I think with a CPU less powerful than a 68020 the emulator is too slow to be useable.
I don't know if Alcuin works with 68060 CPU, so drop me a note if you do - especially some speed informations)
- The Amiga must be running under at least Kickstart 2.04 and Workbench 2.1.
- A HP 48 (S/SX/G/GX) caculator to get a legal copy of the ROM.
- A serial cable to connect your HP 48 to your computer to get a rom-dump

1.8 Using Alcuin

Using Alcuin

Start from Worbench

Start from CLI

How to download a copy of the ROM

The Keyboard

The Menu

Transfer files

Using RAM and ROM cards

1.9 Start from Workbench

Workbench :

Set the Tooltypes according your desired configuration
and just doubleclick the Alcuin icon

ATTENTION ! If you change the configuration of the RAM or ROM modules,
you have to quit the emulator first in switched OFF state,
otherwise the memory content of the emulated HP48 can get
lost.

Following Tooltypes are supported

- DOUBLE_SIZE

If this Tooltype is set you get everything in double size
This is especially for users with graphic-cards which use big
Workbenchscreens like 1024x768 or 1280x1024 or more.
Otherwise you get a normal size display, which is more usable
for screensizes like 640x400.

- COMPACT

This is for a compacter keyboard layout, to make Alcuin also
useable for a 640x200 screensize. If someone likes this layout
more it can also be used for the double resolution.

- RESET

The Emulator is doing a reset on startup.

- INITIALIZE

The Emulator is trying to read the Alcuin_STATE and Alcuin_RAM files
from disk.

- PORT1=RAM (or ROM)

The Emulator is simulating a card plugged in in port1 and
is reading the Alcuin_PORT1 file from disk.
You can select if the plugged in card is RAM or ROM.

- PORT2=RAM (or ROM)

The Emulator is simulating a card plugged in in port2 and
is reading the Alcuin_PORT2 file from disk.
You can select if the plugged in card is RAM or ROM.

- SERIAL=serial.device

Select your favourite serial.device like SERIAL=serial.device for
the serial device.
If not set the emulator uses the serial.device.

- UNIT=0

Select the unit of your serial device like UNIT=0 or UNIT=1.
If not set the emulator is using unit 0 as default.
The maximum unit number is 3.

- XPOS=100

The x-position of the Alcuin window at startup (e.g. 100)

- YPOS=100

The y-position of the Alcuin window at startup (e.g. 100)

1.10 Start from CLI

CLI :

```
Alcuin [DOUBLE/S,COMPACT/S,RESET/S,INIT/S,P1=PORT1/K,P2=PORT2/K,
SER=SERIAL/K,U=UNIT/N,X=XPOS/N,Y=YPOS/N,HELP/S]
```

The options are equal to the
Tooltypes
at start
from the workbench.

- HELP With this option you will get an overview about all options

1.11 The Keyboard

You can use the emulator via mouse or keyboard.

The keys A-Z are similar to those keys, where you get A-Z in the alpha mode. I also think you will have no problems to find the most other keys. But here are some special:

HP 48 G/GX/S/SX

HP	Amiga

· alpha	Ctrl
· shift left	Shift
· shift right	Alt
· ON	ESC

I also have added some special functions on the function keys

- | | | |
|----------------|-----|-----------------------------|
| · ON A F | F1 | Reset |
| · ON B | F2 | Oops (Break an ON- command) |
| · ON C | F3 | Warmstart |
| · ON D | F4 | Testmode |
| · ON E | F5 | Looping selftest |
| · ON 4 | F6 | Cancel Alarm |
| · ON 1 | F7 | Screen dump |
| · ON + | F8 | More contrast |
| · ON - | F9 | Less contrast |
| · ON SPC | F10 | Coma mode |

1.12 The Menu

- About ... open window with infotext about the author
- Reset ... perform a reset of the emulator
- Iconify ... iconify Alcuin
- Exit ... exit Alcuin without saving the state-file
- Save & Exit ... exit Alcuin and save the Alcuin state-file

1.13 Transfer files

Transfer files

The HP 48 has two ports:

- wire (a serial port)
- IR (the built-in infrared port)

The Amiga has no infrared port as far as i know, therefore if you transfer files via wire or IR you always transfer the files via the selected serial port of the Amiga.

If there is a need for a second serial port, leave me a note and i will think about a implementation in the next version.

To transfer files, connect your hp to the serial port of your Amiga and you can transfer files from the emulator to your HP 48 and vice versa.

Because the emulator is slow it is better to use the kermit protocol than the xmodem protocol.

1.14 Using cards

Using cards

Emulating a HP48S or HP48G, you can not use RAM or ROM cards !
For the HP48SX or HP48GX you can create empty RAM cards with the supplied program mkcard.

Using cards you need the right entry in the Tooltypes or the right commandline specifying the card.

ATTENTION ! On a real HP48 it is only allowed to change plug-in modules on a switched-OFF calculator. Using Alcuin you will rarely switch of the calculator, but if you want to change the settings of your plug-in-modules, you have to save and quit the emulator in switched-OFF state first.

HP48GX

Emulating a HP48GX you have 2 Ports.

Port 1 has a maximum capacity of 128 KB and Port 2 has a maximum capacity of 4 MB.

Via the tooltypes you can select if the card is a RAM or a ROM card. I don't have ROM cards, therefore i don't know how to make a image and use it with the emulator, but i think it's no problem to change the supplied program dump2rom.

If there is a RAM card in port 1 you can add the RAM to the system RAM.

HP48SX

2 - 128kB RAM cards

1.15 About the emulation

Alcuin is slower than a real HP :-).

A HP 48 S/SX ROM is much faster than a G/GX ROM but offers less functions.

Alcuin is tested on following Amigas:

```
Amiga 2000, OS 3.1 , 1MB ChipRAM, 4 MB FastrAM
+ Derringer 40Mhz 68030, 66MHz 68882, 16 MB 32BitRAM
+ Picasso II with CybergraphX WB emulation
```

I tested Alcuin with standard ECS and CybergraphX 8-Bit workbench screens. I only have an HP48GX, therefor my experiences with the emulation of HP48 (S/SX/G) is low. If you use any of this systems please tell me how the emulation works.

1.16 Known bugs

- Systemtest shows a bug in the ROM.
- Starting Alcuin, there might be a stop and nothing happens. - A keypress will fix this.
- Because of the lack of betatesters, ther can be bugs due to different systems or system-configurations.

1.17 Legal

The program "Alcuin", the "hp48.font" and this manual are © ←
Copyright 1995

Stephan Schupfer.

The distribution of the programs is free as long as following rules are repected:

- All programs and documentation files remain unchanged.
- The package is always distributed in its complete form.
- No profit must be made by distributing Alcuin, especially the price of a disk containing Alcuin may not exceed US\$ 5,- (or equivalent amounts in other currencies).
- It is free to distribute Alcuin over bulletin board systems and networks.
- It is not allowed to distribute the program in any commercial product without a written consent of the author.

All rights for commercial use remain at the
author

The programs "checkrom", "dump2rom", mkcard" and "ROMDump" are © Copyright 1994 Eddie C. Dost and are free software under the terms of the GNU General Public License as published by the Free Software Foundation.

The keyfile that registered users will receive, must only be installed on one computer and in no case passed on to others. Offences will result in penal prosecution by me. With your signature on the order form, you accept these conditions.

The program is presented to the users as it is, without any warranty of any kind, be it expressed or implicit. Anyone using this programs agrees to incur the risk of using it for himself. In no way can the author be made responsible for any damage directly or indirectly caused by the use or misuse of the program.

The HP ROM files useable for running Alcuin are not part of Alcuin and copyrighted by HP. The author will not take upon himself the responsibility for the legal consequences, an illegal use of such a ROM file can have.

"Amiga" and "Commodore" are registered trademarks of Escom AG, Bochum.

"HP" is a registered trademark of Hewlett-Packard Co.

Names of other hardware and software items mentioned in this manual and in program texts are in most cases registered trade marks of the respective companies and not marked as such. So the lack of such a note may not be used as an indication that these names are free.

1.18 bugreports

ATTENTION ! Please do not send me questions about how the HP48 ←
works or
using the HP48. Please read the manual you got with your HP,
and/or the FAQ of the HP48 newsgroups.

If you find a bug or a misfeature in Alcuin, or have an idea how to make things better, then please drop me a note so I'll be able to improve Alcuin in the future.

My address can be found
here

Important for a bug report is the following information:

- Version of Alcuin (can be found by doing "version Alcuin" from Shell)
 - Used Amiga configuration (e.g. 68030,..,2MB Chip,.. OS 3.0,..serial.device,)
 - Used graphicsmode of the Workbench (e.g. ECS 4 Bit, .., CyberGraphX 8 Bit, ..)
 - Used HP48 ROM version (e.g. GX : P etc.)
 - Information about installed startup programs on the Amiga
 - Information about installed programmes on Alcuin
 - Alcuin settings
-

- Detailed description what program or command produces the bug and how it can be reproduced.

But first please look, if it's a
known bug

.

1.19 Thanks

I would like to thank

- Eddie C. Dost <edc@POOL.Informatik.RWTH-Aachen.DE>
for x48 (a hp48 emulator for unix)
and for his powerful utilities to make a ROM
and also for his help when i had problems !
- Paul Fox <fox@demon.co.uk>
for em48 (a hp48 emulator for unix)
on which x48 is based on
- Mika Heiskanen mheiskan@vipunen.hut.fi
for his document about the HP48 and saturn CPU
- Sebastien Carlier <sebc@cybera.anet.fr>
for Emu48 - what a speed ;-(
- Hewlett Packard for their powerful calculators
- Amiga Technologies for keeping Amiga alive.

1.20 The Author

Software development is a way to keep the Amiga alive !

My address is:

Stephan Schupfer
Brockmanngasse 69
8010 Graz
Austria
Europe

Email:

schupfer@sbox.tu-graz.ac.at

WWW:

<http://www.ping.at/members/schupfer/>
<http://www.sbox.tu-graz.ac.at/home/schupfer/>

Questions, criticism, suggestions and
bugreports
are always welcome.

Email is preferred !

Please understand that I can't answer every letter/mail personally.

Under no circumstance will I send you ROM files, not even "under

friends"! No chance!

1.21 FAQ

Frequently Asked Questions

* Why uses Alcuin the cybergraphics.library ?

For the display routines, Alcuin uses BITMAPS. But the structure of the bitmaps can be different (planar for ECS and AGA, chunky for graphic boards). Therefore Alcuin checks the bitmap format. Is it not STANDARD (ECS,AGA), Alcuin thinks it is the chunky format of the CyberGraphX WB emulation (8 Bit). Other formats are currently not supported. If there is a use on other formats, i need some developer informations on that format. If there is a use to implement the 15/16/24 bit versions of the CyberGraphX, i think about implementation.

1.22 History

History

V1.0 25.April.96
- first public release

V1.01 03.May.96
- code cleanup in CPU functions (major speed improvement)
- code cleanup in display functions
- new memory handler (bug in ROM)
- fixed openlib version stuff - only kickstart 3.0+ supported anymore !
- removed subtask structure
- changed the delays in shutdown - multitasking friendlier.
- new sound routine

1.23 Future

Future

I will contionue work on this product and support it where I have the time, and would therefore appreciate any bug-reports, ideas, gifts, etc.

i think about of implementing next:

- Get rid of all bugs ;-)
 - More speed is always welcome
 - Load and save files direct to the emulator.
-

- Support for more languages