INIT Files Definitions

     NOTE: Data Captured - Date and time data was collected [TattleINIT]
• Total System Heap Space Used = Total bytes taken by listed INIT's in
          System Heap [TattleINIT]
• Total High Memory Space Used = Total bytes taken by listed INIT's in
          High Memory [TattleINIT]

          +

• Extension/INIT# = Order which this file was executed
   ◊ Extension/INIT Name = File name
   ◊ Version = Version number
   ◊ File Integrity =   Reports if file is damaged   [Registered +Checking On]
   ◊ Type = Finder Type of file
   ◊ Creator = Finder Creator of File
   ◊ Modified = Date/Time File was modified
   ◊ Requested System Heap Space = The number of bytes requested to be
              available in the system heap by the sysz Resource.   If this amount is zero,
              then the sysz resource was not present or was set to zero and the
              minimum of 16K bytes was initially allocated
   ◊ System Heap Space Used = The number of bytes of space that this
              extension is currently taking up in your system heap.   This space is
              unavailable to applications so if you are low on memory, you should look
              here for memory eaters.   To regain the memory, simply remove the file
              from the folder specified below   [TattleINIT]
   ◊ High Memory Used = The Number of bytes of memory that this extension is
              using above application memory.   Look at this number along with the
              System Heap Space to find memory eaters   [TattleINIT]
   ◊ Path Name = Location of File
   ◊ Files Used by (Extension Type) : List of files which were opened by the
              extension [TattleINIT]