

IconGad

COLLABORATORS

	<i>TITLE :</i> IconGad		
<i>ACTION</i>	<i>NAME</i>	<i>DATE</i>	<i>SIGNATURE</i>
WRITTEN BY		August 7, 2022	

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME

Contents

1	IconGad	1
1.1	IconGad_plugin: Introduction	1
1.2	IconGad_plugin: Usage	1
1.3	IconGad_plugin: History	2

Chapter 1

IconGad

1.1 IconGad_plugin: Introduction

IconGad plugin

by Fabio Rotondo <fsoft@intercom.it>
and Jason Hulance <jason@fsel.com>

NOTE: many thanks should go to
Jason Hulance, who helped me fixing this PLUGIN.

This PLUGIN is inspired on sources by Will Harwood.

IconGad plugin is a smart PLUGIN which will
allow you to use Icons graphics as gadgets.

Usage

History

1.2 IconGad_plugin: Usage

IconGad plugin

IconGad plugin has these publically accessible methods:

```
PROC init(iconname) OF icongad_plugin
```

This is the initailization method.

You have to call this when you are creating the
PLUGIN.

iconname - The name of the icon
(without the ".info" extension)

See the example source code, IconGad_demo.e, for some actual examples
of this plugin in use.

1.3 IconGad_plugin: History

v1.0 (01.12.97)

- o Initial release.