

EFMUILib

Andreas Håkansson Fouret

COLLABORATORS

	<i>TITLE :</i> EFMUILib		
<i>ACTION</i>	<i>NAME</i>	<i>DATE</i>	<i>SIGNATURE</i>
WRITTEN BY	Andreas Håkansson Fouret	August 7, 2022	

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME

Contents

1	EFMUILib	1
1.1	Welcome	1
1.2	Introduction	4
1.3	Disclaimer	4
1.4	Using	4
1.5	FAQ	5
1.6	Authors	6
1.7	History	6
1.8	Future	7
1.9	About MUI	7
1.10	Vivid Imagination	8
1.11	MUISetMaximumTags max	9
1.12	MUIApplicationTitle title\$	9
1.13	MUIApplicationVersion version\$	9
1.14	MUIApplicationCopyright copyright\$	10
1.15	MUIApplicationAuthor author\$	10
1.16	MUIApplicationDescription description\$	11
1.17	MUIApplicationBase base\$	11
1.18	MUIAddApplicationTags &TagList Tag, Value [, Tag, Value...]	12
1.19	MUICreateApplication	12
1.20	MUIRemoveApplication	13
1.21	MUIApplicationLoc	13
1.22	MUIApplicationObj To MUIObject#	14
1.23	MUIAddSubWindow MUIObject#	14
1.24	MUIFreeObject MUIObject#	14
1.25	MUICreateWindow MUIObject#,title\$ [,id\$ [,MUIObject#]]	15
1.26	MUIOpenWindow MUIObject#	15
1.27	MUICloseWindow MUIObject#	16
1.28	MUICreateMenu MUIObject#,GTMenuItem#,Flags [,TitleUData1 [,...]]	16
1.29	MUISetMenu To MUIObject#,MUIObject#	16

1.30	MUIObjLoc (MUIObject#)	17
1.31	MUIRequest To MUIObject#,Flags,Title\$,Gadgets\$,Format\$ [,Param...]	17
1.32	MUIAddTags MUIObject#, &TagList Tag, Value [,Tag, Value...]	17
1.33	MUINewObject MUIObject#,Class\$, &TagList Tag, Value [,Tag, Value...]	18
1.34	MUIMakeObject MUIObject#,Type, &TagList Tag, Value [,Tag, Value...]	18
1.35	MUIHVSpace MUIObject#	18
1.36	MUIHSpace MUIObject#,x	19
1.37	MUIVSpace MUIObject#,x	19
1.38	MUIString MUIObject#,Contents\$,MaxLen	19
1.39	MUIKeyString MUIObject#,Contents,MaxLen,ControlChar\$	20
1.40	MUICheckMark MUIObject#,Selected	20
1.41	MUIKeyCheckMark MUIObject#,Selected,ControlChar\$	20
1.42	MUISimpleButton MUIObject#,Name\$	21
1.43	MUIKeyButton MUIObject#,Name\$,Key\$	21
1.44	MUICycle MUIObject#, Entry\$ [,Entry\$...] *Array	22
1.45	MUIKeyCycle MUIObject#,Key\$, Entry\$ [,Entry\$...] *Array	22
1.46	MUIRadio MUIObject#,Name\$, Entry\$ [,Entry\$...] *Array	22
1.47	MUIKeyRadio MUIObject#,Key\$,Name\$, Entry\$ [,Entry\$...] *Array	23
1.48	MUISlider MUIObject#,Min,Max,Level	23
1.49	MUIKeySlider MUIObject#,Min,Max,Level,Key\$	23
1.50	MUILabel MUIObject#,Label\$,Flags	24
1.51	MUINumericButton MUIObject#,Format\$,Min,Max	24
1.52	MUIList MUIObject#,MaxEntries,Columns,Format\$ [, *Array Entry\$ [,Entry\$...]]	24
1.53	MUIListView To MUIObject#,MUIObject#	25
1.54	MUIPopButton MUIObject#,Image	25
1.55	MUIImageButton MUIObject#,Shape#	25
1.56	MUIBalanceObject MUIObject#	26
1.57	MUIAddObjHGroup To MUIObject#,MUIObject#	26
1.58	MUICreateHGroup MUIObject#	26
1.59	MUIAddObjVGroup To MUIObject#,MUIObject#	27
1.60	MUICreateVGroup MUIObject#	27
1.61	MUIAddObjPage To MUIObject#,MUIObject#	27
1.62	MUICreatePage MUIObject# ,Page1\$ [,Page2\$...] &Page\$(0)	28
1.63	MUIAddObjsHGroup To MUIObject#,MUIObject# [,MUIObject# [...]]	28
1.64	MUIAddObjsVGroup To MUIObject#,MUIObject# [,MUIObject# [...]]	29
1.65	MUIAddObjsPage To MUIObject#,MUIObject# [,MUIObject# [...]]	29
1.66	MUIInsertSingle MUIObject#,Position, Entry\$ [,Entry\$...] *Array	29
1.67	MUIRemoveSingle MUIObject#,Position	30
1.68	MUIRedrawSingle MUIObject#,Position	30

1.69	MUIListTitle MUIObject#, Title\$ [,Title\$...] *Array	31
1.70	MUISet MUIObject#, &TagList Attr,Value [,Attr,Value...]	31
1.71	MUIGet (MUIObject#,Attribute)	31
1.72	MUIDoMethod MUIObject#, Method,Tag [,Tag] &TagList	32
1.73	MUINotify MUIObject#,Tag,Value,MUIObject#, Tag [,Tag...] &TagList	32
1.74	MUINotifyApp MUIObject#,Tag,Value,ReturnID	33
1.75	MUIEvent	33
1.76	MUIWaitEvent	34
1.77	MUIFindUDData To MUIObject#,MUIObject#,UserData	34

Chapter 1

EFMUILib

1.1 Welcome

```

***** ***** ***** ** ** ***** ** ↵
***** *****
**      **      ** ** ** ** ** ** **   **   **   **   **   **   **
****   ****   ** ** ** **   **   **   **   **   **   ****
**      **      **      ** ** **   **   **   **   **   **
***** **      **      **   **** ***** ***** *****

```

Version 1.2 By Erwan Fouret
 Copyright ©1997 By Vivid Imagination

===== ↵

- Introduction
- Disclaimer
- Using
- FAQ
- Authors
- History
- Future
- About MUI
- Vivid Imagination
- MUISetMaximumTags
- MUIApplicationTitle
- MUIApplicationVersion

MUIApplicationCopyright
MUIApplicationAuthor
MUIApplicationDescription
MUIApplicationBase
MUIAddApplicationTags
MUICreateApplication
MUIRemoveApplication
MUIApplicationLoc
MUIApplicationObj
MUIAddSubWindow
MUIFreeObject
MUICreateWindow
MUIOpenWindow
MUICloseWindow
MUICreateMenu
MUISetMenu
MUIObjLoc
MUIRequest
MUIAddTags
MUINewObject
MUIMakeObject
MUIHVSpace
MUIHSpace
MUIVSpace
MUIString
MUIKeyString
MUICheckMark
MUIKeyCheckMark
MUISimpleButton

MUIKeyButton
MUICycle
MUIKeyCycle
MUIRadio
MUIKeyRadio
MUISlider
MUIKeySlider
MUILabel
MUINumericButton
MUIList
MUIListview
MUIPopButton
MUIImageButton
MUIBalanceObject
MUIAddObjHGroup
MUICreateHGroup
MUIAddObjVGroup
MUICreateVGroup
MUIAddObjPage
MUICreatePage
MUIAddObjsHGroup
MUIAddObjsVGroup
MUIAddObjsPage
MUIInsertSingle
MUIRemoveSingle
MUIRedrawSingle
MUIListTitle
MUISet

MUIGet
MUIDoMethod
MUINotify
MUINotifyApp
MUIEvent
MUIWaitEvent
MUIFindUData

1.2 Introduction

Introduction

This is the complete package to easily develop MUI applications using Blitz ↔
Basic 2.
It is as easy to create MUI applications as creating GadTools+Intuition ↔
Applications,
it's even easier!

1.3 Disclaimer

Disclaimer

You use this software at your own risk! The
authors
accept NO
responsability for any damage caused to the user, his hardware or his software.

This is freeware! You can use and distribute it as long as you don't modify the
distribution and you don't earn money with it (the price of a disk is a maximum).

If you use this lib in your program, please put our names somewhere in the doc
and in the program itself! Thank you!

1.4 Using

Using

When you create a MUI application, don't forget to include the resident mui.res
(type blitzlibs:mui.res in the resident part of compiler options).

The structure of a standard MUI application is :

```

MUIxxx                                ;create objects

MUIAddObjVGroup #g,#                  ;can be HGroup or Page
or
MUIAddObjsVGroup #G,#,#,...          ;can be HGroup or Page

MUICreateVGroup #g

MUICreateWindow #w,"Title","BASE",#g ;the second number is the first child of ←
the win

MUIAddSubWindow #w                    ;Don't forget that!

If MUICreateApplication<>True Then End

MUINotifyApp #w,#MUIA_Window_CloseRequest,1,-1
;returns -1 if the user closes the window

MUIOpenWindow #w

Repeat
  ev.l=MUIWaitEvent
Until ev=-1

MUICloseWindow #w

End ;You don't need to use RemoveApplication

```

Watch out! The TRUE value for MUI is not the same as the True value for Blitz!
The first is 1 and the second is -1.

1.5 FAQ

FAQ

- Q. When I compile my program, the window opens well, with the right gadgets, but ←
the
system is blocked, I can't do anything! What's the problem?
- A. You should have used WaitEvent instead of MUIWaitEvent.
- Q. When I compile my program the window doesn't open, however I use the ←
MUIOpenWindow
with the right number! What can I do?
- A. You must have forgotten to add the command MUIAddSubWindow #.
- Q. Where can I find the autodocs of MUI?
- A. Download the archive mui38dev.lha (dev/mui).
- Q. Where can I find the source of the lib and of the installation utilities?

A. They are available on Aminet : dev/basic/EFMUILibSrc.lha

Q. The lib doesn't work! However I used the Install script! Why?

A. Unfortunately, the lib must have the number of 8. If this number is already used by one of your lib, download the sources (dev/basic/EFMUILibSrc. ← lha) and change #bbmuilib=8 by #bbmuilib=# (where # is free lib number). Then compile it (don't forget to include the residents mui.res and libmacs.res, see the MethodLib (dev/basic) doc for more details on how to compile a lib)

1.6 Authors

Authors

The lib : Erwan Fouret (Erwan.Fouret@wanadoo.fr)
 The examples : Erwan Fouret and Andreas Håkansson (andy@bjuv.mail.telia.com)
 The doc : Erwan Fouret and Andreas Håkansson

IRC : If you want to chat with us, come to DALNet IRC (e.g. server irc.dal.net port 6667) on channels #Amiga and/or #Blitz. Our nicks are :

TJoMMe (Andreas Håkansson)
 WanOO (Erwan Fouret)

1.7 History

History

Version 1.2 (14.12.97)

~~~~~

.

MUIBalanceObject  
 added

.

MUINotifyApp  
 added

.

MUIAddObjsHGroup  
 added

.

MUIAddObjsVGroup  
 added

.

MUIAddObjsPage  
 added

Version 1.1a (11.12.97)

~~~~~

.

MUIImageButton

```

                : bug fixed.
·Not released in P.D.

Version 1.1 (07.12.97)
~~~~~
·MUIApplicationxxx bugs removed
.
                MUIDoMethod
                is now a command
·Menu support added :

                MUICreateMenu

                MUISetMenu

                MUIFindUData
                ·Max objects sets to 50 by default

Version 1.0 (24.11.97)
~~~~~
·First release

```

1.8 Future

```

                Future

- More examples (if necessary)
- More commands (again, if necessary)
- Perhaps the doc will be traducted in many languages, if you want
that, please
                contact us
                !

```

1.9 About MUI

About MUI

```

                MUI - MagicUserInterface

                (c) Copyright 1992-97 by Stefan Stuntz

```

MUI is a system to generate and maintain graphical user interfaces. With the aid of a preferences program, the user of an application has the ability to customize the outfit according to his personal taste.

MUI is distributed as shareware. To obtain a complete package containing lots of examples and more information about registration please look for a file called "muiXXusr.lha" (XX means the latest version number) on your local bulletin boards or on public domain disks.

If you want to register directly, feel free to send

DM 30.- or US\$ 20.-

to

Stefan Stuntz
Eduard-Spranger-Straße 7
80935 München
GERMANY

Support and online registration is available at

<http://www.sasg.com/>

1.10 Vivid Imagination

Vivid Imagination

Vivid Imagination is an amiga development group, founded by Andreas Håkansson, and is run by him and his Co-Partner Erwan Fouret. The aim of Vivid Imagination is to produce high quality games and applications for the amiga.

Vivid Imagination is structured in a way, so that each member spends his time doing what he or she is best at, this is so that the result always will be at its best. This is also to keep the group organized, in the way that the rest of the group knows who does what. The way it's structured is so that the Coders only spend their time with the programming of the software, and the graphics artists spend their time doing graphics, etc etc.

If you would be interested of joining our team, then you should look at our homepage (<http://vivid.home.ml.org>), on the JOIN US page, to read more about how to join, and what rules you have to follow as a member of Vivid Imagination. We are looking for all kind of people. Story writers (for the storyboards of games etc.), coders (Blitz Basic or Assembler), graphics artists (both 2D and 3D), musicians (preferably module makers) and people with other skills that may fit into our group.

You can get in touch with the founder (Andreas Håkansson) at andy@bjuv.mail.telia.com

Sincerely,

- Andreas Håkansson

Founder of Vivid Imagination

1.11 MUISetMaximumTags max

MUISetMaximumTags

Modes : Amiga
Syntax : MUISetMaximumTags max

Function : Set the maximum tags that will be allocated on objects creations.

Example :

```
MUISetMaximumTags 40
```

See also :

MUIAddTags

MUINewObject

1.12 MUIApplicationTitle title\$

MUIApplicationTitle

Modes : Amiga
Syntax : MUIApplicationTitle title\$

Function : Sets the title of the MUI Application.

Example :

```
MUIApplicationTitle "My OWN Application"
```

See also :

MUIApplicationVersion

MUIApplicationCopyright

MUIApplicationAuthor

MUIApplicationDescription

MUIApplicationBase

1.13 MUIApplicationVersion version\$

MUIApplicationVersion

Modes : Amiga

Syntax : MUIApplicationVersion version\$

Function : Sets the version of the MUI Application.

Example :

```
MUIApplicationVersion "$VER: MyApp Version 1.0 (17.11.97) "
```

See also :

MUIApplicationTitle

MUIApplicationCopyright

MUIApplicationAuthor

MUIApplicationDescription

MUIApplicationBase

1.14 MUIApplicationCopyright copyright\$

MUIApplicationCopyright

Modes : Amiga

Syntax : MUIApplicationCopyright copyright\$

Function : Sets the copyright of the MUI Application.

Example :

```
MUIApplicationCopyright "(c)1997 by Me"
```

See also :

MUIApplicationTitle

MUIApplicationVersion

MUIApplicationAuthor

MUIApplicationDescription

MUIApplicationBase

1.15 MUIApplicationAuthor author\$

MUIApplicationAuthor

Modes : Amiga

Syntax : MUIApplicationAuthor author\$

Function : Sets the author of the MUI Application.

Example :

```
MUIApplicationAuthor "Me, of course"
```

See also :

```
MUIApplicationTitle
```

```
MUIApplicationVersion
```

```
MUIApplicationCopyright
```

```
MUIApplicationDescription
```

```
MUIApplicationBase
```

1.16 MUIApplicationDescription description\$

```
MUIApplicationDescription
```

Modes : Amiga

Syntax : MUIApplicationDescription description\$

Function : Sets the description of the MUI Application.

Example :

```
MUIApplicationDescription "This is a test application"
```

See also :

```
MUIApplicationTitle
```

```
MUIApplicationVersion
```

```
MUIApplicationCopyright
```

```
MUIApplicationAuthor
```

```
MUIApplicationBase
```

1.17 MUIApplicationBase base\$

```
MUIApplicationBase
```

Modes : Amiga

Syntax : MUIApplicationBase base\$

Function : Sets the base of the MUI Application.

Example :

```
MUIApplicationBase "MYAPPLICATION"
```

See also :

MUIApplicationTitle
MUIApplicationVersion
MUIApplicationCopyright
MUIApplicationAuthor
MUIApplicationDescription

1.18 MUIAddApplicationTags &TagList | Tag,Value [,Tag,Value...]

MUIAddApplicationTags

Modes : Amiga
Syntax : MUIApplicationTags &TagList | Tag,Value [,Tag,Value...]

Function : Adds some tags to the application.

Example :

```
MUIAddApplicationTags #MUIA_Application_SingleTask,0
```

See also :

MUICreateApplication

1.19 MUICreateApplication

MUICreateApplication

Modes : Amiga
Syntax : MUICreateApplication

Function : Creates the MUI application. Returns True (-1) if the application has been successfully created.

Example :

```
If MUICreateApplication<>True Then End
```

See also :

MUIAddApplicationTags
MUIRemoveApplication
MUIApplicationLoc
MUIApplicationObj

1.20 MUIRemoveApplication

MUIRemoveApplication

Modes : Amiga
 Syntax : MUIRemoveApplication

Function : Removes the MUI Application.

Example :

```
MUIRemoveApplication
```

See also :

MUICreateApplication

1.21 MUIApplicationLoc

MUIApplicationLoc

Modes : Amiga
 Syntax : =MUIApplicationLoc

Function : Returns the address of the application structure.
 This structure is the same as others MUIObjects :

```
NEWTYPED, MUIObject
  adr.l           ;00 : Address of the object
  kind.w         ;04 : Kind of the object
  tagl.l         ;06 : Address of the taglist
  tagp.w         ;10 : Pointer of the taglist
  size.w         ;12 : Size of the taglist
  special.l      ;14 : Special Info
  spesize.w     ;18 : Special info size
  spe2.l        ;20 : Special Info 2 (Hook)
  spe2size.w    ;24 : Special Info 2 size
End NEWTYPE     ;26 : SizeOf
```

Where kind is :

```
#kind_noting=-1 ;Nothing
#kind_app=0     ;Application Object
#kind_win=1     ;Window Object
#kind_menu=2   ;Menu Object (not available)
#kind_gadget=3 ;Gadget Object
#kind_label=4  ;Label Object
#kind_other=5  ;Other Object
```

Example :

```
*app.MUIObject=MUIApplicationLoc
```

See also :

MUICreateApplication

MUIApplicationObj

1.22 MUIApplicationObj To MUIObject#

MUIApplicationObj

Modes : Amiga
Syntax : MUIApplicationObj To MUIObject#

Function : Puts the application object into the MUIObject#.

Example :

```
MUIApplicationObj 11
MUINotify 10, #MUIA_Window_CloseRequest, 1, 11, #MUIM_Application_ReturnID, -1
```

N.B. : This not very useful now, use
MUINotifyApp
instead.

See also :

MUICreateApplication

MUIApplicationLoc

MUINotify

1.23 MUIAddSubWindow MUIObject#

MUIAddSubWindow

Modes : Amiga
Syntax : MUIAddSubWindow MUIObject#

Function : Adds the window MUIObject# to the application.

Note : The Application must not be created when using this function ↔

Example :

```
MUIAddSubWindow 10
```

See also :

MUICreateWindow

1.24 MUIFreeObject MUIObject#

MUIFreeObject MUIObject#

Modes : Amiga

Syntax : MUIFreeObject MUIObject#

Function : Frees the MUIObject#.

Note : Freeing an object will free all children of this object.
e.g. freeing the application (using
MUIRemoveApplication
or using End)
will free ALL objects.

Example :

```
MUIFreeObject 0
```

See also :

1.25 MUICreateWindow MUIObject#,title\$ [,id\$ [,MUIObject#]]

MUICreateWindow

Modes : Amiga

Syntax : MUICreateWindow MUIObject#,title\$ [,id\$ [,MUIObject#]]

Function : Creates a MUI window. The second MUIObject# is the first child of the window (it's often a group).

Example :

```
MUICreateWindow 10,"My Window","MYWI",0
```

See also :

MUIOpenWindow

MUIAddSubWindow

1.26 MUIOpenWindow MUIObject#

MUIOpenWindow

Modes : Amiga

Syntax : MUIOpenWindow MUIObject#

Function : Opens the specified window.

Example :

```
MUIOpenWindow 10
```

See also :

MUICloseWindow

MUICreateWindow

1.27 MUICloseWindow MUIObject#

MUICloseWindow

Modes : Amiga

Syntax : MUICloseWindow MUIObject#

Function : Closes the specified window.

Example :

```
MUICloseWindow 10
```

See also :

MUIOpenWindow

MUICreateWindow

1.28 MUICreateMenu MUIObject#,GTMenuItem#,Flags [,TitleUData1 [...]]

MUICreateMenu

Modes : Amiga

Syntax : MUICreateMenu MUIObject#,GTMenuItem#,Flags [,TitleUData1 [...]]

Function : Creates a menu from the GTMenuItem specified.

Bugs : There is a bug with SubItem shortcuts, due to a problem into
The RIGTMenuLib.

Example :

```
MUICreateMenu 20,0,0,#MEN_PROJECT
```

See also :

MUISetMenu

1.29 MUISetMenu To MUIObject#,MUIObject#

MUISetMenu

Modes : Amiga

Syntax : MUISetMenu To MUIObject#,MUIObject#

Function : Sets a menu to a window.

Example :

```
MUISetMenu 10,20
```

See also :

MUICreateMenu

1.30 MUIObjLoc (MUIObject#)

MUIObjLoc

Modes : Amiga

Syntax : =MUIObjLoc (MUIObject#)

Function : Returns the address of the specified object if created or 0 if not.

Example :

```
*obj.l=MUIObjLoc(0)
```

See also :

1.31 MUIRequest To MUIObject#,Flags,Title\$,Gadgets\$,Format\$ [,Param...]

MUIRequest

Modes : Amiga

Syntax : MUIRequest To MUIObject#,Flags,Title\$,Gadgets\$,Format\$ [,Param...]

Function : Opens a MUI Request in the window MUIObject#.

Example :

```
MUIRequest 10,0,"Infos","OK|Yes|Yeah","We have a=%ld",a
```

See also :

MUICreateWindow

1.32 MUIAddTags MUIObject#, &TagList | Tag,Value [,Tag,Value...]

MUIAddTags

Modes : Amiga

Syntax : MUIAddTags MUIObject#, &TagList | Tag,Value [,Tag,Value...]

Function : Adds tags before the creation of an object.

Example :

```
MUIAddTags 0, #MUIA_Frame, #MUIV_Frame_Group
```

See also :

```
MUINewObject
```

```
MUISetMaximumTags
```

1.33 MUINewObject MUIObject#,Class\$, &TagList | Tag,Value [,Tag,Value...]

```
MUINewObject
```

Modes : Amiga

Syntax : MUINewObject MUIObject#,Class\$, &TagList | Tag,Value [,Tag,Value ↵
...]

Function : Creates an object of the specified class.

Example :

```
MUINewObject 1, "Balance.mui", #MUIA_CycleChain, 1
```

See also :

```
MUIMakeObject
```

```
MUIAddTags
```

```
MUISetMaximumTags
```

1.34 MUIMakeObject MUIObject#,Type, &TagList | Tag,Value [,Tag,Value...]

```
MUIMakeObject
```

Modes : Amiga

Syntax : MUIMakeObject MUIObject#,Type, &TagList | Tag,Value [,Tag,Value ↵
...]

Function : Makes an object of the specified type.

Example :

```
MUIMakeObject 2, #MUIO_HBar, 10
```

See also :

```
MUINewObject
```

1.35 MUIHVSpace MUIObject#

```
MUIHVSpace
```

Modes : Amiga

Syntax : MUIHVSpace MUIObject#

Function : Creates a simple horizontal and vertical space.

Example :

```
MUIHVSpace 3
```

See also :

MUIHSpace

MUIVSpace

1.36 MUIHSpace MUIObject#,x

MUIHSpace

Modes : Amiga

Syntax : MUIHSpace MUIObject#,x

Function : Creates a simple horizontal space of the specified size.

Example :

```
MUIHSpace 3,10
```

See also :

MUIHVSpace

MUIVSpace

1.37 MUIVSpace MUIObject#,x

MUIVSpace

Modes : Amiga

Syntax : MUIVSpace MUIObject#,x

Function : Creates a simple vertical space of specified size.

Example :

```
MUIVSpace 3,10
```

See also :

MUIHVSpace

MUIHSpace

1.38 MUIString MUIObject#,Contents\$,MaxLen

MUIString

Modes : Amiga
Syntax : MUIString MUIObject#,Contents\$,MaxLen

Function : Creates a String object.

Example :

```
MUIString 4,"This is a text",150
```

See also :

MUIKeyString

1.39 MUIKeyString MUIObject#,Contents,MaxLen,ControlChar\$

MUIKeyString

Modes : Amiga
Syntax : MUIKeyString MUIObject#,Contents\$,MaxLen,ControlChar\$

Function : Creates a String object. When the users press the key, the string is activated.

Example :

```
MUIKeyString 4,"This is a text",150,"s"
```

See also :

MUIString

1.40 MUICheckMark MUIObject#,Selected

MUICheckMark MUIObject#,Selected

Modes : Amiga
Syntax : MUICheckMark MUIObject#,Selected

Function : Creates a CheckMark object. If selected is set to true (1), the checkmark will be activated.

Example :

```
MUICheckMark 4,1
```

See also :

MUIKeyCheckMark

1.41 MUIKeyCheckMark MUIObject#,Selected,ControlChar\$

MUIKeyCheckMark

Modes : Amiga

Syntax : MUIKeyCheckMark MUIObject#,Selected,ControlChar\$

Function : Creates a CheckMark object. If selected is set to true (1), the checkmark will be activated. When the user press the key, the `↔` checkmark toggles.

Example :

```
MUICheckMark 4,1,"c"
```

See also :

MUICheckMark

1.42 MUISimpleButton MUIObject#,Name\$

MUISimpleButton

Modes : Amiga

Syntax : MUISimpleButton MUIObject#,Name\$

Function : Creates a simple button.

Example :

```
MUISimpleButton 4,"Button1"
```

See also :

MUIKeyButton

1.43 MUIKeyButton MUIObject#,Name\$,Key\$

MUIKeyButton MUIObject#,Name\$,Key\$

Modes : Amiga

Syntax : MUIKeyButton MUIObject#,Name\$,Key\$

Function : Creates a simple button. When the user presses the key, the button is activated.

Example :

```
MUIKeyButton 4,"Button1","b"
```

See also :

MUISimpleButton

1.44 MUICycle MUIObject#, Entry\$ [,Entry\$...] | *Array

MUICycle

Modes : Amiga

Syntax : MUICycle MUIObject#, Entry\$ [,Entry\$] | *Array

Function : Creates a cycle object.

Example :

```
MUICycle 5, "One", "Two", "Three", "..."
```

See also :

MUIKeyCycle

1.45 MUIKeyCycle MUIObject#,Key\$, Entry\$ [,Entry\$...] | *Array

MUIKeyCycle

Modes : Amiga

Syntax : MUIKeyCycle MUIObject#,Key\$, Entry\$ [,Entry\$] | *Array

Function : Creates a cycle object. When the users presses the key, the gadget cycles.

Example :

```
MUIKeyCycle 5, "c", "One", "Two", "Three", "..."
```

See also :

MUICycle

1.46 MUIRadio MUIObject#,Name\$, Entry\$ [,Entry\$...] | *Array

MUIRadio

Modes : Amiga

Syntax : MUIRadio MUIObject#,Name\$, Entry\$ [,Entry\$] | *Array

Function : Creates a radio object.

Example :

```
MUIRadio 5, "My Radio", "One", "Two", "Three", "..."
```

See also :

MUIKeyRadio

1.47 MUIKeyRadio MUIObject#,Key\$,Name\$, Entry\$ [,Entry\$...] | *Array

MUIKeyRadio

Modes : Amiga

Syntax : MUIKeyRadio MUIObject#,Key\$,Name\$, Entry\$ [,Entry\$] | *Array

Function : Creates a radio object. When the users presses the key, the gadget cycles.

Example :

```
MUIKeyRadio 5,"r","My Radio","One","Two","Three","..."
```

See also :

MUIRadio

1.48 MUISlider MUIObject#,Min,Max,Level

MUISlider

Modes : Amiga

Syntax : MUISlider MUIObject#,Min,Max,Level

Function : Creates a slider object. "level" indicates the actual level of the slider.

Example :

```
MUISlider 5,0,100,99
```

See also :

MUIKeySlider

1.49 MUIKeySlider MUIObject#,Min,Max,Level,Key\$

MUIKeySlider

Modes : Amiga

Syntax : MUIKeySlider MUIObject#,Min,Max,Level,Key\$

Function : Creates a slider object. "level" indicates the actual level of the slider. When the user presses the key, the level is changed.

Example :

```
MUIKeySlider 5,0,100,99,"s"
```

See also :

MUISlider

1.50 MUILabel MUIObject#,Label\$,Flags

MUILabel

Modes : Amiga
 Syntax : MUILabel MUIObject#,Label\$,Flags

Function : Creates a label. The flags are defined in the autodoc file MUI_Label.doc.

Example :

```
MUILabel 6, "My Label", #MUIO_Label_Centered
```

See also :

MUIKeySlider

1.51 MUINumericButton MUIObject#,Format\$,Min,Max

MUINumericButton

Modes : Amiga
 Syntax : MUINumericButton MUIObject#,Format\$,Min,Max

Function : Creates a Numeric Button. Format\$ must contain something like :
 "%ld" : Standard mong decimal format
 "%4ld" : Only 4 figures
 "%x" : In Hexadecimal

Example :

```
MUINumericButton 6, "Rating : %3ld %%", 95, 250
```

See also :

1.52 MUIList MUIObject#,MaxEntries,Columns,Format\$ [, *Array | Entry\$ [, Entry\$...]]

MUIList

Modes : Amiga
 Syntax : MUIList MUIObject#,MaxEntries,Columns,Format\$ [, *Array | Entry\$ [, ←
 Entry\$...]]

Function : Creates a simple list object that can be used in a listview.
 Format\$ indicates things like the width of the columns... See the autodoc MUI_List.doc.

Example :

```
MUIList 6, 100, 3, "BAR, BAR, "
```

See also :

```
MUIListview
MUIInsertSingle
MUIRemoveSingle
MUIRedrawSingle
MUIListTitle
```

1.53 MUIListview To MUIObject#,MUIObject#

```
MUIListview
```

```
Modes      : Amiga
Syntax     : MUIListview To MUIObject#,MUIObject#

Function   : Creates a listview using the list specified.

Example    :

            MUIListview 7,6

See also   :
            MUIList
```

1.54 MUIPopButton MUIObject#,Image

```
MUIPopButton
```

```
Modes      : Amiga
Syntax     : MUIPopButton MUIObject#,Image

Function   : Creates a pop button of the image specified (MUII_xxx).

Example    :

            MUIPopButton 8,#MUII_PopFile

See also   :
```

1.55 MUIImageButton MUIObject#,Shape#

```
MUIImageButton
```

```
Modes      : Amiga
Syntax     : MUIImageButton MUIObject#,Shape#

Function   : Creates a button showing the shape specified.
```

Example :

```
MUIImageButton 8,0
```

See also :

1.56 MUIBalanceObject MUIObject#

MUIBalanceObject

Modes : Amiga

Syntax : MUIBalanceObject MUIObject#

Function : Creates a simple Balance bar.

Example :

```
MUIBalanceObject 8
```

See also : EFBalancing example

1.57 MUIAddObjHGroup To MUIObject#,MUIObject#

MUIAddObjHGroup

Modes : Amiga

Syntax : MUIAddObjHGroup To MUIObject#,MUIObject#

Function : Adds the object (MUIObject#) to the Horizontal Group (To MUIObject ← #).

Example :

```
MUIAddObjHGroup 0,5
```

See also :

MUICreateHGroup

MUIAddObjshGroup

1.58 MUICreateHGroup MUIObject#

MUICreateHGroup

Modes : Amiga

Syntax : MUICreateHGroup MUIObject#

Function : Creates an Horizontal Group.

Example :

```
MUIAddObjHGroup 0,5
MUICreateHGroup 0
```

See also :

```
MUIAddObjHGroup
```

```
MUIAddObjsHGroup
```

1.59 MUIAddObjVGroup To MUIObject#,MUIObject#

```
MUIAddObjVGroup
```

```
Modes      : Amiga
Syntax     : MUIAddObjVGroup To MUIObject#,MUIObject#
```

Function : Adds the object (MUIObject#) to the Vertical Group (To MUIObject#).

Example :

```
MUIAddObjVGroup 0,5
```

See also :

```
MUICreateVGroup
```

```
MUIAddObjsVGroup
```

1.60 MUICreateVGroup MUIObject#

```
MUICreateVGroup
```

```
Modes      : Amiga
Syntax     : MUICreateVGroup MUIObject#
```

Function : Creates a Vertical Group.

Example :

```
MUIAddObjVGroup 0,5
MUICreateVGroup 0
```

See also :

```
MUIAddObjHGroup
```

```
MUIAddObjsVGroup
```

1.61 MUIAddObjPage To MUIObject#,MUIObject#

MUIAddObjPage

Modes : Amiga

Syntax : MUIAddObjPage To MUIObject#,MUIObject#

Function : Adds the object (MUIObject#) to the Register Page (To MUIObject#).

Example :

```
MUIAddObjPage 0,5
```

See also :

MUICreatePage

MUIAddObjsPage

1.62 MUICreatePage MUIObject# ,Page1\$ [,Page2\$...] | &Page\$(0)

MUICreatePage

Modes : Amiga

Syntax : MUICreatePage MUIObject# ,Page1\$ [,Page2\$...] | &Page\$(0)

Function : Creates a Page.

Example :

```
MUIAddObjPage 0,5
MUIAddObjPage 0,6
MUICreatePage 0,"Page1","Page2"
```

or

```
MUIAddObjsPage 0,5,6
MUICreatePage 0,"Page1","Page2"
```

See also :

MUIAddObjPage

MUIAddObjsPage

1.63 MUIAddObjsHGroup To MUIObject#,MUIObject# [,MUIObject# [...]]

MUIAddObjsHGroup

Modes : Amiga

Syntax : MUIAddObjsHGroup To MUIObject#,MUIObject# [,MUIObject# [...]]

Function : Adds the objects specified to the Horizontal Group (To MUIObject#).

Example :

```
MUIAddObjsHGroup 0,1,2,3,4,5,8
```

See also :

```
MUICreateHGroup
```

```
MUIAddObjHGroup
```

1.64 MUIAddObjsVGroup To MUIObject#,MUIObject# [,MUIObject# [...]]

```
MUIAddObjsVGroup
```

Modes : Amiga

Syntax : MUIAddObjsVGroup To MUIObject#,MUIObject# [,MUIObject# [...]]

Function : Adds the objects specified to the Vertical Group (To MUIObject#).

Example :

```
MUIAddObjsVGroup 0,1,2,3,4,5,8
```

See also :

```
MUICreateVGroup
```

```
MUIAddObjVGroup
```

1.65 MUIAddObjsPage To MUIObject#,MUIObject# [,MUIObject# [...]]

```
MUIAddObjsPage
```

Modes : Amiga

Syntax : MUIAddObjsPage To MUIObject#,MUIObject# [,MUIObject# [...]]

Function : Adds the objects specified to the Register Page (To MUIObject#).

Example :

```
MUIAddObjsPage 0,1,2,3,4,5,8
```

See also :

```
MUICreatePage
```

```
MUIAddObjPage
```

1.66 MUIInsertSingle MUIObject#,Position, Entry\$ [,Entry\$...] | *Array

```
MUIInsertSingle
```

Modes : Amiga

Syntax : MUIInsertSingle MUIObject#,Position, Entry\$ [,Entry\$...] | *Array

Function : Inserts a line in a list.

Example :

```
MUIInsertSingle 6,5,"Col#1","And #2","Here : #3"
```

See also :

MUIList

MUIRemoveSingle

MUIRedrawSingle

MUIListTitle

1.67 MUIRemoveSingle MUIObject#,Position

MUIRemoveSingle

Modes : Amiga

Syntax : MUIRemoveSingle MUIObject#,Position

Function : Removes a line in a list.

Example :

```
MUIRemoveSingle 6,4
```

See also :

MUIList

MUIInsertSingle

MUIRedrawSingle

MUIListTitle

1.68 MUIRedrawSingle MUIObject#,Position

MUIRedrawSingle

Modes : Amiga

Syntax : MUIRedrawSingle MUIObject#,Position

Function : Redraws a line in a list.

Example :

```
MUIRedrawSingle 6,5
```

See also :

```
MUIList  
MUIInsertSingle  
MUIRemoveSingle  
MUIListTitle
```

1.69 MUIListTitle MUIObject#, Title\$ [,Title\$...] | *Array

```
MUIListTitle
```

```
Modes      : Amiga  
Syntax     : MUIListTitle MUIObject#, Title$ [,Title$...] | *Array
```

Function : Changes the title(s) of a list.

Example :

```
MUIListTitle 6, "First", "Second", "Third..."
```

See also :

```
MUIList  
MUIInsertSingle  
MUIRemoveSingle  
MUIRedrawSingle
```

1.70 MUISet MUIObject#, &TagList | Attr,Value [,Attr,Value...]

```
MUISet
```

```
Modes      : Amiga  
Syntax     : MUISet MUIObject#, &TagList | Attr,Value [,Attr,Value...]
```

Function : Changes an attribute of an object.

Example :

```
MUISet 4, #MUIA_ShowMe, 0
```

See also :

```
MUIGet
```

1.71 MUIGet (MUIObject#,Attribute)

MUIGet

Modes : Amiga
 Syntax : MUIGet (MUIObject#,Attribute)
 Function : Returns the value of the attribute.
 Example :
 act.l=MUIGet (6,#MUIA_List_Active)
 See also :
 MUISet

1.72 MUIDoMethod MUIObject#, Method,Tag [,Tag] | &TagList

MUIDoMethod

Modes : Amiga
 Syntax : MUIDoMethod MUIObject#, Method,Tag [,Tag] | &TagList
 Function : Executes the method specified for the object.
 Example :
 MUIDoMethod 10,#MUIM_Window_ToBack
 See also :

1.73 MUINotify MUIObject#,Tag,Value,MUIObject#, Tag [,Tag...] | &TagList

MUINotify

Modes : Amiga
 Syntax : MUINotify MUIObject#,Tag,Value,MUIObject#, Method,Tag [,Tag...] | ↔
 &TagList
 Function : When the value of the tag of the first object is equal to Value,
 then MUI will executes the Method for the second object.
 Example :
 MUINotify 4,#MUIA_Pressed,0,11,#MUIM_Application_ReturnID,#ID_BUTTONON
 Repeat
 ev.l=MUIWaitEvent
 If ev=#ID_BUTTONON
 MUIRequest 10,"Info","OK","Button has been released"
 EndIf
 Until ev=-1

N.B. : For this example, MUINotifyApp is better.

See also :

MUIEvent

MUIWaitEvent

MUINotifyApp

1.74 MUINotifyApp MUIObject#,Tag,Value,ReturnID

MUINotifyApp

Modes : Amiga

Syntax : MUINotifyApp MUIObject#,Tag,Value,ReturnID

Function : When the value of the tag of the first object is equal to Value, then The ReturnID will be sent to the application.

Example :

```
MUINotifyApp 4, #MUIA_Pressed, 0, #ID_BUTTON
```

```
Repeat
```

```
  ev.l=MUIWaitEvent
```

```
  If ev=#ID_BUTTON
```

```
    MUIRequest 10, "Info", "OK", "Button has been released"
```

```
  EndIf
```

```
Until ev=-1
```

See also :

MUIEvent

MUIWaitEvent

MUINotify

1.75 MUIEvent

MUIEvent

Modes : Amiga

Syntax : =MUIEvent

Function : It is the same as Event but for MUI.

Example :

```
ev.l=MUIEvent
```

See also :

MUIWaitEvent

1.76 MUIWaitEvent

MUIWaitEvent

Modes : Amiga
Syntax : =MUIWaitEvent

Function : It is the same as WaitEvent but for MUI.

Example :

```
ev.l=MUIWaitEvent
```

See also :

MUIEvent

1.77 MUIFindUDData To MUIObject#,MUIObject#,UserData

MUIFindUDData

Modes : Amiga
Syntax : MUIFindUDData To MUIObject#,MUIObject#,UserData

Function : Please see the autodoc MUI_Notify.

Example :

```
MUIFindUDData 21,20,#MEN_PROJECT
```

See also :