Snaglt User's Manual

(Shareware Version)

Version 2.0

for Microsoft Windows 3.x

TechSmith Corporation

Copyright

© Copyright 1990-1992 TechSmith Corporation. All Rights Reserved.

No part of this manual may be reproduced or transmitted in any form by any means, electronic or mechanical, including photocopying and recording for any purpose without the written consent of TechSmith Corporation.

Snaglt was created by Stewart Nutter and Tim Pearl

Snaglt is a trademark of TechSmith Corporation.

Microsoft is a registered trademark and Windows is a trademark of Microsoft.

SQLWindows is a registered trademark of Gupta Technologies, Inc.

ToolBook is a registered trademark of Asymetrix Corporation.

HP LaserJet is a registered trademark of Hewlett-Packard.

POSTSCRIPT is a registered trademark of Adobe Systems.

IBM is a registered trademark of IBM Corporation.

License Agreement

This SOFTWARE LICENSE AGREEMENT is a legal agreement between you, the Customer, and TECHSMITH CORPORATION. By using this program, you are agreeing to the terms of this License Agreement. If you cannot accept the terms of this License Agreement, return the program to the place of purchase for a full refund.

TECHSMITH grants the Customer the right to use this copy of the software program and related materials, including written materials, binders, and other containters (hereinafter the "SOFTWARE") on a single computer system (i.e. single CPU). The Customer may physically transfer the SOFTWARE from one computer system to another, provided that the SOFTWARE is used on only one computer system at a time. The Customer owns the magnetic or other physical media on which the SOFTWARE is recorded, but TECHSMITH retains ownership of the SOFTWARE. The Customer agrees to use reasonable efforts to protect the SOFTWARE from unauthorized use, modification, reproduction, distribution, and publication. The SOFTWARE is copyrighted, and all rights therein are reserved by TECHSMITH.

The Customer may make copies of the licensed software programs solely for backup purposes. The Customer must include the copyright notice on all backup copies. The copying of the accompanying materials is expressly forbidden.

The SOFTWARE is licensed to the Customer only. The Customer may not

Snaglt Users Manual (Write Version)

transfer any copy of the SOFTWARE to any person unless the Customer transfers all copies, including the original, and advises TECHSMITH of the name and address of that person, who must sign a registration form and agree to the terms of the current license.

TECHSMITH may create updated versions of the SOFTWARE. At its option, TECHSMITH may make available such updates to those Customers who have returned the registration form and have paid the update fee.

TECHSMITH warrants the media on which the software programs are recorded to be free from defects for a period of thirty (30) days from the effective date of this agreement, and will replace without charge the media and recorded software programs if returned within the 30 day period provided the Customer has returned the registration form.

TECHSMITH CORPORATION DISCLAIMS ALL WARRANTIES RELATING TO THIS SOFTWARE, WHETHER EXPRESS OR IMPLIED, INCLUDING **BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF** MERCHANTABLILITY AND FITNESS FOR A PARTICULAR PURPOSE, AND ALL SUCH WARRANTIES ARE EXPRESSLY AND SPECIFICALLY DISCLAIMED. NEITHER TECHSMITH CORPORATION NOR ANYONE ELSE WHO HAS BEEN INVOLVED IN THE CREATION, PRODUCTION, OR DELIVERY OF THIS SOFTWARE SHALL BE LIABLE FOR ANY INDIRECT, CONSEQUENTIAL. OR INCIDENTAL DAMAGES ARISING OUT OF THE **USE OR INABILITY TO USE SUCH SOFTWARE EVEN IF TECHSMITH** CORPORATION HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES OR CLAIMS. IN NO EVENT SHALL TECHSMITH CORPORATION'S LIABILITY FOR ANY DAMAGES EVER EXCEED THE PRICE PAID FOR THE LICENSE TO USE THE SOFTWARE, REGARDLESS OF THE FORM OF CLAIM. THE PERSON USING THE SOFTWARE BEARS ALL RISK AS TO THE QUALITY AND PERFORMANCE OF THE SOFTWARE. Some states do not allow the exclusion of the limit of liability for consequential or incidental damages, so the above limitation may not apply to you.

This agreement shall be governed by the laws of the State of Michigan wnd shall inure to the benefit of TechSmith Corporation and any successors, administrators, heirs and assigns. Any action or proceeding brought by either party against the other arising out of or related to this agreement shall be brought only in a STATE or FEDERAL COURT of competent jurisdiction located in Ingham County, Michigan. The parties hereby consent to in personam jurisdiction of said courts.

This agreement cannot be modified by purchase order, or representations of anyone other than an agreement signed by an officer of TECHSMITH. This license agreement is governed by and interpreted in accordance with the laws of the state of Michigan.

Once you have read the SOFTWARE LICENSE AGREEMENT, and have agreed to its terms, please complete and return the Registration Form, so you will become a registered user. It is understood that by opening the sealed package that contains the licensed SOFTWARE, you show you acceptance of the SOFTWARE LICENSE AGREEMENT.

Should you have any questions concerning this agreement, please contact TECHSMITH CORPORATION, 1745 Hamilton Rd., Suite 300, Okemos, MI 48864 (517) 347-0800

Table of Contents (No page numbers in the Write Version)

Overview

About this Manual

Installation

Setup

Getting Started

Reference

Keyboard Operation and Mouse Controls

Input

Output

Format

Options

Save Setup

Dynamic Data Exchange (DDE)

Using DDE

Setting Snaglt Choices

Activating Snaglt

Snaglt's Status

Appendix A - Other TechSmith Products

DDEWatch

DDELib

Overview

Snaglt is the screen capture and print program for Microsoft Windows 3.0. With Snaglt, Windows users can capture an entire screen, a portion of the screen or a single window or icon. Snaglt sends the captured area to a printer, the Windows clipboard or a file. These images can be pasted into other Windows applications such as word processors and desktop publishing programs.

Snaglt provides a simple solution to the problem of importing high quality Windows screens into documentation. Snaglt is a practical, easy-to-use addition to the programs and tools utilized daily by Windows users.

Snaglt allows documentation writers to cut and paste Windows screens into user manuals, marketing literature, advertisements, newsletters, and other documents.

With Snaglt, Windows programmers can quickly create printouts of program screens, windows, and icons for presentation and review.

Snaglt provides screen print capabilities for other Windows programs. Programmers developing applications with Microsoft Excel macros, Gupta's SQLWindows, Asymetrix's ToolBook, and other tools, can activate Snaglt with dynamic data exchange (DDE) messages.

Snaglt provides DOS users with print screen capability for applications running in a DOS session under Microsoft Windows.

About this Manual

This manual shows you how to install and use SnagIt and is divided into three sections.

In the first section. *Installation*:

- Computer system requirements are listed.
- Setup instructions describe how to install and configure Snaglt.
- Getting Started teaches you the basic operation of Snaglt.

The second section, **Reference**:

- Describes program operation, menu selections, and options available in Snaglt.
- Keyboard operation and mouse controls.
- · Input, output, format, and option menus.
- Shows how to save the Snaglt's configuration.

Snaglt Users Manual (Write Version)

The third section, **Dynamic Data Exchange** (DDE):

- Explains how to use DDE messages.
 Contains the DDE reference that lists the DDE commands supported by Snaglt.

Appendix A of this manual lists other products available from TechSmith Corporation.

This manual was created using Snaglt and Microsoft Word for Windows.

Installation

To use Snaglt, you need:

- · An IBM PC or 100% Compatible
- Microsoft Windows 3.0
- · A mouse or other pointer device
- Any printer that supports bitmaps such as an HP LaserJet or a Postscript printer

To install Snaglt:

- 1. Insert the SnagIt diskette in drive A: or B:.
- 2. Start Microsoft Windows.
- 3. From the Windows Program Manager, choose Run from the File menu
- 4. On the command line type **a:setup** or **b:setup**, as appropriate
- 5. Press Enter.

The following dialog box is displayed.

(Not Shown in Write) The Snaglt installation dialog box

- 6. Enter your name and your company name in the User Information group box.
- 7. If you want Snaglt to load automatically when you start Windows, click on the check box in the Load information group box.
- 8. If you want to install Snaglt to the Window's default directory and the Accessories group, choose Ok.

If you wish to install Snaglt to a different directory or group than shown, enter the name of the new directory or group name and choose Ok.

Note: If you leave the group option blank, Snaglt is not installed in any group. In this instance, you can run Snaglt using the File Run command from the Windows Program Manager.

SnagIt Users Manual (Write Version)

Getting Started

In this section you will learn how to use several of the basic features of Snaglt and create your first screen print.

- 1. Start Microsoft Windows.
- 2. Pick on of the following:
 - a) If you configured SnagIt to load automatically during the setup step, you will see the SnagIt icon displayed at the bottom of your screen.
 - b) If you did not configure SnagIt to load automatically, load SnagIt by selecting the SnagIt icon from the group selected during Setup.
 - c) Execute File Run from the Program Manager and enter the path to Snaglt and press enter.

You can use Snaglt to print the entire screen, a selected region of the screen or a single window. Our Getting Started example will show you how to select the input and output choices to send a full screen to the printer.

First, restore Snaglt by selecting the Snaglt icon.

(Not Shown in Write)
Snaglt Main Screen

The Snaglt window shows the menu and the current settings for the program choices.

For our example select the **Input** menu item to view the list of Snaglt input choices and select **Screen** as the input region choice.

(Not Shown in Write)
Snaglt Input menu

Select the **Output** menu item to view the list of Snaglt output choices and select Printer as the output destination choice.

(Not Shown in Write)
Snaglt Output menu

To start the capture process, send the screen to the printer, press **[Ctrl] [Shift]P** simultaneously.

While Snaglt is busy printing the following message box is displayed.

Snaglt Users Manual (Write Version) (Not Shown in Write)

To cancel the printing operation, select the **Cancel** button in the message box. A message box will be displayed with the message "Output canceled by user." If the printout is canceled a portion of the image may have already been sent to the printer and will print.

To illustrate a second Snaglt feature, select **Region** from the Input menu choices.

Press [Ctrl][Shift]P simultaneously.

The cursor will change from an arrow to cross hairs. Use the cross hairs to select a region by holding down the left mouse button and dragging the cross hairs to the lower right corner of the region you wish to capture. Release the mouse button.

The region you selected will now be output to the printer.

Complete descriptions of the menu options are available in the **Reference** section of this manual.

Reference

This section of this manual describes the mouse buttons, keyboard commands, and the features and options of the Snaglt program.

The following command line arguments control Snaglt's startup.

/nokey or /n Disables keyboard input. For use with DDE.

/hide or /h Hide the SnagIt window at startup

A mouse is required when using Snaglt.

Left Button - The left mouse button is used to select Snaglt menu options and to select screen regions and windows.

Right Button - The right mouse button is used to cancel a region or window selection.

The following keyboard commands are used in the operation of Snaglt.

[Ctrl][Shift]P - Activates Snaglt printing.

[Ctrl][Shift]X - Makes the Snaglt icon or window disappear from the screen. Pressing **[Ctrl][Shift]X** a second time causes the icon or window to reappear.

This section describes the operation of each command on the Snaglt menu bar. The Snaglt menu bar has five choices: **Input**, **Output**, **Format**, **Options** and **Help**.

The **Input** option allows you to select the particular screen image, icon, window or bitmap file or clipboard content that you want Snaglt to capture.

The **Output** option allows you to select an output destination for images captured by Snaglt. Output options include the printer, a bitmap file, a monochrome TIFF file, or the Windows clipboard.

The **Format** option allows you to change how the Snaglt image will appear in finished form: monochrome, color, or gray scale.

The **Options** choice allows you to select from a number of additional

Snaglt Users Manual (Write Version) features offered by the Snaglt program including alert beeps, color boost, scaling, and clipboard chaining.

The **Help** option provides information about each menu selection.

Input

The **Input** menu is used to select the screen, window, or bitmap file or Windows clipboard content that you want Snaglt to capture.

(Not Shown in Write)
Snaglt Input menu

- 1. Select **Input** on the Snaglt menu.
- 2. Select from the following options.

Select **Screen** to capture the entire screen.

Select **Window Client Area** to capture only the client area of a single window. The client area is the content area inside the window borders. The client area does not include the borders, title bar, menu bar, scroll bars or the caption line.

After you press **[Ctrl][Shift]P**, select the client area you wish to capture by positioning the pointer anywhere in the client area.

Press and release the left mouse button.

Select **Entire Window** to capture a complete window including the borders, title bar, menu bar, scroll bars and the caption line.

After you press **[Ctrl][Shift]P**, select the window you want to print.

Press and release the left mouse button.

To select the window you want, not smaller windows such as buttons or icons, select the title bar. Items within a window, such as the Ok and Cancel buttons, are actually small windows. Therefore, if you select one of these items, that item will print, rather than the entire window.

Select **Region** to capture a rectangular region of the screen.

After pressing **[Ctrl][Shift]P**, position the pointer to the upper left corner of the region to capture. Press and hold the left mouse button while you drag the pointer to the lower right corner of the region. A rectangle starting at the upper left corner will follow the pointer, outlining the selected region.

Release the mouse button.

Select **BMP file** to capture an image stored in a bitmap file.

When you press **[Ctrl][Shift]P**, Snaglt displays a dialog box requesting the file name.

Enter the file name.

Choose Ok or press Enter.

Bitmap files are graphics files generated by some paint programs, Snaglt or other Windows programs. Bitmap files have a file extension of "BMP."

Select **Clipboard** to capture the contents of the Windows clipboard. Items are placed on the clipboard by using Snaglt or the cut and copy commands in other Windows programs.

Output

The **Output** menu is used to select the destination for the images captured by Snaglt. Snaglt supports the following destinations:

(Not Shown in Write)
Snaglt Output menu

Choose **Printer** to send the captured image to the currently selected Windows printer.

Choose **Clipboard** to send the captured image to the Windows Clipboard.

Choose **BMP File** to send the captured image to a bitmap file.

Choose **TIF Mono File** to send the captured image to a TIFF file in the Intel format.

Note: To select **TIF Mono File**, you must first select monochrome or gray scale from the Format menu.

After you capture an image, Snaglt displays the following dialog box asking for a file name.

(Not Shown in Write)

Enter a filename.

Choose Ok or press Enter.

Format

Snaglt provides three different format options: Mono-chrome, Color, and Gray Scale. Select the format choice from the Format menu.

(Not Shown in Write)
Snaglt Format menu

The following format choices are provided.

The input image is converted to monochrome before it is sent to the output destination. The intensity threshold level determines the amount of black and white that will appear in the output image.

When you select **Monochrome**, the following dialog box for setting the Intensity Threshold is displayed.

(Not Shown in Write)
Intensity Threshold dialog box

When Microsoft Windows converts a color image to monochrome, it converts the background color to white. All other colors are converted to black. As a result, too much of the image is now black. To prevent this, Snaglt uses an intensity threshold to control the ratio of black and white resulting from the conversion process.

Snaglt looks at the intensity level of each pixel and converts higher intensities (lighter colors) to white and lower intensities (darker colors) to black. This conversion process usually results in a more even balance of black and white in the output image. The amount of black and white is controlled by adjusting the Intensity Threshold value.

All color information for the selected image is sent to the output device

Gray scaling is an alternative to monochrome conversion. When **Gray Scale** is selected, colors are represented by shades of gray.

Snaglt can represent colors with 256 levels of gray. The shades of gray are determined by the intensity level of the colors.

Caution: Gray scaling is a pixel by pixel process and can be very slow. You may want to experiment with gray scaling by printing a small region of the screen before printing the whole screen. You may also want to enable the

Snaglt Users Manual (Write Version) **Alert** feature under the **Options** menu to let you know when the gray scaling process is completed.

Options

The **Options** menu provides additional features for Snaglt users: **Alert**, **Clipboard Chain**, **Color Boost**, and **Scale**.

(Not Shown in Write)
Snaglt Options menu

Set the **Alert** option to have Snaglt signal you with a beep(s) when it has completed processing. There is an alert option for both input and output processing. The values entered for these fields determine the number of beeps. This feature is particularly useful when using the **Gray Scale** option.

(Not Shown in Write)
Alert dialog box

Setting the **Clipboard Chain** option causes Snaglt to print each time new information is sent to the clipboard.

Clipboard chaining is useful for printing a screen from a DOS session. When you press the **[Print Scrn]** key in a

DOS box, Windows copies the screen to the clipboard. If you have selected the clipboard chain option, Snaglt automatically copies the image to the printer for you.

Note: To select **Clipboard Chain**, the input device must be set to **Clipboard**, and output device must be set to **Printer**.

Color Boost is used to adjust the color intensities for red, green, and blue portions of each pixel. This option may be used for color separation, brightening, or darkening the output image. When **Color Boost** is selected, a dialog box is displayed for color boost values.

(Not Shown in Write)
Color Boost dialog box

You may control the intensity for each pixel in two ways.

- 1. Increase or decrease intensity levels of each color by a percentage (saturation) by using the slider bar.
- 2. Add or subtract intensity levels (hue) for each color range by entering a value from -255 to 255.

Snaglt Users Manual (Write Version)

The default value for each additive range is zero and the percentage bar is 100%.

To activate color boost, click on the "Use Color Boost?" check box.

Color boost is used to change the intensity of the colors. Increasing the boost value lightens the output. Snaglt performs color boost before gray scaling or monochrome conversion. Therefore you can use color boost to lighten or darken the output with those options as well.

The **Scale** option allows you to enter an integer scaling factor that is applied to the input image. With a scaling factor of 2 the output image will be double the size of the input image in dots. With a 300 dpi laser printer, a scale of three (3) is a good place to start.

(Not Shown in Write)
Scale dialog box

Save Setup

Snaglt can save all of the currently selected options from each Snaglt menu. The **Save Setup** option is located under the **System Menu**.

(Not Shown in Write)
Snaglt System menu

You can access the **System Menu** by pressing **[Alt][Space]** or by selecting the **Close Box** (minus sign) in the upper left corner of the Snaglt window.

Save the current configuration by choosing **Save Setup** from the **System Menu**.

When you save the setup, Snaglt writes all of the current settings to your WIN.INI file. Snaglt then uses the saved setup each time it is loaded until you save different settings.

Dynamic Data Exchange

Snaglt supports Windows Dynamic Data Exchange (DDE). You can invoke Snaglt from other Windows programs by sending Snaglt DDE Messages. For instance, you can write an Excel macro that will print a portion of the screen using Snaglt. For more information concerning please see the DDE section in the Software Developer's Kit reference book "Windows Guide to Programming."

To initiate a DDE session with Snaglt, send a DDE_INITIATE message with the application parameter of "Snaglt" and the topic parameter of "System".

Snaglt's DDE_EXECUTE **Set** command or DDE_POKE commands configures Snaglt's operation in the same fashion as though choices were being selected from the menus.

Usage: DDE_EXECUTE

[set ("string")]

Usage: DDE POKE

"variable", "value"

Example: Set the **Input** menu choice to **Region**.

[set ("input region")] (DDE EXECUTE)

"input", "region" (DDE POKE)

The parameter **string** must be one of the following strings. The variable names are italicized.

input window (input = entire window)

scale n (option scale = integer > 0)
output printer (output = current printer)

Snaglt Users Manual (Write Version)

chain bool (option chain = True or False)
boost red, green, blue (option boost = Enabled)
boost off (option boost = Disabled)

add red, green, blue
add off
inalert n

(option boost = Enabled)
(option boost = Disabled)
(option alert input = value)

outalert n (option alert output = value)

window hide (hide SnagIt)
window show (unhides SnagIt)

Snaglt's capture process is started by sending a DDE_EXECUTE command with **Snag** message:

Usage:

[snag("string")]

Example: Snag the client window, handle 0x43B, to the selected destination

[Snag ("client handle 0x43B")]

The *string* parameter must be one of the following:

empty or null (equivalent to [Ctrl][Shift]P)

clipboard (get image from the clipboard)

screen (get the image from the screen)

filename (get image from BMP file)

x y (get entire window under the point)
client x y (get client window under the point)
handle h (get entire window from handle)

client handle *h* (get client window from handle)

tx ty bx by (get region between two points)

exit (terminate Snaglt)

Note: All numbers may be decimal or hexadecimal. Hex values must start with "0x."

Getting Snaglt's status is accomplished by using sending a DDE_REQUEST command with **Status**. Snaglt will return either **Ready** or **Busy**.

Ready: Snaglt is ready for another command.

Busy: Snaglt is currently processing the last command

Appendix A DDE Watch

Dynamic Data Exchange Monitor

Dynamic Data Exchange (DDE) is the way that today's powerful Windows applications communicate. Until now, you could not monitor these DDE messages or validate your DDE macros and programs. Now there is DDEWatch, a tool to let you see DDE. With DDEWatch you can scrutinize each DDE message, concentrate on selected DDE sessions, learn the DDE protocol, and improve the quality of your code.

View DDE Messages in Detail

DDEWatch gives you a window into the world of DDE messages. With it, you can view the details of any DDE message. DDEWatch displays the message type (e.g. initiate or ack). The name of the application, topic, or item and the symbolic name of each bit-flag are also displayed. You can even see the data in execute, poke, and data messages.

Locate Active DDE Sessions

Frequently DDE sessions run simultaneously which can be confusing. But DDEWatch provides you with a list of all active sessions. From this list, you may select to view messages for only those sessions in which you are interested.

Learn DDE

With DDEWatch you can learn the DDE protocol by observing interactions between programs like Excel and Word for Windows. You will see how the initiate is broadcast to all applications, how an advise is usually followed by a request, and how two applications negotiate a common data format.

Improve Program Quality

Using DDEWatch, you can improve the quality of the macros and programs you write. For example, you can verify that the flags are set correctly, the memory has been properly allocated, and the data is correct. Then you can document this quality by logging the DDE messages into a file.

Page 23

DDELib

A Library for Implementing DDE

DDELib is a dynamic link library for Microsoft Windows 3.0 programmers who are developing dynamic data exchange (DDE) applications. This library provides a set of software functions that implement the complex details of the DDE protocol. By using DDELib, application developers can quickly and easily generate powerful DDE software.

Saves Time

DDELib saves time because it frees programmers from many details of the DDE protocol. Memory management tasks are simplified, and the need to process DDE messages, issue acknowledgements, or handle atoms is eliminated. As a result, programmers can concentrate on processing data, not DDE.

Easy to Use

DDELib reduces complex tasks to simple function calls by providing an intuitive application program interface. For example, the code fragment: hDDE=DDEInitiate("Excel","sheet1");

initiates a DDE session with Microsoft's Excel. All functions provided by DDELib are clearly documented, making DDELib easy to use.

Powerful DDE Support

DDELib performs advanced DDE communications. For example, DDELib supports the *fAckReq* flow control strategy, the *fDeferUpd* warm and hot links, and any valid setting of the *fRelease* memory management scheme. DDELib provides functionality beyond the DDE protocol, including a facility to keep track of active advise circuits, which is useful for developing DDE server applications.

Includes Sample Programs

Sample programs included with DDELib illustrate how to use the library to build client and server applications. For example, *AccExcel* demonstrates how to interface with Excel, while *Session* and *SessUtil* show how to build a server application that supports multiple clients. The versatility of DDELib is shown by *Sub*, which operates a submarine in a fish tank.

Page 24