



Help for IniCon

IniCon is a Visual Basic custom control that will make access to [INI files](#) easier.

[About/Copyright](#)

[Getting Custom Controls Written](#)

[Usage](#)

[Layout](#)

[Properties](#)

Usage

Reading from WIN.INI

Set Filename property to blank

Set Application property to the name of the application section in WIN.INI

Set Parameter property to the name of the entry within the section

Read value in Value property (it now contains the value of the profile string specified by Application and Parameter)

Writing to WIN.INI

Set Filename property to blank

Set Application property to the name of the application section in WIN.INI

Set Parameter property to the name of the entry within the section

Write value into Value property (this will write the value given into the profile string specified by Application and Parameter)

Deleting an application in WIN.INI

Set Filename property to blank

Set Application property to the name of the application section in WIN.INI

Set DeleteApp property to True

Deleting a property in WIN.INI

Set Filename property to blank

Set Application property to the name of the application section in WIN.INI

Set Parameter property to the name of the entry within the section

Set DeleteParm property to True

Reading from a private INI file

Set Filename property to the path and filename of the private INI file

Set Application property to the name of the application section in the private INI file

Set Parameter property to the name of the entry within the section

Read value in Value property (it now contains the value of the profile string specified by Filename, Application and Parameter)

Writing to a private INI file

Set Filename property to the path and filename of the private INI file

Set Application property to the name of the application section in the private INI file

Set Parameter property to the name of the entry within the section

Write value into Value property (this will write the value given into the profile string specified by Filename, Application and Parameter)

Deleting an application in a private INI file

Set Filename property to blank

Set Application property to the name of the application section in the private INI file

Set DeleteApp property to True

Deleting a property in a private INI file

Set Filename property to the path and filename of the private INI file

Set Application property to the name of the application section in the private INI file

Set Parameter property to the name of the entry within the section

Set DeleteParm property to True

Layout

If you look in an INI file (WIN.INI is a good example) you'll see many profile strings broken up into sections. Section headers are formatted as follows:

[Application Name]

In each section there are profile strings. Each profile string is identified by a an entry name. These lines are formatted as such:

Parameter=Value

Properties

IniCon supports most of the usual control properties. On top of those, here are the additional properties that IniCon supports:

Application

DeleteApp

DeleteParm

Filename

Parameter

Value

DeleteApp Property

Description

Deletes an application from an INI file.

Usage

[*form.*][*label.*]DeleteApp[= *delete*]

Remarks

This property, when set to True, deletes the specified application from the INI file. The property deleted is determined by setting the Filename and Application properties.

Data Type

Integer (boolean)

DeleteParm Property

Description

Deletes a property from an INI file.

Usage

[*form.*][*label.*]DeleteParm[= *delete*]

Remarks

This property, when set to True, deletes the specified property from the INI file. The property deleted is determined by setting the Filename, Application, and Parameter properties.

Data Type

Integer (boolean)

Parameter Property

Description

Sets filename of INI file to use.

Usage

[*form.*][*label.*]Parameter[= *parameter*\$]

Remarks

This property determines which line in an application section of an INI file to use. This property must be non-blank. When a new value is written to this property the value specified by this property, Filename, and Application, is read into the Value property.

Data Type

String

Filename Property

Description

Sets filename of INI file to use.

Usage

[*form.*][*label.*]Filename[= *filename\$*]

Remarks

This property determines if IniCon uses a private INI file or WIN.INI. If this property is blank, profile strings are read from and written to WIN.INI. If this field is not blank, profile strings are written to and read from the file specified in this property.

When a new value is written to this property the value specified by this property, Parameter, and Application, is read into the Value property.

Data Type

String

Application Property

Description

Specifies what part of the INI file to use.

Usage

[*form.*][*label.*]Application[= *application\$*]

Remarks

This property determines which application section of an INI file to use. This property must be non-blank. When a new value is written to this property the value specified by this property, Filename, and Parameter, is read into the Value property.

Data Type

String

Value Property

Description

Value of profile string identified by Filename, Application and Parameter properties.

Usage

[form.][label.]Value[= Value\$]

Remarks

This property serves two purposes: to read the value of a profile string from an INI file, and to write a profile string to an INI file. When a program reads this property, the profile string is read from the INI file. When a program writes to this property, the value written is put into the INI file specified.

Data Type

String

INI Files

An INI file contains profile strings. Windows programs keep configuration and other pieces of static data them. INI files are managed by the Windows API functions `GetProfileString`, `WriteProfileString`, `GetPrivateProfileString`, and `WritePrivateProfileString`.

About IniCon

IniCon was written by James Shields. Inquiries can be sent to 71231,2066 on CompuServe, or mabry@halycon.com on Internet. If you must send something via U.S. Mail, the address is:

James Shields
Mabry Software
P.O. Box 31926
Seattle, WA 98103-1926

You can register this program by sending \$5 (\$10 for international orders) and your address. CompuServe members may register by sending \$3 and their account number (the registered version will be E-mailed to you). CompuServe members may also register this package by going to the SWREG forum. INICON is registered there. INICON's registration ID number is 833.

Source code to this control is available for \$25 (\$30 for international orders). With source code you get a registered version of the control. If you are a CompuServe member, you may get the source code in the Software Registration forum (GO SWREG). It's registration number is 1003.

(C) Copyright 1992-1993 by James Shields



Getting Custom Controls Written

If you or your organization would like to have custom controls written, contact either me or Zane Thomas (co-author of the Waite Group's VB How-To, 2nd Edition). Here's how we can be reached:

James Shields
CompuServe: 71231,2066
US Mail: P.O. Box 31926; Seattle, WA 98103-1926

Zane Thomas:
CompuServe: 72060,3327
US Mail: P.O. Box 300; Indianola, WA 98342