

**User's Guide  
to  
pcl-cvs - the Emacs Front-End to CVS**

release 1.02

Per Cederqvist

last updated 29 Mar 1992

Copyright © 1992 Per Cederqvist

Permission is granted to make and distribute verbatim copies of this manual provided the copyright notice and this permission notice are preserved on all copies.

Permission is granted to copy and distribute modified versions of this manual under the conditions for verbatim copying, provided also that the section entitled “GNU General Public License” is included exactly as in the original, and provided that the entire resulting derived work is distributed under the terms of a permission notice identical to this one.

Permission is granted to copy and distribute translations of this manual into another language, under the above conditions for modified versions, except that the section entitled “GNU General Public License” and this permission notice may be included in translations approved by the Free Software Foundation instead of in the original English.

# GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright © 1989, 1991 Free Software Foundation, Inc.  
675 Mass Ave, Cambridge, MA 02139, USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

## Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software—to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

## TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

1. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The “Program”, below, refers to any such program or work, and a “work based on the Program” means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term “modification”.) Each licensee is addressed as “you”.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

2. You may copy and distribute verbatim copies of the Program’s source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

3. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:
  - a. You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.
  - b. You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.
  - c. If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

4. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:
  - a. Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
  - b. Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
  - c. Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

5. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.
6. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

7. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.
8. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

9. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.
10. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.  
Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.
11. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software

which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

## **NO WARRANTY**

12. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.
13. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

## **END OF TERMS AND CONDITIONS**

## Appendix: How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the “copyright” line and a pointer to where the full notice is found.

```
one line to give the program's name and a brief idea of what it does.
Copyright (C) 19yy name of author
```

```
This program is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.
```

```
This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.
```

```
You should have received a copy of the GNU General Public License
along with this program; if not, write to the Free Software
Foundation, Inc., 675 Mass Ave, Cambridge, MA 02139, USA.
```

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) 19yy name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type 'show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type 'show c' for details.
```

The hypothetical commands ‘show w’ and ‘show c’ should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than ‘show w’ and ‘show c’; they could even be mouse-clicks or menu items—whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a “copyright disclaimer” for the program, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program
'Gnomovision' (which makes passes at compilers) written by James Hacker.
```

```
signature of Ty Coon, 1 April 1989
Ty Coon, President of Vice
```

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.



# 1 Installation

This section describes the installation of `pcl-cvs`, the GNU Emacs CVS front-end. You should install not only the elisp files themselves, but also the on-line documentation so that your users will know how to use it. You can create typeset documentation from the file `pcl-cvs.texinfo` as well as an on-line info file. The following steps are also described in the file `INSTALL` in the source directory.

## 1.1 Installation of the `pcl-cvs` program

1. Edit the file `Makefile` to reflect the situation at your site. The only things you have to change is the definition of `lispdir` and `infodir`. The elisp files will be copied to `lispdir`, and the info file to `infodir`.
2. Configure `pcl-cvs.el`

There are a couple of paths that you have to check to make sure that they match you system. They appear early in the file `pcl-cvs.el`.

**NOTE:** If your system is running emacs 18.57 or earlier you **MUST** uncomment the line that says:

```
(setq delete-exited-processes nil)
```

Setting `delete-exited-processes` to `nil` works around a bug in emacs that causes it to dump core. The bug was fixed in emacs 18.58.

3. Type `'make install'` in the source directory. This will byte-compile all `.el` files and copy both the `.el` and the `.elc` into the directory you specified in step 1.

If you don't want to install the `.el` files but only the `.elc` files (the byte-compiled files), you can type `"make install_elc"` instead of `"make install"`.

If you only want to create the compiled elisp files, but don't want to install them, you can type `'make elcfiles'` instead. This is what happens if you only type `'make'` without parameters.

4. Edit the file `default.el` in your emacs lisp directory (usually `/usr/gnu/emacs/lisp` or something similar) and enter the contents of the file `pcl-cvs-startup.el` into it. It contains a couple of `auto-loads` that facilitates the use of `pcl-cvs`.

## 1.2 Installation of the on-line manual.

1. Create the info file `pcl-cvs` from `pcl-cvs.texinfo` by typing `'make info'`. If you don't have the program `'makeinfo'` you can get it by anonymous ftp from e.g. `'ftp.gnu.ai.mit.edu'` as `pub/gnu/texinfo-2.14.tar.Z` (there might be a newer version there when you read this), or you could use the preformatted info file `pcl-cvs.info` that is included in the distribution (type `'cp pcl-cvs.info pcl-cvs'`).
2. Move the info file `pcl-cvs` to your standard info directory. This might be called something like `/usr/gnu/emacs/info`.
3. Edit the file `dir` in the info directory and enter one line to contain a pointer to the info file `pcl-cvs`. The line can, for instance, look like this:

```
* Pcl-cvs: (pcl-cvs).      An Emacs front-end to CVS.
```

### 1.3 How to make typeset documentation from `pcl-cvs.texinfo`

If you have `TEX` installed at your site, you can make a typeset manual from `pcl-cvs.texinfo`.

1. Run `TEX` by typing “`make pcl-cvs.dvi`”. You will not get the indices unless you have the `texindex` program.
2. Convert the resulting device independent file `pcl-cvs.dvi` to a form which your printer can output and print it. If you have a postscript printer there is a program, `dvi2ps`, which does. There is also a program which comes together with `TEX`, `dvips`, which you can use.

## 2 About `pcl-cvs`

`Pcl-cvs` is a front-end to CVS version 1.3. It integrates the most frequently used CVS commands into emacs.

### 2.1 Contributors to `pcl-cvs`

Contributions to the package are welcome. I have limited time to work on this project, but I will gladly add any code that you contribute to me to this package (see Chapter 8 [Reporting bugs and ideas], page 19).

The following persons have made contributions to `pcl-cvs`.

- Brian Berliner wrote CVS, together with some other contributors. Without his work on CVS this package would be useless. . .
- Per Cederqvist wrote most of the otherwise unattributed functions in `pcl-cvs` as well as all documentation.
- Inge Wallin (`inge@lysator.liu.se`) wrote the skeleton to `pcl-cvs.texinfo`, and gave useful comments on it. He also wrote the files `elib-node.el` and `compile-all.el`. The file `cookie.el` was inspired by Inge.
- Linus Tolke (`linus@lysator.liu.se`) contributed useful comments on both the functionality and the documentation.

### 2.2 Where can I get `pcl-cvs`?

This release of `pcl-cvs` is included in the CVS 1.3 distribution. However, since `pcl-cvs` has had less time to mature (the first line of code was written less than a year ago) it is likely that there will be a new release of `pcl-cvs` before the next release of CVS.

The latest release of `pcl-cvs` can be fetched via anonymous ftp from `ftp.lysator.liu.se`, (IP no. 130.236.254.1) in the directory `pub/emacs`. If you don't live in Scandinavia you should probably check with `archie` to see if there is a site closer to you that archives `pcl-cvs`.

New releases will be announced to appropriate newsgroups. If you send your email address to me I will add you to my list of people to mail when I make a new release.

### 3 Getting started

This document assumes that you know what CVS is, and that you at least knows the fundamental concepts of CVS. If that is not the case you should read the man page for CVS.

Pcl-cvs is only useful once you have checked out a module. So before you invoke it you must have a copy of a module somewhere in the file system.

You invoke pcl-cvs by typing *M-x pcl-cvs RET*. If your emacs responds with ‘[No match]’ your system administrator has not installed pcl-cvs properly. Try *M-x load-library RET pcl-cvs RET*. If that also fails - talk to your root. If it succeeds you might put this line in your `.emacs` file so that you don’t have to type the ‘load-library’ command every time you wish to use pcl-cvs:

```
(autoload 'cvs-update "pcl-cvs" nil t)
```

The function `cvs-update` will ask for a directory. The command ‘`cvs update`’ will be run in that directory. (It should contain files that have been checked out from a CVS archive.) The output from `cvs` will be parsed and presented in a table in a buffer called ‘`*cvs*`’. It might look something like this:

```
PCL-CVS release 1.02.

In directory /users/ceder/F00/test:
  Updated      bar
  Updated      file.txt
  Modified ci  namechange
  Updated      newer

In directory /users/ceder/F00/test/sub:
  Modified ci  ChangeLog
----- End -----
```

In this example the three files (`bar`, `file.txt` and `newer`) that are marked with ‘Updated’ have been copied from the CVS repository to `/users/ceder/F00/test/` since someone else have checked in newer versions of them. Two files (`namechange` and `sub/ChangeLog`) have been modified locally, and needs to be checked in.

You can move the cursor up and down in the buffer with *C-n* and *C-p* or *n* and *p*. If you press *c* on one of the ‘Modified’ files that file will be checked in to the CVS repository. See Section 5.4 [Committing changes], page 14. You can press *x* to get rid of the “uninteresting” files that have only been ‘Updated’ (and don’t require any further action from you).

You can also easily get a ‘diff’ between your modified file and the base version that you started from, and you can get the output from ‘`cvs log`’ and ‘`cvs status`’ on the listed files simply by pressing a key (see Section 5.6 [Getting info about files], page 14).

## 4 Buffer contents

The display contains four columns. They contain, from left to right:

- An asterisk when the file is *marked* (see Section 4.2 [Selected files], page 12).
- The status of the file. See Section 4.1 [File status], page 11, for more information.
- A "need to be checked in"-marker ('ci').
- The file name.

### 4.1 File status

The 'file status' field can have the following values:

'Updated' The file was brought up to date with respect to the repository. This is done for any file that exists in the repository but not in your source, and for files that you haven't changed but are not the most recent versions available in the repository.

'Modified' The file is modified in your working directory, and there was no modification to the same file in the repository.

'Merged' The file is modified in your working directory, and there were modifications in the repository as well as in your copy, but they were merged successfully, without conflict, in your working directory.

'Conflict' A conflict was detected while trying to merge your changes to *file* with changes from the source repository. *file* (the copy in your working directory) is now the output of the 'rcsmerge' command on the two versions; an unmodified copy of your file is also in your working directory, with the name *.#file.version*, where *version* is the RCS revision that your modified file started from. See Section 5.10 [Viewing differences], page 15, for more details.

'Added' The file has been added by you, but it still needs to be checked in to the repository.

'Removed' The file has been removed by you, but it needs to be checked in to the repository. You can resurrect it by typing *a* (see Section 5.7 [Adding and removing files], page 14).

'Unknown' A file that was detected in your directory, but that neither appears in the repository, nor is present on the list of files that CVS should ignore.

There are also a few special cases, that rarely occur, which have longer strings in the fields:

'Removed from repository' The file has been removed from your directory since someone has removed it from the repository. (It is still present in the Attic directory, so no permanent loss has occurred). This, unlike the other entries in this table, is not an error condition.

‘Removed from repository, changed by you’

You have modified a file that someone have removed from the repository. You can correct this situation by removing the file manually (see see Section 5.7 [Adding and removing files], page 14).

‘Removed by you, changed in repository’

You have removed a file, and before you committed the removal someone committed a change to that file. You could use `a` to resurrect the file (see see Section 5.7 [Adding and removing files], page 14).

‘Move away *file* - it is in the way’

For some reason CVS does not like the file *file*. Rename or remove it.

‘This repository is missing! Remove this dir manually.’

It is impossible to remove a directory in the CVS repository in a clean way. Someone have tried to remove one, and CVS gets confused. Remove your copy of the directory.

## 4.2 Selected files

Many of the commands works on the current set of *selected* files.

- If there are any files that are marked they constitute the set of selected files.
- Otherwise, if the cursor points to a file, that file is the selected file.
- Otherwise, if the cursor points to a directory, all the files in that directory that appears in the buffer are the selected files.

This scheme might seem a little complicated, but once one get used to it, it is quite powerful.

See Section 5.3 [Marking files], page 13, tells how you mark and unmark files.

## 5 Commands

This chapter describes all the commands that you can use in pcl-cvs.

### 5.1 Updating the directory

*M-x cvs-update*

Run a ‘`cvs update`’ command. You will be asked for the directory in which the ‘`cvs update`’ will be run. The output will be parsed by pcl-cvs, and the result printed in the ‘`*cvs*`’ buffer (see Chapter 4 [Buffer contents], page 11, for a description of the contents).

By default, ‘`cvs-update`’ will descend recursively into subdirectories. You can avoid that behavior by giving a prefix argument to it (e.g., by typing `C-u M-x cvs-update RET`).

All other commands in pcl-cvs requires that you have a ‘`*cvs*`’ buffer. This is the command that you use to get one.

*g* This will run ‘`cvs update`’ again. It will always use the same buffer that was used with the previous ‘`cvs update`’. Give a prefix argument to avoid descending into subdirectories. This runs the command ‘`cvs-update-no-prompt`’.

### 5.2 Movement Commands

You can use most normal Emacs commands to move forward and backward in the buffer. Some keys are rebound to functions that take advantage of the fact that the buffer is a pcl-cvs buffer:

*SPC*

*C-n*

*n* These keys move the cursor one file forward, towards the end of the buffer (`cookie-next-cookie`).

*C-p*

*p* These keys move one file backward, towards the beginning of the buffer (`cookie-previous-cookie`).

### 5.3 Marking files

Pcl-cvs works on a set of *selected files* (see Section 4.2 [Selected files], page 12). You can mark and unmark files with these commands:

*m* This marks the file that the cursor is positioned on. If the cursor is positioned on a directory all files in that directory will be marked. (`cvs-mark`).

*u* Unmark the file that the cursor is positioned on. If the cursor is on a directory, all files in that directory will be unmarked. (`cvs-unmark`).

*M* Mark *all* files in the buffer (`cvs-mark-all-files`).

*U* Unmark *all* files (`cvs-unmark-all-files`).

*DEL* Unmark the file on the previous line, and move point to that line (`cvs-unmark-up`).

## 5.4 Committing changes

- c** All files that have a "need to be checked in"-marker (see Chapter 4 [Buffer contents], page 11) can be checked in with the `c` command. It checks in all selected files (see Section 4.2 [Selected files], page 12) (except those who lack the "ci"-marker - they are ignored). Pressing `c` causes  `cvs-commit` to be run. When you press `c` you will get a buffer called `'*cvs-commit-message*`'. Enter the log message for the file(s) in it. When you are ready you should press `C-c C-c` to actually commit the files (using  `cvs-edit-done`).
- Normally the `'*cvs-commit-message*`' buffer will retain the log message from the previous commit, but if the variable  `cvs-erase-input-buffer` is set to a non-nil value the buffer will be erased. Point and mark will always be located around the entire buffer so that you can easily erase it with `C-w` (`'kill-region'`).

## 5.5 Editing files

There are currently three commands that can be used to find a file (that is, load it into a buffer and start editing it there). These commands work on the line that the cursor is situated at. They ignore any marked files.

- f** Find the file that the cursor points to. Run `'dired'` if the cursor points to a directory ( `cvs-find-file`).
- o** Like `f`, but use another window ( `cvs-find-file-other-window`).
- A** Invoke `'add-change-log-entry-other-window'` to edit a `'ChangeLog'` file. The `'ChangeLog'` will be found in the directory of the file the cursor points to. ( `cvs-add-change-log-entry-other-window`).

## 5.6 Getting info about files

Both of the following commands can be customized. See Chapter 6 [Customization], page 17.

- l** Run `'cvs log'` on all selected files, and show the result in a temporary buffer ( `cvs-log`).
- s** Run `'cvs status'` on all selected files, and show the result in a temporary buffer ( `cvs-status`).

## 5.7 Adding and removing files

The following commands are available to make it easy to add and remove files from the CVS repository.

- a** Add all selected files. This command can be used on `'Unknown'` files (see see Section 4.1 [File status], page 11). The status of the file will change to `'Added'`, and you will have to use `c` (`'cvs-commit'`, see see Section 5.4 [Committing changes], page 14) to really add the file to the repository.
- This command can also be used on `'Removed'` files (before you commit them) to resurrect them.



Selected files that are neither ‘Unknown’ nor ‘Removed’ will be ignored by this command.

The command that is run is `cvs-add`.

- r* This command removes the selected files (after prompting for confirmation). The files are ‘rm’ed from your directory and (unless the status was ‘Unknown’; see Section 4.1 [File status], page 11) they will also be ‘`cvs remove`’d. If the files were ‘Unknown’ they will disappear from the buffer. Otherwise their status will change to ‘Removed’, and you must use `c` (‘`cvs-commit`’, see Section 5.4 [Committing changes], page 14) to commit the removal.

The command that is run is `cvs-remove-file`.

## 5.8 Removing handled entries

- x* This command allows you to remove all entries that you have processed. More specifically, the lines for ‘Updated’ files (see Section 4.1 [File status], page 11, and files that have been checked in (see Section 5.4 [Committing changes], page 14) are removed from the buffer. If a directory becomes empty the heading for that directory is also removed. This makes it easier to get an overview of what needs to be done.

The command is called `cvs-remove-handled`. If ‘`cvs-auto-remove-handled`’ is set to non-‘nil’ this will automatically be performed after every commit.

- C-k* This command can be used for lines that ‘`cvs-remove-handled`’ would not delete, but that you want to delete (`cvs-acknowledge`).

## 5.9 Ignoring files

- i* Arrange so that CVS will ignore the selected files. The file names are added to the `.cvsignore` file in the corresponding directory. If the `.cvsignore` doesn’t exist it will be created.

The `.cvsignore` file should normally be added to the repository, but you could ignore it also if you like it better that way.

This runs `cvs-ignore`.

## 5.10 Viewing differences

- d* Display a ‘`cvs diff`’ between the selected files and the RCS version that they are based on. See Chapter 6 [Customization], page 17, describes how you can send flags to ‘`cvs diff`’. (The function that does the job is `cvs-diff-cvs`).

- b* If CVS finds a conflict while merging two versions of a file (during a ‘`cvs update`’, see Section 5.1 [Updating the directory], page 13) it will save the original file in a file called `.#FILE.VERSION` where `FILE` is the name of the file, and `VERSION` is the RCS version number that your file was based on.

With the `b` command you can run a ‘diff’ on the files `.#FILE.VERSION` and `FILE`. You can get a context- or Unidiff by setting ‘`cvs-diff-flags`’ - see Chapter 6 [Customization], page 17. This command only works on files that

have status 'Conflict' or 'Merged'. The name of the command is `cvs-diff-backup`.

## 6 Customization

If you have an idea about any customization that would be handy but isn't present in this list, please tell me! See Chapter 8 [Reporting bugs and ideas], page 19, for info on how to reach me.

### 'cvs-erase-input-buffer'

If set to anything else than 'nil' the edit buffer will be erased before you write the log message (see Section 5.4 [Committing changes], page 14).

### 'cvs-inhibit-copyright-message'

The copyright message that is displayed on startup can be annoying after a while. Set this variable to 't' if you want to get rid of it. (But don't set this to 't' in the system defaults file - new users should see this message at least once).

### 'cvs-cvs-diff-flags'

A list of strings to pass as arguments to the 'cvs diff' program. This is used by 'cvs-diff-cvs' (key *d*, see Section 5.10 [Viewing differences], page 15). If you prefer the Unidiff format you could add this line to your .emacs file:

```
(setq cvs-cvs-diff-flags '("-u"))
```

### 'cvs-diff-flags'

Like 'cvs-cvs-diff-flags', but passed to 'diff'. This is used by 'cvs-diff-backup' (key *b*, see Section 5.10 [Viewing differences], page 15).

### 'cvs-log-flags'

List of strings to send to 'cvs log'. Used by 'cvs-log' (key *l*, see Section 5.6 [Getting info about files], page 14).

### 'cvs-status-flags'

List of strings to send to 'cvs status'. Used by 'cvs-status' (key *s*, see Section 5.6 [Getting info about files], page 14).

### 'cvs-auto-remove-handled'

If this variable is set to any non-'nil' value 'cvs-remove-handled' will be called every time you check in files, after the check-in is ready. See Section 5.8 [Removing handled entries], page 15.

## 7 Future enhancements

Pcl-cvs is still under development and needs a number of enhancements to be called complete. Here is my current wish-list for future releases of pcl-cvs:

- Dired support. I have an experimental `dired-cvs.el` that works together with CVS 1.2. Unfortunately I wrote it on top of a non-standard `dired.el`, so it must be rewritten.
- It should be possible to run commands such as ‘`cvs log`’, ‘`cvs status`’ and ‘`cvs commit`’ directly from a buffer containing a file, instead of having to ‘`cvs-update`’. If the directory contains many files the ‘`cvs-update`’ can take quite some time, especially on a slow machine.

If you miss something in this wish-list, let me know! I don’t promise that I will write it, but I will at least try to coordinate the efforts of making a good Emacs front end to CVS. See See Chapter 8 [Reporting bugs and ideas], page 19, for information about how to reach me.

## 8 Reporting bugs and ideas

If you find a bug or misfeature, don't hesitate to tell me! Send email to 'ceder@lysator.liu.se'.

If you have ideas for improvements, or if you have written some extensions to this package, I would like to hear from you. I hope that you find this package useful!

## Function and Variable Index

<code>cookie-next-cookie</code> .....	13	<code>cv</code> s-inhibit-copyright-message (variable) .....	17
<code>cookie-previous-cookie</code> .....	13	<code>cv</code> s-log .....	14
<code>cv</code> s-acknowledge .....	15	<code>cv</code> s-log-flags (variable) .....	17
<code>cv</code> s-add .....	14	<code>cv</code> s-mark .....	13
<code>cv</code> s-add-change-log-entry-other-window.....	14	<code>cv</code> s-mark-all-files .....	13
<code>cv</code> s-auto-remove-handled (variable).....	17	<code>cv</code> s-remove-file .....	14
<code>cv</code> s-commit.....	14	<code>cv</code> s-remove-handled.....	15
<code>cv</code> s-cvs-diff-flags (variable).....	17	<code>cv</code> s-status.....	14
<code>cv</code> s-diff-backup.....	15	<code>cv</code> s-status-flags (variable) .....	17
<code>cv</code> s-diff-cvs.....	15	<code>cv</code> s-unmark .....	13
<code>cv</code> s-diff-flags (variable).....	17	<code>cv</code> s-unmark-all-files .....	13
<code>cv</code> s-erase-input-buffer (variable) .....	14, 17	<code>cv</code> s-unmark-up .....	13
<code>cv</code> s-find-file .....	14	<code>cv</code> s-update .....	13
<code>cv</code> s-find-file-other-window.....	14	<code>cv</code> s-update-no-prompt .....	13

# Concept Index

## A

About pcl-cvs .....	9
Active files .....	12
Added (file status) .....	11
Adding files .....	14
Archives .....	9
Author, how to reach .....	19
Authors .....	9
Automatically remove handled files .....	17

## B

Buffer contents .....	11
Bugs, how to report them .....	19

## C

Ci .....	14
Commit buffer .....	14
Committing changes .....	14
Conflict (file status) .....	11
Conflicts, how to resolve them .....	15
Context diff, how to get .....	17
Contributors .....	9
Copyright message, getting rid of it .....	17
Customization .....	17

## D

Deleting files .....	14
Diff. ....	15
Dired .....	14

## E

Edit buffer .....	14
Editing files .....	14
Email archives .....	9
Email to the author .....	19
Enhancements .....	18
Erasing commit message .....	14
Erasing the input buffer .....	17
Example run .....	10
Expunging uninteresting entries .....	15

## F

File selection .....	12
File status .....	11
Finding files .....	14
Ftp-sites .....	9

## G

Generating a typeset manual .....	8
Generating the on-line manual .....	7
Getting pcl-cvs .....	9
Getting rid of the Copyright message .....	17
Getting rid of uninteresting lines .....	15
Getting status .....	14

## H

Handled lines, removing them .....	15
------------------------------------	----

## I

Info-file (how to generate) .....	7
Inhibiting the Copyright message .....	17
Installation .....	7
Installation of elisp files .....	7
Installation of on-line manual .....	7
Installation of typeset manual .....	8
Introduction .....	10
Invoking dired .....	14

## L

Loading files .....	14
Log (RCS/cvs command) .....	14

## M

Manual installation (on-line) .....	7
Manual installation (typeset) .....	8
Marked files .....	12
Marking files .....	13
Merged (file status) .....	11
Modified (file status) .....	11
Move away <i>file</i> - it is in the way (file status) .....	11
Movement Commands .....	13

## O

On-line manual (how to generate) .....	7
--	---

## P

Printing a manual .....	8
Putting files under CVS control .....	14

**R**

Removed (file status) .....	11
Removed by you, changed in repository (file status) .....	11
Removed from repository (file status) .....	11
Removed from repository, changed by you (file status).....	11
Removing files .....	14
Removing uninteresting (processed) lines .....	15
Reporting bugs and ideas .....	19
Resurrecting files .....	14

**S**

Selected files .....	12
Selecting files (commands to mark files) .....	13
Sites .....	9
Status (cvs command) .....	14

**T**

TeX - generating a typeset manual .....	8
This repository is missing!... (file status) .....	11

**U**

Unidiff, how to get .....	17
Uninteresting entries, getting rid of them .....	15
Unknown (file status) .....	11
Updated (file status).....	11

**V**

Variables, list of all .....	17
Viewing differences.....	15



## Key Index

### A

a - add a file..... 14  
 A - add ChangeLog entry..... 14

### B

b - diff backup file..... 15

### C

c - commit files..... 14  
 C-k - remove selected entries..... 15  
 C-n - Move down one file..... 13  
 C-p - Move up one file..... 13

### D

d - run 'cvs diff'..... 15  
 DEL - unmark previous file..... 13

### F

f - find file or directory..... 14

### G

g - Rerun 'cvs update'..... 13

### L

l - run 'cvs log'..... 14

### M

m - marking a file..... 13  
 M - marking all files..... 13

### N

n - Move down one file..... 13

### O

o - find file in other window..... 14

### P

p - Move up on file..... 13

### R

r - remove a file..... 14

### S

s - run 'cvs status'..... 14  
 SPC - Move down one file..... 13

### U

u - unmark a file..... 13  
 U - unmark all files..... 13

### X

x - remove processed entries..... 15

## Short Contents

GNU GENERAL PUBLIC LICENSE .....	1
1 Installation .....	7
2 About pcl-cvs .....	9
3 Getting started .....	10
4 Buffer contents .....	11
5 Commands .....	13
6 Customization .....	17
7 Future enhancements .....	18
8 Reporting bugs and ideas .....	19
Function and Variable Index .....	20
Concept Index .....	21
Key Index .....	23

# Table of Contents

<b>GNU GENERAL PUBLIC LICENSE</b> .....	<b>1</b>
Preamble .....	1
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION .....	2
Appendix: How to Apply These Terms to Your New Programs .....	6
<b>1 Installation</b> .....	<b>7</b>
1.1 Installation of the pcl-cvs program .....	7
1.2 Installation of the on-line manual .....	7
1.3 How to make typeset documentation from pcl-cvs.texinfo .....	8
<b>2 About pcl-cvs</b> .....	<b>9</b>
2.1 Contributors to pcl-cvs .....	9
2.2 Where can I get pcl-cvs? .....	9
<b>3 Getting started</b> .....	<b>10</b>
<b>4 Buffer contents</b> .....	<b>11</b>
4.1 File status .....	11
4.2 Selected files .....	12
<b>5 Commands</b> .....	<b>13</b>
5.1 Updating the directory .....	13
5.2 Movement Commands .....	13
5.3 Marking files .....	13
5.4 Committing changes .....	14
5.5 Editing files .....	14
5.6 Getting info about files .....	14
5.7 Adding and removing files .....	14
5.8 Removing handled entries .....	15
5.9 Ignoring files .....	15
5.10 Viewing differences .....	15
<b>6 Customization</b> .....	<b>17</b>
<b>7 Future enhancements</b> .....	<b>18</b>
<b>8 Reporting bugs and ideas</b> .....	<b>19</b>

<b>Function and Variable Index</b> .....	<b>20</b>
<b>Concept Index</b> .....	<b>21</b>
<b>Key Index</b> .....	<b>23</b>